# Cisco Compute-Only C240 M8 Node Family

## Contents

Product overview ....2
Features ....5
Product specifications ....6
Ordering information ....7
Cisco services ....8
Product sustainability ....8
Cisco Capital ....8
Document history ....9

© 2026 Cisco and/or its affiliates. All rights reserved.
© Intel Corporation.

Cisco and Nutanix have partnered to introduce the IT industry's most complete hyperconverged solution by integrating and validating Cisco® servers, storage, networking, and SaaS operations with the Nutanix hybrid multicloud platform. Cisco Compute Hyperconverged with Nutanix is built, managed, and supported holistically to deliver a more seamless experience, foster innovation, and accelerate customers' hybrid-cloud journeys. Modern workloads require modern flexibility. Traditional hyperconverged solutions require scaling compute and storage together. When you need to scale compute capacity without adding storage, Cisco Compute-Only (CO) nodes provide that critical capability – empowering you to design clusters that match your exact requirements.

## Product overview



Figure 1. Cisco Compute-Only C240 M8 Node family

### A. Expanding Cisco Compute Hyperconverged node cluster with Cisco Compute-Only node

The Cisco Compute-Only node solution enables you to expand the compute resources of Cisco hyperconverged clusters running Nutanix by adding Cisco UCS®-certified servers without additional storage. These storage-less, Compute-Only (CO) servers certified by Cisco integrate seamlessly into your existing or new hyperconverged Nutanix cluster, allowing organizations to efficiently support compute intensive applications by scaling compute resources independently of storage infrastructure.

### Key benefits

- Cost-effective scaling for compute-heavy workloads
- Flexibility in cluster design

© 2026 Cisco and/or its affiliates. All rights reserved.
© Intel Corporation.

Table 1. Minimum cluster requirements for Cisco Compute-Only nodes

| Cluster attributes | Hyperconverged (HCI) node with Cisco Compute-Only node |
|---|---|
| **Number of nodes** | Minimum of 3 HCI nodes and minimum of 2 CO nodes |
| **Nodes ratio** | **Nutanix recommends the following nodes ratio:**<br>**1 CO: 2 HCI (default)**<br>**1 CO: 1 HCI (This is supported only when the total number of VMs is less than or equal to 128 times the number of HCI nodes.)** |
| **Hypervisor** | Hyperconverged node: Nutanix Acropolis Hypervisor (AHV) only<br>Compute-Only node: Nutanix Acropolis Hypervisor (AHV) only |
| **Management** | Cisco Intersight® Managed Mode (IMM)<br>Cisco Intersight® Standalone Mode (ISM) |
| **Licensing** | NCI licenses on a per-core basis<br>For more information about NCI licenses, see the NCI section in Nutanix Cloud Platform Software Options |
| **Nutanix Cloud Platform software** | The same as Cisco Compute Hyperconverged with Nutanix |

**B. Cisco Compute-Only node connected to Everpure Flash Array (FlashStack with Nutanix)**

Everpure FlashArray//X and FlashArray//XL delivers mission-critical performance with the efficiency and resiliency that's missing from legacy arrays. FlashArray //X and FlashArray//XL packs more IOPS, ultra- consistent latency, and greater scale into a smaller footprint. Nondisruptive upgrades, always-on availability, and built-in data protection ensure workloads are always running while cutting risk. FlashArray//XL is designed to provide the highest performance density with a level of operational and management simplicity. FlashArray//C™ delivers a balanced all-flash storage solution optimized for file services and general-purpose workloads. With predictable performance, streamlined operations, and built-in cyber resiliency, it keeps applications consistently secure and positions organizations to outperform capacity-optimized, all-flash, and hybrid storage alternatives.

Nutanix Cloud Platform (NCP) consolidates computing, storage, and networking into a unified pool. It uses Nutanix Acropolis Operating System (AOS) for storage, Nutanix (Acropolis Hypervisor (AHV) for virtualization, and Prism Central for centralized management across environments.

The Cisco Compute-Only node with Nutanix Cloud Platform (NCP) and Everpure FlashArray solution delivers a disaggregated infrastructure architecture that enables independent scaling of compute and storage resources. This solution combines industry-standard Cisco Compute-Only node servers running Nutanix AHV and AOS connected to external Everpure FlashArray. This architecture leverages Everpure software-defined storage environment optimized for enterprise workloads. The FlashStack solution with Nutanix integration provides organizations with the agility to adapt infrastructure resources dynamically while maintaining enterprise-level reliability and performance.

© 2026 Cisco and/or its affiliates. All rights reserved.
© Intel Corporation.

## Key benefits

- **Independent scalability:** scale compute and storage resources separately based on workload demands
- **Enterprise-grade protection:** built-in data protection and disaster recovery capabilities
- **Hybrid-cloud readiness:** seamlessly extend operations across on-premises and cloud environments
- **Investment protection:** use Nutanix Cloud Platform with existing external storage

Table 1.1. Requirements for Connecting to Everpure FlashArray

| Attributes | Cisco Compute-Only (CO) node connected to Everpure FlashArray |
|---|---|
| **Cisco Compute-Only nodes** | Nutanix Foundation allocates the following minimum resources to the CVM: (Dependent on AOS version)<br>• CVM logical cores: 12<br>• CPU physical cores per Socket: 12<br>**Note:** For AOS releases earlier than version 7.6: CVM logical cores: 16,<br>CPU physical cores per socket: 16<br>vRAM (in GiB): 32<br>(Please leverage Nutanix Sizer for all customer workload sizing)<br>M.2 boot drives with M.2 RAID controller (A minimum of 480GB is required)<br>Storage protocol: NVMe over Fabric (NVMeoF) over TCP<br>A 25Gb Ethernet network connection is recommended between the Cisco Nutanix Compute cluster and external storage. (10Gb will be supported.)<br>A minimum of 3 CO nodes |
| **Hypervisor** | Nutanix AHV only |
| **Management** | Cisco Intersight Managed Mode (IMM) (or)<br>Cisco Intersight Standalone Mode (ISM) |
| **Everpure** | FlashArray//, FlashArray//XL, FlashArray//C |
| **Nutanix Cloud Platform software** | Supported Nutanix software:<br>• Nutanix Cloud Infrastructure (NCI)<br>• Nutanix Cloud Manager (NCM)<br>• Nutanix Cloud Platform (NCP)<br>• Nutanix Kubernetes Platform (NKP) |

© 2026 Cisco and/or its affiliates. All rights reserved.
© Intel Corporation.

| Attributes | Cisco Compute-Only (CO) node connected to Everpure FlashArray |
|---|---|
| **Licensing** | Nutanix Cloud Infrastructure (NCI) licenses on a per-core basis<br>Nutanix Cloud Infrastructure: Compute (NCI-C) (2000 cores minimum)<br>For more information about NCI licenses, see NCI section in Nutanix Cloud Platform Software Options. |

The Cisco Compute-Only C240 M8 Node family incorporates the Intel® Xeon® 6 processors. It improves security, performance, and efficiency while helping achieve sustainability goals with built-in accelerators such as Intel Trust Domain Extensions (TDX), Intel Data Streaming Accelerator (DSA), Intel QuickAssist Technology (QAT), Intel Advanced Matrix Extensions (AMX), and Intel In-Memory Analytics Accelerator (IAA).

Cisco Compute-Only C240 M8 Nodes can be repurposed as HCI nodes by adding a drive controller and drives. For more information, please refer to specification document Cisco Compute Hyperconverged and Compute-Only with Nutanix-240 M8 All-Flash Server or Cisco Compute Hyperconverged and Compute-Only with Nutanix-240 M8 All-NVMe E3.S Server.

These servers can be interconnected and managed in:

- **Intersight Managed mode:** The nodes are connected to a pair of Cisco UCS 6400 Series, a pair of Cisco UCS 6500 Series, or a pair of Cisco UCS 6600 fabric interconnects that are entirely managed from Intersight (SaaS, PVA, or CVA). All servers are connected to the same pair of fabric interconnects.

## Features

Table 2. Summary of features of Cisco Compute-Only C240 M8 Node

| Feature | Benefits |
|---|---|
| **Memory** | • High memory capacity<br>• Up to 8 TB memory (32 x 256 GB DDR5 DIMMs) |
| **Processors** | • 6th Generation Intel Xeon Scalable Processors (Granite Rapids)<br>• Massive processing power with up to 86 cores per socket<br>• Improved performance with AI-accelerated features and new virtual machine security features<br>• High speed DDR5 memory technology for up to 6400 MT/s<br>• Multiple built-in accelerators for new functional capabilities across AI, analytics, security, and storage |
| **Unified network fabric** | • Wire-once deployment model, eliminating the need to install adapters and re-cable racks and switches when changing I/O configurations<br>• Fewer interface cards, cables, and upstream network ports to purchase, power, configure, and maintain |

© 2026 Cisco and/or its affiliates. All rights reserved.
© Intel Corporation.

| Feature | Benefits | |
|---|---|---|
| **Cloud-based services and management** | Cisco Intersight simplifies infrastructure operations across on-premises data centers, edge sites, and public clouds<br>• Use a software-as-a-service platform that bridges applications with infrastructure<br>• Correlate visibility and management across bare-metal servers, hypervisors, and application components<br>• Transform operations with artificial intelligence to reach needed scale and velocity | Nutanix Cloud Platform (NCP) includes Nutanix Cloud Infrastructure (NCI or NCI-C), Nutanix Cloud Management (NCM), and desktop services:<br>• NCI unifies compute, storage, and network, hypervisors, and containers, in public or enterprise clouds<br>• NCM offers customers simplicity and ease of use to build and grow their cloud deployments and realize rapid ROI, by providing intelligent operations, self- service and orchestration, visibility, and governance |
| **Security** | • Trusted Platform Module (TPM), a chip (microcontroller) that can securely store artifacts, including passwords, certificates, and encryption keys, which are used to authenticate the platform (node). Supports TPM 2.0<br>• Software based data-at-rest encryption and microsegmentation | |

## Product specifications

Table 3. Specifications for Cisco Compute-Only C240 M8 Node

| Feature | Common specifications across the Cisco Compute-Only C240 M8 Node family |
|---|---|
| **Chassis** | 2RU of rack space per node |
| **Processors** | One or two 6th Gen Intel Xeon 6700P or 6500P processors (Granite Rapids) |
| **Memory** | 32 DIMM slots (16 DIMMS per CPU):<br>• 16, 32, 48, 64, 96,128, 256 GB DDR5 at up to 6400 MT/s for up to 8 TB of memory<br>• 32, 64 GB MRDIMMs at up to 8000 MT/s |
| **Boot drives** | • Dual M.2 SATA SSDs with HW RAID support<br>• 480GB M.2 SATA SSD |
| **PCIe** | • Up to 8 PCIe 5.0 slots plus 1 dedicated 24-Gbps RAID controller slot and 1 dedicated mLOM/OCP 3.0 slot |

© 2026 Cisco and/or its affiliates. All rights reserved.
© Intel Corporation.

| Feature | Common specifications across the Cisco Compute-Only C240 M8 Node family |
|---|---|
| **Graphics Processing Units (GPUs)** | • Up to three double-wide or eight single-wide GPUs supported. For a complete list refer to spec sheet |
| **Network** | • Cisco UCS Virtual Interface Card 15238 or 15427 (modular LAN on Motherboard)<br>• Quad 10/25/50 G or Dual 40/100 G Ethernet VIC (Cisco UCS Virtual Interface Card 15425 or 15235) (optional) |
| **Management** | • Cisco Intersight<br>• Cisco Integrated Management Controller (CIMC) |
| **Advanced Reliability, Availability, and Serviceability (RAS) features** | • Robust reporting and analytics<br>• Dual-redundant fans and hot-swappable, redundant power supplies for enterprise-class reliability and a convenient latching lid for easy access to internal server<br>• Tool-free CPU insertion, enabling processor upgrades and replacements with less risk of damage<br>• Tool-free access to all serviceable items and color-coded indicators to guide users to hot-pluggable and serviceable items<br>• Nondisruptive rolling upgrades using Nutanix Life-Cycle Manager (LCM) |
| **Front-panel connector** | • 1 KVM console connector per node (each connector supplies 2 USB connectors, 1 VGA connector, and 1 serial connector) |
| **Front-panel locator LED** | • Helps direct administrators to specific servers in large data-center environments |
| **Power and cooling** | • Hot-pluggable, redundant platinum, and titanium options:<br>• Platinum: 1050W DC and 1600W AC<br>• Titanium: 1200W AC and 2300W AC |
| **Rail-kit options** | • Cisco ball-bearing rail kit with optional reversible cable-management arm |

## Ordering information

For a complete list of part numbers, refer to the Cisco Compute-Only node spec sheet.

Table 4. Ordering information

| Part | Product description |
|---|---|
| **HCI-M8-NTNX-MLB** | Cisco Compute Hyperconverged with Nutanix M8 rack server MLB |
| **HCONX240C-M8E3S** | Cisco Compute-Only C240 M8 2RU NVMe-optimized server with up to 24x E3.S NVMe drive bays (Drives are optional) |

© 2026 Cisco and/or its affiliates. All rights reserved.
© Intel Corporation.

| Part | Product description |
|---|---|
| **HCONX240C-M8S** | Cisco Compute-Only C240 M8 2RU All-Flash server with up to 24x SAS/SATA SSD drive bays (Drives are optional) |

## Cisco services

Cisco, Nutanix, and our industry-leading partners deliver services that accelerate your transition to Cisco Compute Hyperconverged systems. Professional services can help you create an agile infrastructure, accelerate time to value, reduce costs and risks, and maintain availability during deployment and migration. After you have deployed your system, our services can help you improve performance, availability, and resiliency as your business needs evolve.

## Product sustainability

Information about Cisco's Environmental, Social, and Governance (ESG) initiatives and performance is provided in Cisco's Corporate Social Responsibility (CSR) and sustainability reporting.

Table 5. Cisco environmental sustainability information

| Sustainability topic | | Reference |
|---|---|---|
| **General** | Information on product-material-content laws and regulations | Materials |
| | Information on electronic waste laws and regulations, including our products, batteries, and packaging | WEEE Compliance |
| | Information on product takeback and reuse program | Cisco Takeback and Reuse Program |
| | Sustainability inquiries | Contact: csr_inquiries@cisco.com |

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital® makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. Learn more.

© 2026 Cisco and/or its affiliates. All rights reserved.
© Intel Corporation.

# Document history

| New or Revised Topic | Described In | Date |
|---|---|---|
| **Cisco Compute-Only (CO) C240 M8 Node Family** | Data sheet | April 2026 |
| **Minimum cluster requirements for Cisco Compute-Only nodes.** | Table 1, Management<br>2 Requirements for Connecting to External Storage | August 2026 |
| **Nutanix Foundation** | Table 1.1 | September 2026 |

© 2026 Cisco and/or its affiliates. All rights reserved. Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)
C78-6058101-02 09/26

© Intel Corporation. Intel, the Intel logo, and other Intel marks are trademarks of Intel Corporation or its subsidiaries. Other names and brands may be claimed as the property of others.