Troubleshoot a Scenario Related to Bulkstats Schemas and Recommended Workarounds in StarOS

Contents

[Introduction](#)
[Prerequisites](#)
[Requirements](#)
[Components Used](#)
[Background Information](#)
[Problem](#)
[Test Scenarios](#)
[Solution](#)

Introduction

This document describes a scenario related to the addition and deletion of bulkstat schemas in StarOS along with issues and recommended workarounds for these issues.

Prerequisites

Requirements

Cisco recommends that you have knowledge of these topics:

- Linux
- StarOS

Cisco recommends that you must have privilege access:

- hidden mode to execute the **debug shell** in order to access linux shell command prompt
- Secure File Transfer Protocol (SFTP) access to the StarOS node

Components Used

The information in this document is based on StarOS version-21.16.6.77063.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, ensure that you understand the potential impact of any command.

Background Information

1. To configure a config-file to store the configurations related to bulkstats.
2. The format of the command is:

```
configure

      [no] bulkstats config [ schema | supplement ] <url>

end
```

Where:

- The optional **schema** keyword allows you to replace only the schema using the file provided and preserve the server configuration.
- The optional **supplement** keyword allows you to supplement the running bulkstats configuration with the contents of the configuration file provided. These keywords only work on existing files.
- URL specifies the location of the bulkstats configuration file.

Problem

Unable to add new schemas/re-add the current schema (if deleted) via the CLI command prompt.

Test Scenarios

1. Faced this issue due to the use of the cli **bulkstat config schema <URL>**.
2. It is an expected result per design when an optional keyword **schema** is used.
3. The same scenario was tested out in the lab. Here are the outcomes:
   Scenario A. Initially **bulkstat config <url>** cli was configured.

```
[local]MME# show configuration bulkstats

config

 bulkstats collection

 bulkstats historical collection

 bulkstats config /hd-raid/file1

 bulkstats mode

   file 1

     header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

     footer format EndOfFile

     card schema cardSch1 format
PPM,card,cardSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpubusy%,%cpuidle%,%numpr
oc%,%memused%,%memtotal%,%numcpu%,%cpu0-cpubusy%,%cpu0-cpuidle%,%cpu0-numproc%,%cpu0-
memused%,%cpu0-memtotal%,%cpu0-name%,%cpu0-cpuused-user%,%cpu0-cpuused-sys%,%cpu0-cpuused-
io%,%cpu0-cpuused-irq%,%cpu0-cpuused-idle%,%cpu1-cpubusy%,%cpu1-cpuidle%,%cpu1-numproc%,

     card schema cardSch2 format
```

```
PPM,card,cardSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu1-memused%,%cpu1-
memtotal%,%cpu1-name%,%cpu1-cpuused-user%,%cpu1-cpuused-sys%,%cpu1-cpuused-io%,%cpu1-cpuused-
irq%,%cpu1-cpuused-idle%,%cpu2-cpubusy%,%cpu2-cpuidle%,%cpu2-numproc%,%cpu2-memused%,%cpu2-
memtotal%,%cpu2-name%,%cpu2-cpuused-user%,%cpu2-cpuused-sys%,%cpu2-cpuused-io%,%cpu2-cpuused-
irq%,%cpu2-cpuused-idle%,%cpu3-cpubusy%,%cpu3-cpuidle%,

     card schema cardSch3 format
PPM,card,cardSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu3-numproc%,%cpu3-
memused%,%cpu3-memtotal%,%cpu3-name%,%cpu3-cpuused-user%,%cpu3-cpuused-sys%,%cpu3-cpuused-
io%,%cpu3-cpuused-irq%,%cpu3-cpuused-idle%,%15avg-cpubusy%,%15peak-cpubusy%,%5avg-
cpubusy%,%5peak-cpubusy%,%1avg-cpubusy%,%15avg-memused%,%15peak-memused%,%5avg-memused%,%5peak-
memused%,%1avg-memused%,%cpu0-15avg-cpubusy%,%cpu0-15peak-cpubusy%,

     port schema portSch1 format
PPM,port,portSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%maxrate%,%rxbytes%
,%txbytes%,%ucast_inpackets%,%ucast_outpackets%,%mcast_inpackets%,%mcast_outpackets%,%bcast_inpa
ckets%,%bcast_outpackets%,%rxpackets%,%txpackets%,%rxdiscbytes%,%rxdiscpackets%,%txdiscbytes%,%t
xdiscpackets%,%rxerrorbytes%,%rxerrorpackets%,%txerrorbytes%,%txerrorpackets%,

     port schema portSch2 format
PPM,port,portSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%frag-rcvd%,%pkt-
reassembled%,%frag-tokernel%,%util-rx-curr%,%util-tx-curr%,%util-rx-5min%,%util-tx-5min%,%util-
rx-15min%,%util-tx-15min%,%port-5peak-rx-util%,%port-5peak-tx-util%,%port-15peak-rx-util%,%port-
15peak-tx-util%,

     apn-expansion schema apn1 format PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

     apn-expansion schema apn2 format PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

     apn-expansion schema apn3 format PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

   #exit

 #exit

end


[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

 Server State:                  Enabled

 File Limit:                    7500 KB

 Sample Interval:               15 minutes (0D 0H 15M)

 Transfer Interval:             480 minutes (0D 8H 0M)

 Receiver Mode:                 Secondary-on-failure

 Historical Data Collection:    Enabled (15 samples stored)



Bulk Statistics Server Statistics:

 Records awaiting transmission: 0

 Bytes awaiting transmission:   0

 Total records collected:       0
```

```
 Total bytes collected:         0

 Total records transmitted:     0

 Total bytes transmitted:       0

 Total records discarded:       0

 Total bytes discarded:         0

 Last collection time required: 0 second(s)

 Last transfer time required:   0 second(s)

 No successful data transfers

 No attempted data transfers



 File 1

   Remote File Format:            %date%-%time%

   File Header:                   Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

   File Footer:                   EndOfFile

   No bulkstats receivers

   File Statistics:

     Records awaiting transmission: 0

     Bytes awaiting transmission:   0

     Total records collected:       0

     Total bytes collected:         0

     Total records transmitted:     0

     Total bytes transmitted:       0

     Total records discarded:       0

     Total bytes discarded:         0

     Last transfer time required:   0 second(s)

     No successful data transfers

     No attempted data transfers



 File 2 not configured
```

```
 File 3 not configured



 File 4 not configured



------------------- Schemas for File 1----------------------------------------

Type         Name                      Active-Only Format

------------ ------------------------ ---------- ---------------------------------------

card         cardSch1                  No
PPM,card,cardSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpubusy%,%cpuidle%,%numpr
oc%,%memused%,%memtotal%,%numcpu%,%cpu0-cpubusy%,%cpu0-cpuidle%,%cpu0-numproc%,%cpu0-
memused%,%cpu0-memtotal%,%cpu0-name%,%cpu0-cpuused-user%,%cpu0-cpuused-sys%,%cpu0-cpuused-
io%,%cpu0-cpuused-irq%,%cpu0-cpuused-idle%,%cpu1-cpubusy%,%cpu1-cpuidle%,%cpu1-numproc%,

card         cardSch2                  No
PPM,card,cardSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu1-memused%,%cpu1-
memtotal%,%cpu1-name%,%cpu1-cpuused-user%,%cpu1-cpuused-sys%,%cpu1-cpuused-io%,%cpu1-cpuused-
irq%,%cpu1-cpuused-idle%,%cpu2-cpubusy%,%cpu2-cpuidle%,%cpu2-numproc%,%cpu2-memused%,%cpu2-
memtotal%,%cpu2-name%,%cpu2-cpuused-user%,%cpu2-cpuused-sys%,%cpu2-cpuused-io%,%cpu2-cpuused-
irq%,%cpu2-cpuused-idle%,%cpu3-cpubusy%,%cpu3-cpuidle%,

card         cardSch3                  No
PPM,card,cardSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu3-numproc%,%cpu3-
memused%,%cpu3-memtotal%,%cpu3-name%,%cpu3-cpuused-user%,%cpu3-cpuused-sys%,%cpu3-cpuused-
io%,%cpu3-cpuused-irq%,%cpu3-cpuused-idle%,%15avg-cpubusy%,%15peak-cpubusy%,%5avg-
cpubusy%,%5peak-cpubusy%,%1avg-cpubusy%,%15avg-memused%,%15peak-memused%,%5avg-memused%,%5peak-
memused%,%1avg-memused%,%cpu0-15avg-cpubusy%,%cpu0-15peak-cpubusy%,

port         portSch1                  No
PPM,port,portSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%maxrate%,%rxbytes%
,%txbytes%,%ucast_inpackets%,%ucast_outpackets%,%mcast_inpackets%,%mcast_outpackets%,%bcast_inpa
ckets%,%bcast_outpackets%,%rxpackets%,%txpackets%,%rxdiscbytes%,%rxdiscpackets%,%txdiscbytes%,%t
xdiscpackets%,%rxerrorbytes%,%rxerrorpackets%,%txerrorbytes%,%txerrorpackets%,

port         portSch2                  No
PPM,port,portSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%frag-rcvd%,%pkt-
reassembled%,%frag-tokernel%,%util-rx-curr%,%util-tx-curr%,%util-rx-5min%,%util-tx-5min%,%util-
rx-15min%,%util-tx-15min%,%port-5peak-rx-util%,%port-5peak-tx-util%,%port-15peak-rx-util%,%port-
15peak-tx-util%,

apn-expansion apn1                      No          PPM,apn-
expansion,%epochtime%,%localdate%,%localtime%,

apn-expansion apn2                      No          PPM,apn-
expansion,%epochtime%,%localdate%,%localtime%,

apn-expansion apn3                      No          PPM,apn-
expansion,%epochtime%,%localdate%,%localtime%,

mon-di-net   mdn1                      No          PPM,%epochtime%,%localdate%,%localtime%,

[local]MME#
```

Scenario B. To add the optional keyword **schema**, you need to first remove the bulkstat cli by **no bulkstats config**. The moment you execute **no bulkstats config**, all the current schemas in the

node get deleted.

```
[local]MME#

[local]MME# configure

[local]MME(config)# bulkstats collection

[local]MME(config)# no bulkstats config

<cr>                - newline

[local]MME(config)# no bulkstats config

[local]MME(config)# end

[local]MME# show configuration bulkstats

config

 bulkstats collection

 bulkstats historical collection

 bulkstats mode

   file 1

     header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

     footer format EndOfFile

   #exit

 #exit

end

[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

 Server State:                  Enabled

 File Limit:                    7500 KB

 Sample Interval:               15 minutes (0D 0H 15M)

 Transfer Interval:             480 minutes (0D 8H 0M)

 Receiver Mode:                 Secondary-on-failure

 Historical Data Collection:    Enabled (15 samples stored)



Bulk Statistics Server Statistics:

 Records awaiting transmission: 0
```

```
 Bytes awaiting transmission:   0

 Total records collected:       0

 Total bytes collected:         0

 Total records transmitted:     0

 Total bytes transmitted:       0

 Total records discarded:       0

 Total bytes discarded:         0

 Last collection time required: 0 second(s)

 Last transfer time required:   0 second(s)

 No successful data transfers

 No attempted data transfers



 File 1

   Remote File Format:            %date%-%time%

   File Header:                   Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

   File Footer:                   EndOfFile

   No bulkstats receivers

   File Statistics:

     Records awaiting transmission: 0

     Bytes awaiting transmission:   0

     Total records collected:       0

     Total bytes collected:         0

     Total records transmitted:     0

     Total bytes transmitted:       0

     Total records discarded:       0

     Total bytes discarded:         0

     Last transfer time required:   0 second(s)

     No successful data transfers

     No attempted data transfers



 File 2 not configured
```

```
 File 3 not configured



 File 4 not configured

[local]MME#

[local]MME#
```

Scenario C. Then the cli **bulkstat config schema <url>** is configured. All the configurations and schemas present in the configuration file are added to the node.

```
[local]MME# configure

[local]MME(config)# bulkstats collection

[local]MME(config)# bulkstats config schema /hd-raid/file2

Info: config

Info: bulkstats mode

Info: file 2

Info: header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

Info: footer format EndOfFile

Info: diameter-auth schema diameter-authSch1 format PPM,diameter-auth,diameter-
authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servert
ype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-
acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-
req-rcvd%,%raa-ans-accpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

Info: diameter-auth schema diameter-authSch2 format PPM,diameter-auth,diameter-
authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%sta-
ans-accpt-rcvd%,%asr-req-rcvd%,%asa-rsp-accpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-
err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

Info: diameter-auth schema diameter-authSch3 format PPM,diameter-auth,diameter-
authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%
diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-
protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-
msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

Info: schema systemSch1 format
PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-
ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-
ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-
curaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-
curaaaacctitemsmax%,%sess-curaaabuffused%,%sess-curaaabuffmax%,%sess-ttlaaacancauth%,%sess-
ttlaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

Info: schema systemSch10 format
PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-
curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-
```

```
ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-
ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-
ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-
ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-
marretry%,%diamauth-msg-maatimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

Info: schema systemSch100 format
PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-
qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-
qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-
bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-
5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-
qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-
bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-
5day-qci7%,

Info: sgs schema sgsSch1 format
PPM,sgs,sgsSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-rej-rx%,%service-
req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-retx%,%dl-ud-rx%,%ul-ud-tx%,%ul-
ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-req-retx%,

Info: sgs schema sgsSch2 format
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-
rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-
rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-
rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

Info: sgs schema sgsSch3 format
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-
retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-
tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

Info: exit

[local]MME(config)# end

[local]MME#

[local]MME# show configuration bulkstats

config

 bulkstats collection

 bulkstats historical collection

 bulkstats config schema /hd-raid/file2

 bulkstats mode

   file 1

     header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

     footer format EndOfFile

   #exit

   file 2
```

```
     header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

     footer format EndOfFile

     schema systemSch1 format
PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-
ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-
ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-
curaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-
curaaaacctitemsmax%,%sess-curaaabuffused%,%sess-curaaabuffmax%,%sess-ttlaaacancauth%,%sess-
ttlaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

     schema systemSch10 format
PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-
curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-
ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-
ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-
ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-
ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-
marretry%,%diamauth-msg-maatimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

     schema systemSch100 format
PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-
qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-
qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-
bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-
5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-
qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-
bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-
5day-qci7%,

     diameter-auth schema diameter-authSch1 format PPM,diameter-auth,diameter-
authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servert
ype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-
acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-
req-rcvd%,%raa-ans-accpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

     diameter-auth schema diameter-authSch2 format PPM,diameter-auth,diameter-
authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%sta-
ans-accpt-rcvd%,%asr-req-rcvd%,%asa-rsp-accpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-
err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

     diameter-auth schema diameter-authSch3 format PPM,diameter-auth,diameter-
authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%
diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-
protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-
msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

     sgs schema sgsSch1 format
PPM,sgs,sgsSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-rej-rx%,%service-
req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-retx%,%dl-ud-rx%,%ul-ud-tx%,%ul-
ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-req-retx%,

     sgs schema sgsSch2 format
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-
rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-
rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-
rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

     sgs schema sgsSch3 format
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
```

```
d%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-
retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-
tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

   #exit

 #exit

end

[local]MME#
```

Scenario D. After that, it is not possible to add any new schemas. When you try to remove a current schema and add it back again, the schema gets deleted but you will not be able to add it back. However, the current schema was still present in the configuration file (configuration file present in the URL).

```
[local]MME# configure

[local]MME(config)# bulkstats mode



mode                 - Enters bulk statistics configuration mode, where you can define what
statistics to collect

[local]MME(config)# bulkstats mode

[local]MME(config-bulkstats)# file 1

[local]MME(config-bulkstats-file-1)# mon-di-net schema mdn1 format PPM,%epochti

me%,%localdate%,%localtime%,

[local]MME(config-bulkstats-file-1)# exit

[local]MME(config-bulkstats)# file 2

[local]MME(config-bulkstats-file-2)# mon-di-net schema mdn2 format PPM,%epochti

me%,

[local]MME(config-bulkstats-file-2)# end

[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

 Server State:                  Enabled

 File Limit:                    7500 KB

 Sample Interval:               15 minutes (0D 0H 15M)

 Transfer Interval:             480 minutes (0D 8H 0M)

 Receiver Mode:                 Secondary-on-failure

 Historical Data Collection:    Enabled (15 samples stored)
```

```
Bulk Statistics Server Statistics:

 Records awaiting transmission: 0

 Bytes awaiting transmission:   0

 Total records collected:       0

 Total bytes collected:         0

 Total records transmitted:     0

 Total bytes transmitted:       0

 Total records discarded:       0

 Total bytes discarded:         0

 Last collection time required: 0 second(s)

 Last transfer time required:   0 second(s)

 No successful data transfers

 No attempted data transfers



 File 1

   Remote File Format:            %date%-%time%

   File Header:                   Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

   File Footer:                   EndOfFile

   No bulkstats receivers

   File Statistics:

     Records awaiting transmission: 0

     Bytes awaiting transmission:   0

     Total records collected:       0

     Total bytes collected:         0

     Total records transmitted:     0

     Total bytes transmitted:       0

     Total records discarded:       0

     Total bytes discarded:         0

     Last transfer time required:   0 second(s)

     No successful data transfers
```

```
     No attempted data transfers



 File 2

   Remote File Format:            %date%-%time%

   File Header:                   Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

   File Footer:                   EndOfFile

   No bulkstats receivers

   File Statistics:

     Records awaiting transmission: 0

     Bytes awaiting transmission:   0

     Total records collected:       0

     Total bytes collected:         0

     Total records transmitted:     0

     Total bytes transmitted:       0

     Total records discarded:       0

     Total bytes discarded:         0

     Last transfer time required:   0 second(s)

     No successful data transfers

     No attempted data transfers



 File 3 not configured



 File 4 not configured



------------------- Schemas for File 2----------------------------------------

Type         Name                     Active-Only Format

------------ ------------------------ ----------- ----------------------------------------

system       systemSch1               No
PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-
ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-
ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-
curaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-
```

```
curaaaacctitemsmax%,%sess-curaaabuffused%,%sess-curaaabuffmax%,%sess-ttlaaacancauth%,%sess-
ttlaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

system       systemSch10              No
PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-
curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-
ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-
ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-
ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-
ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-
marretry%,%diamauth-msg-maatimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

system       systemSch100             No
PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-
qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-
qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-
bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-
5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-
qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-
bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-
5day-qci7%,

diameter-auth diameter-authSch1        No          PPM,diameter-auth,diameter-
authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servert
ype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-
acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-
req-rcvd%,%raa-ans-accpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

diameter-auth diameter-authSch2        No          PPM,diameter-auth,diameter-
authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%sta-
ans-accpt-rcvd%,%asr-req-rcvd%,%asa-rsp-accpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-
err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth diameter-authSch3        No          PPM,diameter-auth,diameter-
authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%
diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-
protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-
msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

sgs          sgsSch1                  No
PPM,sgs,sgsSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-rej-rx%,%service-
req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-retx%,%dl-ud-rx%,%ul-ud-tx%,%ul-
ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-req-retx%,

sgs          sgsSch2                  No
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-
rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-
rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-
rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

sgs          sgsSch3                  No
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-
retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-
tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

[local]MME# configure

[local]MME(config)# bulkstats mode

[local]MME(config-bulkstats)# file 2
```

```
[local]MME(config-bulkstats-file-2)# no sgs

sgs                  - Removes sgs bulk statistics schema

[local]MME(config-bulkstats-file-2)# no sgs schema sgsSch1

[local]MME(config-bulkstats-file-2)# end

[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

 Server State:                  Enabled

 File Limit:                    7500 KB

 Sample Interval:               15 minutes (0D 0H 15M)

 Transfer Interval:             480 minutes (0D 8H 0M)

 Receiver Mode:                 Secondary-on-failure

 Historical Data Collection:    Enabled (15 samples stored)



Bulk Statistics Server Statistics:

 Records awaiting transmission: 0

 Bytes awaiting transmission:   0

 Total records collected:       0

 Total bytes collected:         0

 Total records transmitted:     0

 Total bytes transmitted:       0

 Total records discarded:       0

 Total bytes discarded:         0

 Last collection time required: 0 second(s)

 Last transfer time required:   0 second(s)

 No successful data transfers

 No attempted data transfers



 File 1

   Remote File Format:            %date%-%time%

   File Header:                   Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

   File Footer:                   EndOfFile
```

```
  No bulkstats receivers

  File Statistics:

    Records awaiting transmission: 0

    Bytes awaiting transmission:   0

    Total records collected:       0

    Total bytes collected:         0

    Total records transmitted:     0

    Total bytes transmitted:       0

    Total records discarded:       0

    Total bytes discarded:         0

    Last transfer time required:   0 second(s)

    No successful data transfers

    No attempted data transfers



 File 2

  Remote File Format:            %date%-%time%

  File Header:                   Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

  File Footer:                   EndOfFile

  No bulkstats receivers

  File Statistics:

    Records awaiting transmission: 0

    Bytes awaiting transmission:   0

    Total records collected:       0

    Total bytes collected:         0

    Total records transmitted:     0

    Total bytes transmitted:       0

    Total records discarded:       0

    Total bytes discarded:         0

    Last transfer time required:   0 second(s)

    No successful data transfers

    No attempted data transfers
```

File 3 not configured

File 4 not configured

---------- Schemas for File 2----------

Type Name Active-Only Format

---

system systemSch1 No
PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-curaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-curaaaacctitemsmax%,%sess-curaaabuffused%,%sess-curaaabuffmax%,%sess-ttlaaacancauth%,%sess-ttlaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

system systemSch10 No
PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-maatimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

system systemSch100 No
PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,

diameter-auth diameter-authSch1 No PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-accpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

diameter-auth diameter-authSch2 No PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%sta-ans-accpt-rcvd%,%asr-req-rcvd%,%asa-rsp-accpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth diameter-authSch3 No PPM,diameter-auth,diameter-authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

```
sgs          sgsSch2                  No
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-
rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-
rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-
rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

sgs          sgsSch3                  No
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-
retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-
tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

[local]MME# configure

[local]MME(config)# bulkstats mode

[local]MME(config-bulkstats)# file 2

[local]MME(config-bulkstats-file-2)# sgs schema sgsSch1 format PPM,sgs,sgsSch1,

%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%serv

id%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-r

ej-rx%,%service-req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-r

etx%,%dl-ud-rx%,%ul-ud-tx%,%ul-ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-

req-retx%,

[local]MME(config-bulkstats-file-2)# end

[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

 Server State:                  Enabled

  File Limit:                    7500 KB

 Sample Interval:               15 minutes (0D 0H 15M)

 Transfer Interval:             480 minutes (0D 8H 0M)

 Receiver Mode:                 Secondary-on-failure

 Historical Data Collection:    Enabled (15 samples stored)



Bulk Statistics Server Statistics:

 Records awaiting transmission: 0

 Bytes awaiting transmission:   0

 Total records collected:       0

 Total bytes collected:         0

 Total records transmitted:     0
```

```
 Total bytes transmitted:       0

 Total records discarded:       0

 Total bytes discarded:         0

 Last collection time required: 0 second(s)

 Last transfer time required:   0 second(s)

 No successful data transfers

 No attempted data transfers



 File 1

   Remote File Format:            %date%-%time%

   File Header:                   Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

   File Footer:                   EndOfFile

   No bulkstats receivers

   File Statistics:

     Records awaiting transmission: 0

     Bytes awaiting transmission:   0

     Total records collected:       0

     Total bytes collected:         0

     Total records transmitted:     0

     Total bytes transmitted:       0

     Total records discarded:       0

     Total bytes discarded:         0

     Last transfer time required:   0 second(s)

     No successful data transfers

     No attempted data transfers



 File 2

   Remote File Format:            %date%-%time%

   File Header:                   Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

   File Footer:                   EndOfFile
```

```
   No bulkstats receivers

   File Statistics:

     Records awaiting transmission: 0

     Bytes awaiting transmission:   0

     Total records collected:       0

     Total bytes collected:         0

     Total records transmitted:     0

     Total bytes transmitted:       0

     Total records discarded:       0

     Total bytes discarded:         0

     Last transfer time required:   0 second(s)

     No successful data transfers

     No attempted data transfers



 File 3 not configured



 File 4 not configured



------------------- Schemas for File 2----------------------------------------

Type         Name                     Active-Only Format

------------ ------------------------ ----------- ----------------------------------------

system       systemSch1               No
PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-
ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-
ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-
curaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-
curaaaacctitemsmax%,%sess-curaaabuffused%,%sess-curaaabuffmax%,%sess-ttlaaacancauth%,%sess-
ttlaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

system       systemSch10              No
PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-
curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-
ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-
ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-
ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-
ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-
marretry%,%diamauth-msg-maatimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

system       systemSch100             No
PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-
```

```
qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-
qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-
bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-
5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-
qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-
bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-
5day-qci7%,

diameter-auth diameter-authSch1        No          PPM,diameter-auth,diameter-
authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servert
ype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-
acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-
req-rcvd%,%raa-ans-accpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

diameter-auth diameter-authSch2        No          PPM,diameter-auth,diameter-
authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%sta-
ans-accpt-rcvd%,%asr-req-rcvd%,%asa-rsp-accpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-
err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth diameter-authSch3        No          PPM,diameter-auth,diameter-
authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%
diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-
protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-
msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

sgs          sgsSch2                   No
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-
rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-
rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-
rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

sgs          sgsSch3                   No
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-
retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-
tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

[local]MME#
```

Scenario E. So the outcome is whenever you use the optional keyword **schema**, you cannot add any new schemas. You can delete any current schemas (from the node) but can't add them back. However, the current schemas present in the configuration file (which is present in the <url>, does not get affected by the changes done in the node).

Solution

1. The cli **bulkstat config schema <url>** is used, due to which they faced this issue.
2. It is an expected result per design, which you get if optional keyword **schema** is used.
3. There are three solutions for this case, which are:

A.To remove the cli **bulkstat config schema <url>** and control the schemas addition/deletion via manual cli/command prompt.

B. To use the optional keyword **supplement** in the bulkstat config cli. With the cli **bulkstat config supplement <url>** you can add the schemas present in the config file to the current node's schemas. You can add/delete new schemas and current schemas can also be deleted/added back via the CLI command prompt.

C. To add/delete the required schemas directly in the config file and then reload the configurations

with the config file (first remove the cli by **no bulkstat config**, add the schemas in the config file and then add it back by **bulkstats config schema <url>**). To add the schemas in the config file, you can either do it with the vi editor or by SFTP the file

With the vi editor:

```
[local]MME-01# cli test-commands password <pswd>
Warning: Test commands enables internal testing and debugging commands
USE OF THIS MODE MAY CAUSE SIGNIFICANT SERVICE INTERRUPTION

[local]MME-01# debug shell
Last log in: Wed Dec 22 15:05:12 +0530 2021 on pts/3 from 10.227.224.108.
MME-01:card1-cpu0# ls -lrtha

total 16
-r--r--r-- 1 root root 952 Dec 15 23:30 .rhosts
-r--r--r-- 1 root root 1.7K Dec 15 23:30 .gdbinit
drwx------ 2 root root 100 Dec 15 23:30 .ssh
drwxr-xr-x 24 root root 500 Dec 15 23:30 ..
-rw------- 1 root root 118 Dec 21 14:48 .bash_history
-rw-r--r-- 1 root root 1 Dec 22 15:05 file
drwxr-xr-x 3 root root 140 Dec 22 15:05 .

MME-01:card1-cpu0# vi file
```

SFTP the config file from the <url> to your local drive, edit it and SFTP it back to the <url>.