

Editing IP Fabric for Media (IPFM) Fabric Settings, Release 4.3.1

Table of Contents

New and changed information . . . 1
Understanding IPFM fabrics . . . 2
Editing an IPFM fabric . . . 3
- General . . . 3
- Fabric management . . . 3
  - General Parameters . . . 4
  - Multicast . . . 5
  - Protocols . . . 11
  - Advanced . . . 12
  - Freeform . . . 14
  - Manageability . . . 14
  - Bootstrap . . . 15
- Add switches . . . 17

Additional settings . . . 18
- Retrieving the authentication key . . . 18
  - Retrieve the 3DES encrypted OSPF authentication key . . . 18
  - Retrieve the encrypted IS-IS authentication key . . . 18
  - Retrieve the 3DES encrypted BGP authentication key . . . 19
  - Retrieve the encrypted BFD authentication key . . . 19
- Interface configuration for IPFM fabrics . . . 20
  - Supported templates for configuring interfaces . . . 21
  - Supported interface types for creating interfaces . . . 22
  - Create an interface for IPFM fabrics . . . 22
  - Create a sub-interface for IPFM fabrics . . . 25
  - Edit an interface for IPFM fabrics . . . 28
  - Configuring PTP for IPFM fabrics . . . 30
  - Guidelines for configuring PTP telemetry monitoring on Cisco Catalyst 9000 switches . . . 31
  - Add the PTP telemetry policy to a Cisco Catalyst 9000 switch . . . 31
  - Verify the PTP telemetry policy configuration . . . 32
  - Edit a PTP telemetry policy configuration . . . 32
  - View the PTP telemetry policy configuration on Topology . . . 33
- Creating an IPFM fabric group . . . 33
  - Benefits of creating an IPFM fabric group . . . 33
  - Guidelines and limitations for creating an IPFM fabric group . . . 33
  - Create an IPFM fabric group . . . 33
  - Add a child IPFM fabric to an IPFM fabric group . . . 34
  - Associate hosts from two fabrics in a host group . . . 34
  - Associate flows to a host group . . . 34
  - View side-by-side associations of IPFM member fabrics . . . 35
- Working with policies when configuring an IPFM fabric . . . 35
  - Add a policy for an IPFM fabric . . . 36

Edit a policy for an IPFM fabric 37
PFM-SD policies for non-default VRFs and multi-site deployments 37
Copyright 47

New and changed information

The following table provides an overview of the significant changes up to this current release. The table does not provide an exhaustive list of all changes or of the new features up to this release.

Release Version	Feature	Description
Nexus Dashboard 4.3.1	Support for PIM PFM-SD on IPFM fabrics.	Beginning with release 4.3.1, Nexus Dashboard supports configuring Protocol Independent Multicast (PIM) flooding mechanism – source discovery (PFM-SD) on IPFM fabrics. PFM-SD enables faster multicast source discovery by allowing first-hop routers to announce active multicast sources across the fabric. This eliminates the dependency on a Rendezvous Point (RP), MSDP, or BSR. PFM-SD supports single-site and multi-site deployments, default and non-default VRFs, and inter-fabric boundary control. For more information, see PIM flooding mechanism for source discovery and PFM-SD policies for non-default VRFs and multi-site deployments.
Nexus Dashboard 4.3.1	Support for new Cisco switches	Beginning with Nexus Dashboard 4.3.1, Nexus Dashboard adds support for the following switches running NX-OS 10.6(3) or a later release: • N9348Y12C-SE1 • N9396Y12C-SE1 • N9348Y2C6D-SE1U • N9396T12C-SE1 • N9364E-SG2-Q • N9364E-SG2-O For more information, see Add switches.
Nexus Dashboard 4.3.1	Cisco Nexus 9000 Series name change	Cisco Nexus 9000 Series is now the Cisco N9000 Series.

Understanding IPFM fabrics

The IP Fabric for Media (IPFM) fabric type is part of a LAN fabric.

Choose the **IP Fabric for Media** fabric to automate the creation of IP-based broadcast production networks on Cisco Nexus (NX-OS) switches.

This article describes how to edit an IPFM fabric that you already created. For instructions on creating a new IPFM fabric, see Creating Fabrics and Fabric Groups.

Editing an IPFM fabric

Follow these procedures to edit an IPFM fabric.

1. Navigate to the main **Fabrics** page:

   Manage > Fabrics

2. In the table showing all of the Nexus Dashboard fabrics that you have already created, locate the row with the IPFM fabric that you want to edit.
3. Click the circle next to the appropriate fabric to choose it, then click **Actions > Edit Fabric Settings**.

   You can also access the **Edit *fabric-name* settings** page for a fabric by navigating to that fabric's **Overview** page, then clicking **Actions > Edit fabric settings**.

4. On the **Edit *fabric-name* settings** page, click the appropriate tab to edit fabric settings in these areas.
   - General
   - Fabric management

General

In the **General** tab, edit the fabric settings that you configured when you first created this fabric.

Fabric type	Description
Name	The name for the fabric. Even though this field is shown, it is not editable.
Type	Displays the type of fabric. This field is not editable.
Location	Change the location for the fabric, if necessary.
License tier for fabric	Change the licensing tier for the fabric, if necessary: • **Essentials** • **Advantage** • **Premier** Click on the information icon (i) next to **License tier for fabric** to see what functionality is enabled for each license tier.
Security domain	Change the security domain for the fabric, if necessary.

What's next: Complete the configurations in another tab if necessary, or click **Save** when you have completed the necessary configurations for this fabric.

Fabric management

In the **Fabric management** tab, click the appropriate subtab to edit fabric settings in these areas.

- General Parameters
- Multicast
- Protocols
- Advanced
- Freeform
- Manageability
- Bootstrap

General Parameters

The **General Parameters** tab is displayed by default. The fields in this tab are described in the following table.

Field	Description
Fabric Interface Numbering	Supports only numbered, point-to-point, networks.
Fabric Subnet IP Mast	Specifies the subnet mask for the fabric interface IP addresses.
Fabric Routing Protocol	Specifies the Cisco Interior Gateway Routing Protocol (IGP) used in the fabric. Options are: • **OSPF**—Open Shortest Path First (OSPF) is an IGP designed for IP networks that supports IP subnetting and tagging of externally derived routing information. OSPF also allows packet authentication and uses IP multicast when sending and receiving packets. • **IS-IS**—Integrated Intermediate System-to-Intermediate Systems (IS-IS) is a link-state IGP for propagating information required to build a complete network connectivity map on each participating device. The map is then used to calculate the shortest path to destinations.
Fabric Routing Loopback Id	Specifies that the loopback interface ID is populated as 0 since loopback0 is usually used for fabric-underlay IGP peering purposes. The valid value ranges are from 0 to 1023.

Field	Description
Manual Fabric IP Address Allocation	Check this check box to disable dynamic allocation of the fabric IP address. By default, Nexus Dashboard allocates the underlay IP address resources (for loopbacks, fabric interfaces, and so on) dynamically from the defined pools. If you check the check box, the allocation scheme switches to static, and some of the dynamic IP address range fields are disabled. For static allocation, the underlay IP address resources must be populated into the Resource Manager (RM) using REST APIs. For more information, see the *Cisco REST API Reference Guide, Release 12.0.1a*. The REST APIs must be invoked after the switches are added to the fabric and before you use the **Save & Deploy** option. Changing from static to dynamic allocation keeps the current IP resource usage intact. Only future IP address allocation requests are taken from dynamic pools.
Fabric Routing Loopback IP Range	Specifies the range of loopback IP addresses for protocol peering.
Fabric Subnet IP Range	Specifies the IP addresses for the underlay point-to-point routing traffic between the interfaces.
Enable Performance Monitoring	Check this check box to monitor the performance of the fabric. Ensure that you do not clear interface counters from the command-line interface of the switches. Clearing interface counters can cause the **Performance Monitor** to display incorrect data for traffic utilization. If you must clear the counters and the switch has both clear counters and clear counters snmp commands (not all switches have the clear counters snmp command), ensure that you run both the main and the SNMP commands simultaneously. For example, you must run the clear counters interface ethernet slot/port command followed by the clear counters interface ethernet slot/port snmp command. This can lead to a one time spike.

What's next: Complete the configurations in another tab if necessary, or click **Save** when you have completed the necessary configurations for this fabric.

Multicast

The **Multicast** tab allows you to configure and monitor Non-Blocking Multicast (NBM) active and passive VRFs. In NBM passive mode, Nexus Dashboard only monitors the IPFM fabric and does not configure it, except to set the VRF mode to NBM passive.

You can also enable Protocol Independent Multicast (PIM) flooding mechanism - source discovery (PFM-SD) to speed up multicast source discovery in media environments.



In NBM or regular multicast, both sender and receiver must be in the same fabric to display an active flow.

PIM flooding mechanism for source discovery

PFM-SD is a faster way to discover multicast sources in IPFM fabrics. It is designed for media environments where many multicast sources (such as SMPTE ST 2110 video and audio streams) start simultaneously.

With PFM-SD, active multicast sources are announced automatically across the fabric. This removes the need for traditional multicast components such as a PIM Rendezvous Point (RP), MSDP, or BSR, which simplifies the fabric design and reduces control-plane complexity.

When a multicast source becomes active, the first-hop router (the switch directly connected to the source) announces the source to the rest of the fabric. These announcements are distributed to all routers using the existing unicast routing, so every router learns about active sources proactively. Receivers can then join a source immediately, without waiting for RP registration.

For detailed information regarding the underlying protocol behavior, CLI configuration, and MSDP integration on Cisco Nexus switches, see the Cisco N9000 Series NX-OS Multicast Routing Configuration Guide.

Benefits of PFM-SD

- Faster source discovery—Receivers join active sources without the delay of RP-based registration.
- Simpler fabric design—No RP, MSDP, or BSR configuration is required for groups using PFM-SD.
- Better scalability—Announcement rate and gap controls prevent control-plane overload when many sources come online at once.

For more information, see Enable PFM-SD.

The following table describes the fields under the **Multicast** tab.

Field	Description
Enable NBM Passive Mode	Check this check box to enable NBM mode to Protocol Independent Multicast (PIM) passive mode. If you enable NBM passive mode, the switch ignores all rendezvous point (RP) and Multicast Source Discovery Protocol (MSDP) configurations. This is a mandatory check box. If you check this check box, the remaining fields and check boxes are disabled. For more information, see the Configuring an NBM VRF for Static Flow Provisioning section of the Cisco N9000 Series NX-OS IP Fabric for Media Solution Guide, Release 10.2(x). You must add the **IP PIM Passive** command when you add the VRF that is in passive mode to the interface. Perform the steps below to add the **IP PIM Passive** command: 1. On the **Fabric Overview** page, choose **Links > Links**. 2. Select the appropriate fabric with the policy **int_ipfm_intra_fabric_num_link** and choose **Actions > Edit**. The **Link Management - Edit Link** page appears. 3. On the **General Parameters** tab, enter the default VRF for the **Interface VRF** name. 4. Click the **Advanced** tab, enter **IP PIM Passive** on the **Source Interface Freeform Config** and **Destination Interface Freeform Config** fields. 5. Click **Save**.  You cannot edit the existing fabric to change the NBM mode. You must delete and recreate the fabric to change the NBM mode from active to passive mode or vice versa.
Enable ASM	Check this check box to enable groups with receiver sending (*,G) joins. If you check this check box, you enable the **Any source multicast** (ASM)-related section.

Field	Description
NBM Flow ASM Groups for default VRF (w/wo SPT-Threshold Infinity)	Specifies ASM-related information. 1. Click the expander arrow next to the title of this section to collapse or expand the section. 2. Use the **Actions** drop-down list to add, edit, or delete the ASM groups in the table. **Add** - Choose this option to open the **Add Item** dialog box. 3. In the **Add Item** dialog box, perform the following steps: a. Enter the appropriate values in the fields and check or clear the check box as follows: ▪ **Group_Address**—Specifies the IP address for the NBM flow ASM group subnet. ▪ **Prefix**—Specifies the subnet mask length for the ASM group subnet. The valid value for the subnet mask length ranges from 4 to 32. For example, 239.1.1.0/25 is the group address with the prefix. b. **Enable_SPT_Threshold**-- Check this check box to enable the shortest path tree (SPT) threshold infinity. 4. Click **Save** to add the configured NBM flow ASM groups to the table or click **Cancel** to discard the values. 5. **Edit** - Check the check box next to the group address and then choose this option to open the **Edit Item** page. 6. Open the edit item and edit the ASM group parameters. 7. Click **Save** to update the values in the table or click **Cancel** to discard the values. 8. Check the **Delete** check box next to the group address and then choose this option to delete the ASM group from the table. The table displays the values for the group address, prefix, and the enabled-SPT threshold.

What's next: Complete the configurations in another tab if necessary, or click **Save** when you have completed the necessary configurations for this fabric.

Enable PFM-SD

Before you begin

Ensure that all switches in the fabric are running Cisco NX-OS Release 10.3(2) or later. If any switch is running an older version, the fabric save operation fails with a version validation error.

Follow these steps to enable PFM-SD for the default VRF on an IPFM fabric.

1. Navigate to the **Fabrics** page.

   Go to **Manage > Fabrics**.


2. From the **Fabrics** table, click an IPFM fabric.

   The **Fabric Overview** page displays.

3. From the **Actions** drop-down list, choose **Edit fabric settings**.

   The **Edit *fabric_name* settings** page displays.

4. Click the **Fabric management** tab and then click the **Multicast** tab.



5. Check the **Enable PFM-SD** check box.

   PFM-SD is enabled for the default VRF across all spine and leaf switches in the fabric.

6. In the **PFM-SD Groups for default VRF** table, add one or more multicast group ranges eligible for PFM-SD source discovery.

   Follow these steps to add multicast group.

   a. From the **Actions** drop-down list, choose **Add**.

      The **Add Item** dialog box appears.



b. Provide the following values.

- **Group Subnet**—provide the IPv4 multicast group subnet address.
- **Prefix**—provide the subnet mask length for the multicast group subnet. Valid values range from 4 to 32.

c. Click **Save** to add the group range to the table.

> A maximum of 20 group ranges is supported per fabric. At least one group range is required.

7. In the **PFM-SD Announcement Gap** field, provide the minimum time gap (in milliseconds) between consecutive PFM-SD announcements.

   This prevents bursts of control-plane traffic and improves scalability when a large number of multicast sources become active simultaneously.

   > Valid values range from 50 to 65535. The default value is 1000.

8. In the **PFM-SD Announcement Rate** field, provide the maximum number of PFM-SD announcements sent per interval.

   > Valid values range from 1 to 65535. The default value is 6.

9. Click **Save** to save the fabric settings.
10. Go to the **Fabric Overview** page, choose **Actions > Recalculate and deploy** to push the configuration to the switches.
11. Review the pending configuration and then click **Deploy all**.
12. After deployment completes, verify that all switches show an **In sync** status.

Guidelines and limitations for PFM-SD

- PFM-SD requires Cisco NX-OS release 10.3(2) or later on all switches in the fabric. If any switch is running an older version, fabric save fails with a version validation error.
- PFM-SD can be selectively enabled for specific multicast group ranges without impacting existing RP-based groups. Only groups matching the configured ranges use PFM-SD; other groups continue to use RP-based mechanisms if configured.
- You cannot disable PFM-SD in fabric settings while multi-site policies (ipfm_pfm_sd_multisite) exist for the default VRF. You must delete the child multi-site policies first and deploy the changes before disabling PFM-SD.
- For non-default VRFs, PFM-SD is configured per-switch using the ipfm_pfm_sd policy template. For more information, see Working with policies when configuring an IPFM fabric.
- For multi-site deployments, each fabric participating in the deployment is configured independently. A deployment may include a mix of PFM-SD-enabled fabrics and traditional RP/MSDP-based fabrics.

Protocols

The fields in this tab are shown below.

Field	Description
Fabric Routing Protocol Tag	Specifies the routing process tag for the fabric.
OSPF Area Id	Specifies the OSPF area ID, if OSPF is used as the IGP within the fabric.  The **OSPF** or **IS-IS** authentication fields are enabled based on your selection in the **Fabric Routing Protocol** field in the **General Parameters** tab.
Enable OSPF Authentication	Check the check box to enable OSPF authentication. Clear the check box to disable it. If you enable this field, the **OSPF Authentication Key ID** and the **OSPF Authentication Key** fields get enabled.
OSPF Authentication Key ID	Indicates that the key ID is populated.
OSPF Authentication Key	Ensure that the OSPF authentication key is the Triple Data Encryption Standard (3DES) key from the switch.  Plain-text passwords are not supported. Log in to the switch, retrieve the encrypted key, and enter it in this field. For more information, see the Retrieving the authentication key section for details.

Field	Description
IS-IS Level	Choose the IS-IS level. Available options are: · **level-1** · **level-2**
Enable IS-IS Network Point-to-Point	Enables network point-to-point on numbered fabric interfaces.
Enable IS-IS Authentication	Check the check box to enable IS-IS authentication. Clear the check box to disable it. If you enable this field, the **IS-IS Key ID** field is auto populated.
IS-IS Authentication Keychain Name	Specifies the name of the IS-IS key chain.
IS-IS Authentication Key ID	Specifies the IS-IS authentication key ID.
IS-IS Authentication Key	Specifies the encrypted IS-IS authentication key. Log in to the switch, retrieve the encrypted key, and enter it in this field. A plain-text password gets converted to a Cisco type 7 password. For more information, see the Retrieve the encrypted IS-IS authentication key section for details.
Enable PIM Hello Authentication	Enables the PIM hello authentication.
PIM Hello Authentication Key	Specifies the PIM hello authentication key.

What's next: Complete the configurations in another tab if necessary, or click **Save** when you have completed the necessary configurations for this fabric.

Advanced

The fields in this tab are shown below.

Field	Description
Intra Fabric Interface MTU	Specifies the maximum transmission unit (MTU) for the intra fabric interface. This value must be an even number. The valid values range from 576 to 9216. This is a mandatory field.

Field	Description
Layer 2 Host Interface MTU	Specifies the MTU for the Layer 2 host interface. This value must be an even number. The valid values range from 1500 to 9216.
Power Supply Mode	Choose the appropriate power supply mode that will be the default mode for the fabric from the drop-down list. This is a mandatory field.
Enable CDP for Bootstrapped Switch	Check this check box to enable the Cisco Discovery Protocol on the management (mgmt0) interface for a bootstrapped switch. By default, for bootstrapped switches, Cisco Discovery Protocol is disabled on the mgmt0 interface.
Enable AAA IP Authorization	Enables AAA IP authorization, when **IP Authorization** is enabled in the remote authentication server. This is required to support Nexus Dashboard in scenarios where customers have strict control of which IP addresses can have access to the switches.
Enable NDFC as Trap Host	Check this check box to enable Nexus Dashboard as an SNMP trap destination. Typically, for a native HA Nexus Dashboard deployment, the eth1 VIP IP address will be configured as SNMP trap destination on the switches. By default, this check box is enabled.
Enable Precision Time Protocol (PTP)	Enables PTP across a fabric. When you select this check box, PTP is enabled globally and on intra fabric interfaces. Additionally, the **PTP Source Loopback Id** and **PTP Domain Id** fields are editable. For more information, see Configuring PTP for IPFM fabrics.
PTP Source Loopback Id	Specifies the loopback interface ID loopback that is used as the source IP address for all PTP packets. The valid values range from 0 to 1023. The PTP loopback ID cannot be the same as the RP loopback ID. Otherwise, an error appears. The PTP loopback ID can be the same as the Border Gateway Protocol (BGP) loopback or user-defined loopback that is created from Nexus Dashboard. The PTP loopback will be created automatically if it is not created.
PTP Domain Id	Specifies the PTP domain ID on a single network. The valid values range from 0 to 127.
PTP Profile	Select a PTP profile from the list. The PTP profile is enabled only on Inter-Switch Links (ISL) links. The supported PTP profiles are IEEE-1588v2, SMPTE-2059-2, and AES67-2015.

Field	Description
Leaf Freeform Config	Adds CLIs that should be added to switches that have the **Leaf**, **Border**, and **Border Gateway** roles.
Spine Freeform Config	Adds CLIs that should be added to switches with a **Spine**, **Border Spine**, **Border Gateway Spine**, and **Super Spine** roles.
Intra-fabric Links Additional Config	Adds CLIs that should be added to the intra fabric links.

What's next: Complete the configurations in another tab if necessary, or click **Save** when you have completed the necessary configurations for this fabric.

Freeform

The fields in this tab are shown below. For more information, see "Enable freeform configurations on fabric switches" in Working with Inventory in Your Nexus Dashboard LAN or IPFM Fabrics.

Field	Description
Leaf Pre-Interfaces Freeform Config	Enter additional CLIs, added before interface configurations, for all Leafs and Tier2 Leafs as captured from Show Running Configuration.
Spine Pre-Interfaces Freeform Config	Enter additional CLIs, added before interface configurations, for all Spines as captured from Show Running Configuration.
Leaf Post-Interfaces Freeform Config	Enter additional CLIs, added after interface configurations, for all Leafs and Tier2 Leafs as captured from Show Running Configuration.
Spine Post-Interfaces Freeform Config	Enter additional CLIs, added after interface configurations, for all Spines as captured from Show Running Configuration.
Intra-fabric Links Additional Config	Add CLIs that should be added to the intra-fabric links.

Manageability

The fields in this tab are shown below.

Field	Description
DNS Server IPs	Specifies the comma-separated list of IP addresses (IPv4 or IPv6) of the Domain Name System (DNS) servers.
DNS Server VRFs	Specifies one VRF for all DNS servers or a comma-separated list of VRFs, one per DNS server.
NTP Server IPs/Hostnames	Specifies a comma-separated list of IP addresses (IPv4/IPv6) or hostnames for the NTP server. Hostnames are limited to 80 characters in length and must not contain any whitespace or special characters, except for hyphens (-) and periods (.).
NTP Server VRFs	Specifies one VRF for all NTP servers or a comma-separated list of VRFs, one per NTP server.

Field	Description
Syslog Server IPs/Hostnames	Specifies a comma-separated list of IP addresses (IPv4/IPv6) or hostnames for the Syslog server. Hostnames are limited to 199 characters in length and should not contain any whitespace or special characters, except for hyphens (-) and periods (.).
Syslog Server Severity	Specifies a comma-separated list of syslog severity values, one per syslog server. The minimum value is 0 and the maximum value is 7. To specify a higher severity, enter a higher number.
Syslog Server VRFs	Specifies one VRF for all syslog servers or a comma-separated list of VRFs, one per syslog server.
AAA Freeform Config	Specifies the AAA freeform Configurations. If AAA configurations are specified in the fabric settings, a **switch_freeform** Policy Template Instance (PTI) with a source as **UNDERLAY_AAA** and description as **AAAConfigurations** is created.

What's next: Complete the configurations in another tab if necessary, or click **Save** when you have completed the necessary configurations for this fabric.

Bootstrap

The fields in this tab are shown below.

Field	Description
Enable Bootstrap	Check this check box to enable the bootstrap feature. Bootstrap functionality allows easy day-0 import and bring-up of new devices into an existing fabric. Bootstrap functionality leverages the NX-OS PowerOn Auto Provisioning (POAP) functionality. After you enable bootstrap functionality, you can enable the DHCP server for automatic IP address assignment for POAP using one of the following methods: · **External DHCP Server** Enter information about the external DHCP server in the **Switch Mgmt Default Gateway** and **Switch Mgmt IP Subnet Prefix** fields. · **Local DHCP Server** Enable the **Local DHCP Server** check box and enter details for the remaining mandatory fields.

Field	Description
Enable Local DHCP Server	Check this check box to initiate enabling of automatic IP address assignment through the local DHCP server. When you check this check box, the **DHCP Scope Start Address** and **DHCP Scope End Address** fields become editable. If you do not check this check box, Nexus Dashboard uses the remote or external DHCP server for automatic IP address assignment.
DHCP Version	Select **DHCPv4** or **DHCPv6** from this drop-down list. When you select **DHCPv4**, the **Switch Mgmt IPv6 Subnet Prefix** field is disabled. If you select **DHCPv6**, the **Switch Mgmt IP Subnet Prefix** field is disabled.  Cisco N9000 and Cisco Nexus 3000 series switches support IPv6 POAP only when switches are either Layer 2 adjacent (eth1 or out-of-band subnet must be a /64) or they are Layer 3 adjacent residing in some IPv6 /64 subnet. Subnet prefixes except /64 are not supported.
DHCP Scope Start Address	Specifies the first IP address in the IP address range to be used for the switch out-of-band POAP.
DHCP Scope End Address-	Specifies the last IP address in the IP address range to be used for the switch out-of-band POAP.
Switch Mgmt Default Gateway	Specifies the default gateway for the management VRF on the switch.
Switch Mgmt IP Subnet Prefix	Specifies the prefix for the mgmt0 interface on the switch. The prefix should be between 8 and 30. *DHCP scope and management default gateway IP address specification* If you specify the management default gateway IP address 10.0.1.1 and subnet mask 24, ensure that the DHCP scope is within the specified subnet, between 10.0.1.2 and 10.0.1.254.
Switch Mgmt IPv6 Subnet Prefix	Specifies the IPv6 prefix for the mgmt0 interface on the switch. The prefix should be between 64 and 126. This field is editable if you enable IPv6 for DHCP.
Enable AAA Config	Check this check box to include an AAA configurations from the **Manageability** tab as part of the device startup configuration post bootstrap.

Field	Description
Bootstrap Freeform Config	(Optional) Enter additional commands as needed. For example, if you require some additional configurations to be pushed to the device and be available post device bootstrap, they can be captured in this field, to save the desired intent. After the devices boot up, they will contain the configuration defined in the **Bootstrap Freeform Config** field. Copy-paste the running configuration to a **freeform config** field with the correct indentation, as seen in the running configuration on the NX-OS switches. The **freeform config** must match the running configuration. For more information on resolving freeform configuration errors in switches, see the Working with Inventory in Your Nexus Dashboard LAN or IPFM Fabrics.
DHCPv4/DHCPv6 Multi Subnet Scope	Specifies the field to enter one subnet scope per line. This field is editable after you check the **Enable Local DHCP Server** check box. The format of the scope should be defined as:
DHCP Scope Start Address, DHCP Scope End Address, Switch Management Default Gateway, Switch Management Subnet Prefix	For example, 10.6.0.2,10.6.0.9,10.6.0.1,24

What's next: Complete the configurations in another tab if necessary, or click **Save** when you have completed the necessary configurations for this fabric.

Add switches

A switch can be added to a single fabric at any point in time. To add switches to a fabric and discover existing or new switches, refer to the "Add Switches to a Fabric" section in Working with Inventory in Your Nexus Dashboard LAN or IPFM Fabrics.

Beginning with Nexus Dashboard 4.3.1 release, Nexus Dashboard adds support for the following switches running NX-OS 10.6(3) release:

- N9348Y12C-SE1
- N9396Y12C-SE1
- N9348Y2C6D-SE1U
- N9396T12C-SE1
- N9364E-SG2-Q
- N9364E-SG2-O

Additional settings

The following sections provide information for additional settings that might be necessary when editing the settings for an IPFM fabric.

Retrieving the authentication key

Retrieve the 3DES encrypted OSPF authentication key

1. SSH into the switch.
2. On an unused switch interface, enable the following:

```
config terminal
   feature ospf
   interface Ethernet1/1
     no switchport
     ip ospf message-digest-key 127 md5 ospfAuth
```

   In the example, **ospfAuth** is the unencrypted password.

   This Step 2 is needed when you want to configure a new key.

3. Enter the **show run interface Ethernet1/1** command to retrieve the password.

```
Switch # show run interface Ethernet1/1
  interface Ethernet1/1
    no switchport
    ip ospf message-digest key 127 md5 3 sd8478f4fsw4f4w34sd8478fsdfw
    no shutdown
```

   The sequence of characters after **md5 3** is the encrypted password.

4. Update the encrypted password into the **OSPF Authentication Key** field.

Retrieve the encrypted IS-IS authentication key

To get the key, you must have access to the switch.

1. SSH into the switch.
2. Create a temporary keychain.

```
config terminal
  key chain isis
  key 127
```

```
  key-string isisAuth
```

In the example, **isisAuth** is the plaintext password. This will get converted to a Cisco type 7 password after the CLI is accepted.

3. Enter the **show run | section "key chain"** command to retrieve the password.

```
key chain isis
  key 127
    key-string 7 071b245f5a
```

The sequence of characters after key-string 7 is the encrypted password. Save it.

4. Update the encrypted password into the ISIS Authentication Key field.
5. Remove any unwanted configuration made in Step 2.

Retrieve the 3DES encrypted BGP authentication key

1. SSH into the switch and enable BGP configuration for a non-existent neighbor.



Non-existent neighbor configuration is a temporary BGP neighbor configuration for retrieving the password.

```
router bgp
  neighbor 10.2.0.2 remote-as 65000
  password bgpAuth
```

In the example, **bgpAuth** is the unencrypted password.

2. Enter the show run bgp command to retrieve the password. A sample output:

```
neighbor 10.2.0.2
  remote-as 65000
  password 3 sd8478fswerdfw3434fsw4f4w34sdsd8478fswerdfw3434fsw4f4w3
```

The sequence of characters after password 3 is the encrypted password.

3. Update the encrypted password into the **BGP Authentication Key** field.
4. Remove the BGP neighbor configuration.

Retrieve the encrypted BFD authentication key

1. SSH into the switch.
2. On an unused switch interface, enable the following:

```
switch# config terminal
switch(config)# int e1/1
switch(config-if)# bfd authentication keyed-SHA1 key-id 100 key passwd
```

In the example, **passwd** is the unencrypted password and the key ID is **100**.



This Step 2 is needed when you want to configure a new key.

3. Enter the **show running-config interface** command to retrieve the key.

```
switch# show running-config interface Ethernet1/1

interface Ethernet1/1
description connected-to- switch-Ethernet1/1
no switchport
mtu 9216
bfd authentication Keyed-SHA1 key-id 100 hex-key 636973636F313233
no ip redirects
ip address 10.4.0.6/30
no ipv6 redirects
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
no shutdown
```

The BFD key ID is **100** and the encrypted key is **636973636F313233**.

4. Update the key ID and key in the **BFD Authentication Key ID** and **BFD Authentication Key** fields.

Interface configuration for IPFM fabrics

Nexus Dashboard allows you to configure IPFM external links for each switch in your fabric. The external device can connect to the network through this interface by marking it an IPFM external link.



A user with the network operator role in Nexus Dashboard cannot save, deploy, undeploy, or edit interface configurations.

Interfaces in IPFM fabrics are managed by Nexus Dashboard interface manager. The default interface policy for IPFM is **int_ipfm_l3_port**.

The following issues are seen when an NBM VRF is deleted from Nexus Dashboard after an an interface is enabled with an NBM external link and unicast BW setting. When this occurs, the affected interfaces continue to show the external link and ucast BW as set.

Perform the following steps to resolve interface issues:

1. Choose all the switches that have these interface issues under the **Configuration > Policies** tab

using **Add policy**.

2. Choose the **host_port_resync** template and click **Save**.
3. Select **Recalculate & Deploy**.

   This syncs switch configuration with Nexus Dashboard.

4. Select **Resync All**.

The following are non-fabric ethernet interface policy templates for IPFM fabrics:

- **int_ipfm_l3_port**
- **int_ipfm_access_host**
- **int_ipfm_trunk_host**

The following are the port-channel interface policy templates for IPFM fabrics:

- **int_ipfm_port_channel_access_host**
- **int_ipfm_port_channel_trunk_host**
- **int_ipfm_port_channel_access_member**
- **int_ipfm_port_channel_trunk_member**

The Switch Virtual Interface (SVI) template for IPFM fabrics is **int_ipfm_vlan**.

Supported templates for configuring interfaces

Template	Description
GigabitEthernet	Interface template for creating a GigabitEthernet interface on an IOS XE switch.
GigabitEthernet_freeform	Interface template for a GigabitEthernet interface using a freeform config on a Cisco Catalyst 9000 series switch.
GigabitEthernet_mgmt	Interface template for a GigabitEthernet interface using a freeform config on a Cisco Catalyst 9000 series switch.
ios_xe_int_access_host	Interface template for creating an access switch port on a Cisco Catalyst 9000 series switch.
ios_xe_int_monitor_ethernet	Interface template for putting an ethernet interface into monitor mode.
ios_xe_int_routed_host	Interface template for creating a Layer 3 routed port on a Cisco Catalyst 9000 series switch.
ios_xe_int_stackwise_dual_active	Interface template for a stackwise virtual dual-active detection.
ios_xe_int_stackwise_link	Interface template for a stackwise virtual link.
ios_xe_int_trunk_host	Interface template for creating a trunk switchport on a Cisco Catalyst 9000 series switch.

Template	Description
ios_xe_ptp_telemetry_template	Interface template for configuring PTP monitoring on a Cisco Catalyst 9000 series switch.

Supported interface types for creating interfaces

You can create the following types of interfaces on a Cisco Catalyst 9000 series switch in a Classic IPFM fabric:

- **Port Channel**
- **Virtual Port Channel (VPC)**
- **Straight-through (ST) FEX**
- **Active-Active (AA) FEX**
- **Loopback**
- **Tunnel**
- **Ethernet**
- **Switch Virtual Interface (SVI)**

For more information on creating interfaces, see the section "Add interfaces" in Working with Connectivity in Your Nexus Dashboard LAN Fabrics.

Create an interface for IPFM fabrics

This section describes the procedure to create a new interface for an IPFM fabric based on the template that you have selected from the available IPFM fabric interface templates.

IPFM fabrics do not support an IPv6 underlay.

To create an interface for IPFM fabrics, perform these steps:

1. Navigate to the **Fabric Overview** page for your fabric and click the **Connectivity > Interfaces** tab.
2. Choose **Create new interface** from the **Actions** drop-down list.

   The **Create new interface** page appears.
3. Choose either **Port Channel**, **Loopback**, or **SVI** as the interface type for IPFM.
4. Choose a device from the drop-down list. The switches (spine and leaf) that are a part of the fabric are displayed in the drop-down list.
5. Enter the **Port Channel ID**, **Loopback ID**, or **VLAN ID**, based on your choice of the interface type.
6. Click the **No Policy Selected** link to select a policy that is specific to IPFM. In the **Select Attached Policy Template** dialog box, choose the required interface policy template and click **Save**.
7. Enter the appropriate values in the **Policy Options** area. Note that the appropriate **Policy Options** fields are displayed based on the policy.

Field	Description
Type - Port Channel	Following are the supported types: • **Port Channel Member Interfaces**—Specify a list of member interfaces, for example, e1/5, eth1/7-9. • **Port Channel Mode**—Choose one of the following channel mode options: **on**, **active**, or **passive**. • **Enable BPDU Guard**—Choose one of the following options for a spanning-tree Bridge Protocol Data Unit (BPDU) guard: ◦ **true**—enables bdpuguard ◦ **false**—disables bpduguard ◦ **no**—returns to default settings
Enable Port Type Fast	Check this check box to enable spanning-tree edge port behavior.
MTU	Specify the maximum transmission unit (MTU) for the port channel or the MTU for the interface. The valid value range for MTU for the interface is from 576 to 9216.
SPEED	Specify the port channel speed or the interface speed.
Access VLAN	Specify the VLAN for the access port.
Trunk Allowed VLANS	Enter one of the following values: • none • all • VLAN ranges, for example, 1-200, 500-2000, 3000
Enable PTP	Check this check box to enable Precision Time Protocol (PTP) for the host interface for the IPFM fabric. For more information about PTP, see Configuring PTP for IPFM fabrics.
PTP Profile	Choose a PTP profile from the drop-down list: **IEEE-1588v2**, **SMPTE-2059-2**, or **AES67-2015**.
PTP VLAN	Specifies the PTP VLAN for a member interface when PTP is enabled.
Port Channel Description	Enter description for the port channel.
Freeform Config	Enter an additional CLI for the port channel if required.
Enable Port Channel	Check this check box to enable the port channel.

Field	Description
Type - Loopback	Following are the available types: • **Interface VRF**—Enter the name of the interface VRF. Enter **default** for default VRF. • **Loopback IP**-- Enter an IPv4 address for the loopback interface. • **Loopback IPv6 address**—Enter an IPv6 address for the loopback interface if the VRF is the non-default VRF. For the default VRF, add the IPv6 address in the freeform configuration. • **Route-Map TAG**—Enter the route-map tag associated with the interface IP. • **Interface Description**-- Enter description for the interface. The maximum size limit is 254 characters. • **Freeform Config**—Enter an additional CLI for the loopback interface if required. • **Enable Interface**—Check this check box to enable the interface.
Type - SVI	Following are the available options: • **Interface VRF**-- Enter the name of the interface VRF. Enter **default** for the default VRF. • **VLAN Interface IP**-- Enter IP address of the VLAN interface. • **IP Netmask Length**—Specify the IP netmask length used with the IP address. The valid value range is from 1 to 31. • **Routing TAG**—Enter the routing tag associated with the interface IP. • **MTU**—Specify the maximum transmission unit (MTU) for the Port Channel or the MTU for the interface. The valid value range for MTU for the interface is from 576 to 9216. • **Disable IP redirects**—Check this check box to disable both IPv4 and IPv6 redirects on the interface. • **IPFM External-Link**-- Check this check box to specify that the interface is connected to an external router. • **Interface Description**-- Enter description for the interface. The maximum size limit is 254 characters. • **Freeform Config**-- Enter an additional CLI for the VLAN interface if required. • **Enable interface**-- Check this check box to enable admin state for the interface.  The **Interface Admin State** field has been renamed to **Enable interface**.

8. Based on your requirements, click one of the following buttons:

- Save - Click **Save** to save the configuration changes.
- Preview - Click **Preview** to open the **Preview interfaces configuration** page and view the details.
- Deploy - Click **Deploy** to configure the interfaces.

What to do next:

If you want to edit the interface, see Edit an interface for IPFM fabrics.

If your interface is ready, add a policy for configuring the IPFM fabric. For more information, see Add a policy for an IPFM fabric

Create a sub-interface for IPFM fabrics

This section describes the procedure to create a new sub-interface for an IPFM fabric.

1. Navigate to the **Fabric Overview** page for your fabric and click the **Connectivity > Interfaces** tab.
2. Select a leaf or a spine switch from the list of devices and choose **Actions > Configuration > Create Subinterface**.

   The **Create Subinterface** page appears.
3. Click the **No Policy Selected** link to select a policy that is specific to IPFM.
4. In the **Select Attached Policy Template** dialog box, choose the **int_ipfm_subif** policy template and click **Select**.
5. Enter the appropriate values in the **Policy Options** area. Note that the appropriate **Policy Options** fields are displayed based on the policy.

Field	Description
Type - Port Channel	Following are the supported types: • **Port Channel Member Interfaces**—Specify a list of member interfaces, for example, e1/5, eth1/7-9. • **Port Channel Mode**—Choose one of the following channel mode options: **on**, **active**, or **passive**. • **Enable BPDU Guard**—Choose one of the following options for a spanning-tree Bridge Protocol Data Unit (BPDU) guard: ◦ **true**—enables bdpuguard ◦ **false**—disables bpduguard ◦ **no**—returns to default settings
Enable Port Type Fast	Check this check box to enable spanning-tree edge port behavior.
MTU	Specify the maximum transmission unit (MTU) for the port channel or the MTU for the interface. The valid value range for MTU for the interface is from 576 to 9216.
SPEED	Specify the port channel speed or the interface speed.

Field	Description
Access Vlan	Specify the VLAN for the access port.
Trunk Allowed Vlans	Enter one of the following values: • none • all • VLAN ranges, for example, 1-200, 500-2000, 3000
Enable PTP	Check this check box to enable Precision Time Protocol (PTP) for the host interface for the IPFM fabric. For more information about PTP, see Configuring PTP for IPFM fabrics.
PTP Profile	Choose a PTP profile from the drop-down list: **IEEE-1588v2**, **SMPTE-2059-2**, or **AES67-2015**.
PTP VLAN	Specifies the PTP VLAN for a member interface when PTP is enabled.
Port Channel Description	Enter description for the port channel.
Freeform Config	Enter an additional CLI for the port channel if required.
Enable Port Channel	Check this check box to enable the port channel.
Type - Loopback	Following are the available types: • **Interface VRF**—Enter the name of the interface VRF. Enter **default** for default VRF. • **Loopback IP**-- Enter an IPv4 address for the loopback interface. • **Loopback IPv6 address**—Enter an IPv6 address for the loopback interface if the VRF is the non-default VRF. For the default VRF, add the IPv6 address in the freeform configuration. • **Route-Map TAG**—Enter the route-map tag associated with the interface IP. • **Interface Description**-- Enter description for the interface. The maximum size limit is 254 characters. • **Freeform Config**—Enter an additional CLI for the loopback interface if required. • **Enable Interface**—Check this check box to enable the interface.

Field	Description
Type - SVI	Following are the available options: • **Interface VRF**-- Enter the name of the interface VRF. Enter **default** for the default VRF. • **VLAN Interface IP**-- Enter IP address of the VLAN interface. • **IP Netmask Length**—Specify the IP netmask length used with the IP address. The valid value range is from 1 to 31. • **Routing TAG**—Enter the routing tag associated with the interface IP. • **MTU**—Specify the maximum transmission unit (MTU) for the Port Channel or the MTU for the interface. The valid value range for MTU for the interface is from 576 to 9216. • **Disable IP redirects**—Check this check box to disable both IPv4 and IPv6 redirects on the interface. • **IPFM External-Link**-- Check this check box to specify that the interface is connected to an external router. • **Interface Description**-- Enter description for the interface. The maximum size limit is 254 characters. • **Freeform Config**-- Enter an additional CLI for the VLAN interface if required. • **Enable interface**-- Check this check box to enable admin state for the interface. The **Interface Admin State** field has been renamed to **Enable interface**.
IPFM Unicast Bandwidth Percentage	Specifies the dedicated percentage of bandwidth for unicast traffic. The remaining percentage is automatically reserved for multicast traffic. If you leave this field blank, IPFM uses a global unicast bandwidth reservation.
IPFM Bandwidth Capacity Percentage	Specifies the dedicated percentage of bandwidth for this interface. If you leave this field blank, Nexus Dashboard IPFM uses a global unicast bandwidth reservation.

6. Based on your requirements, click one of the following buttons:
    - **Save**—Click **Save** to save the configuration changes.
    - **Preview**—Click **Preview** to open the **Preview interfaces configuration** page and view the details.
    - **Deploy**—Click **Deploy** to configure the interfaces.

What to do next:

If you want to edit the interface, see Edit an interface for IPFM fabrics.

If your interface is ready, add a policy for the IPFM fabric. For more information, see Add a policy for an IPFM fabric.

Edit an interface for IPFM fabrics

This section describes the procedure to edit an existing IPFM fabric interface template. You can either change a template or edit the values for any of the editable parameters in the **Policy Options** area.

1. Navigate to the **Fabrics** page.

   Go to **Manage > Fabrics**.

2. From the **Fabrics** table, click an IPFM fabric.

   The **Fabric Overview** page displays.

3. In the **Fabric Overview** page, go to **Connectivity > Interfaces**.
4. Choose an **easyFabric_IPFM** fabric with an **int_ipfm_13_port** policy and an **Up** operational status.
5. From the **Actions** drop-down list, choose **Edit configuration**.

   The **Edit interface(s)** page appears.

6. In the **Policy** field, choose a policy specific to an IPFM fabric.
7. In the **Select Attached Policy Template** dialog box, choose the required interface policy template and click **Save**.
8. Edit the required values in the **Policy Options** area.

   Note that the appropriate **Policy Options** fields are displayed based on the policy. For more information about the parameters, see Create an interface for IPFM fabrics.

   The following fields are specific to the **int_ipfm_l3_port** policy and the subinterface **int_ipfm_subif** policy:

Field	Description
IPFM Unicast Bandwidth Percentage	Specifies the dedicated percentage of bandwidth for unicast traffic. The remaining percentage is automatically reserved for multicast traffic. If you leave this field blank, IPFM uses a global unicast bandwidth reservation.
IPFM Bandwidth Capacity Percentage	Specifies the dedicated percentage of bandwidth for this interface. If you leave this field blank, Nexus Dashboard IPFM uses a global unicast bandwidth reservation.
IPFM External-Link	Check this check box to specify that the interface is connected to an external router.
Border Router	Check this check box to enable the border router configuration on the interface. The interface is a boundary of a Protocol Independent Multicast (PIM) domain.

Field	Description
Interface Description	Enter a description for the interface. The maximum size limit is 254 characters.
Enable Host Source Group Proxy	Check this check box to enable an IGMP host proxy on the interface. The IGMP host proxy connects a PIM-enabled multicast network to a domain different from the PIM domain. For more information on configuring an IGMP source group proxy, see the Cisco N9000 Series NX-OX Multicast Routing Configuration Guide.
IGMP Host Source Group Proxy	You can filter by proxy groups, or you can add a new proxy group. From the **Actions** drop-down list, choose **Add**, **Edit**, **Delete**, or **Insert Above** for adding IGMP proxy groups. When policy groups are associated with an IGMP source group proxy, Nexus Dashboard creates a route map for the corresponding interface. Use the switch-level **Deploy** option to provision the route map on a switch. Choose a group from the drop-down list to filter by IGMP proxy groups.

9. Ensure that you check the **Enable interface** check box.
10. Choose from one of the following options depending on your configuration:
    - Click **Save** to save the configuration changes.
    - Click **Preview** to open the **Preview interfaces configuration** page and view the details.
    - Click **Deploy** to configure the interfaces.

What to do next:

Add a policy for configuring the IPFM fabric. For more information, see Add a policy for an IPFM fabric.

Configure PFM-SD boundary on inter-fabric interfaces

When you enable PFM-SD, first-hop routers announce active multicast sources across the entire fabric. In a multi-site deployment where fabrics are interconnected, these announcements can cross fabric boundaries through inter-fabric interfaces. In some deployments, you may want to contain source discovery within each individual fabric so that each fabric discovers only its own multicast sources.

A PFM-SD boundary blocks PFM-SD advertisements from crossing an inter-fabric interface. Configure a PFM-SD boundary on an interface that connects to a neighbor fabric when you want to keep multicast source discovery contained within the local fabric.

- The PFM-SD boundary controls whether PFM-SD advertisements cross between fabrics. This is independent of the ipfm_pfm_sd_multisite policy, which uses MSDP to intentionally share source information between fabrics. You can use the boundary when you want to contain source discovery, and use the multi-site

policy when you want to share source discovery. For more information, see Add an ipfm_pfm_sd_multisite policy.

- The **PFM-SD boundary** option is available on the interface regardless of whether **PFM-SD** option is enabled at the fabric level. However, the boundary takes effect only when PFM-SD is active in the fabric.

Follow these steps to configure the PFM-SD boundary on an inter-fabric interface.

1. Navigate to the **Fabrics** page.

   Go to **Manage > Fabrics**.

2. From the **Fabrics** table, click an IPFM fabric.

   The **Fabric Overview** page displays.

3. In the **Fabric Overview** page, go to **Connectivity > Interfaces**.
4. Choose the inter-fabric interface that you want to configure.
5. From the **Actions** drop-down list, choose **Edit configuration**.

   The **Edit Interface(s)** page displays.

6. In the Policy Options area, check the IPFM external-link check box.

   This marks the interface as connected to a neighbor fabric.

7. Check the **PFM-SD Boundary** check box.

   This applies the ip pim pfm-sd boundary both command to the interface and blocks PFM-SD advertisements from crossing the fabric boundary.

8. Click **Save**.
9. Click **Deploy** to push the configuration to the switch.

Configuring PTP for IPFM fabrics

The Precision Time Protocol (PTP) is a protocol used to synchronize clocks throughout a computer network. When creating an interface, if you enable the **Enable PTP** check box, PTP is enabled across the fabric and on all the intra-fabric interfaces. The supported PTP profiles for IPFM fabrics are **IEEE-1588v2**, **SMPTE-2059-2**, and **AES67-2015**.

A few things to note about the per-interface PTP profile for nonfabric ethernet interfaces are:

- You must enable PTP and select the PTP profile on each nonfabric ethernet interface.
- A PTP profile can be different from the fabric-level PTP profile.
- You must enable PTP in the fabric settings before you can configure PTP on a nonfabric ethernet interface.



If you disable PTP from the fabric settings, Nexus Dashboard removes the PTP configuration from all the interfaces, that is, both the fabric and nonfabric interfaces.

For more information about PTP monitoring for IPFM fabrics, see the section "PTP monitoring" in Working with Inventory in Your Nexus Dashboard LAN or IPFM Fabrics.

With this release, Nexus Dashboard 4.1.1 added support for PTP telemetry monitoring on Cisco Catalyst 9000 series switches. PTP monitoring uses telemetry and the configuration is similar to PTP monitoring for Cisco Catalyst 9000 series switches. You can retrieve statistics from a Cisco Catalyst 9000 series switch using PTP telemetry monitoring.

Nexus Dashboard added a **ios_xe_ptp_telemetry** policy for configuring PTP telemetry monitoring on Cisco Catalyst 9000 series switches. For more information, see Supported templates for configuring interfaces.

Guidelines for configuring PTP telemetry monitoring on Cisco Catalyst 9000 switches

- Cisco Catalyst 9000 telemetry configuration requires a user-supplied IP address as the source address for telemetry.
- The polling interval on a Cisco Catalyst 9000 series switch is 100th of a second, whereas it is a 1000th of a second (millisecond) on a Cisco N9000 series switch. The PTP template uses the same sampling interval for sensors.
- You can view PTP telemetry sync status on the **Switch Overview > PTP** page. The **Switch Overview > Telemetry Collection** or **Fabric Overview > Telemetry Status** is not applicable for PTP telemetry.

Add the PTP telemetry policy to a Cisco Catalyst 9000 switch

1. Navigate to **Manage > Fabrics** and click on the fabric for which you want to configure PTP telemetry monitoring.

   Fabric Overview displays.

2. Click **Configuration Polices**.

   Configuration Policies > Policies displays.

3. Click **Actions > Add policy**.

   Create Policy displays.

4. Choose the Cisco Catalyst 9000 switch or switches for which you would like to configure PTP monitoring.
5. Click **Next**.

   The Cisco Catalyst 9000 switch or switches appear in **Switch List**.

6. In the **Description** field, enter **telemetry**.

   The **Select Policy Template** dialog box displays.

7. In the search field, enter **telemetry**.

   The **ios_xe_ptp_telemetry** policy displays.

8. Click **Select**.
9. If you are configuring a single Cisco Catalyst 9000 switch, enter the switch management IP address in the **Telemetry Source IP Address** field. If you are configuring multiple Cisco Catalyst 9000 switches, leave the **Telemetry Source IP Address** field empty.
10. In the **Telemetry VRF** field, specify **Mgmt-vrf** as the source VRF.
11. In the **Telemetry Receiver IP Address** field, use the same IP address as you used for importing the Cisco Catalyst 9000 series switch in Nexus Dashboard.
12. In the **PTP Monitoring Interval** field, specify a period in units of 100ths of a second.
13. Click **Save**.
14. Navigate to **Manage > Fabrics > Configuration Policies > Policies**.
15. Click **Actions > Recalculate and deploy** in the toolbar to push the configuration to the Cisco Catalyst 9000 switch or switches.

    Deploy Configuration displays the progress of the deploy operation and the pending configurations.

16. On **Deploy Configuration**, if you click the hyperlink in **Pending Config**, you can view the pending configuration, which configures the PTP telemetry template.
17. Click **Deploy All** to deploy the pending configurations.
18. Once the deployment is successful, click **Close**.

Verify the PTP telemetry policy configuration

1. Navigate to **Manage > Inventory > Switches** to verify that the Cisco Catalyst 9000 switch or switches you added are included in the list of switches.
2. Click on a Cisco Catalyst 9000 switch on which you configured PTP monitoring.

   Switch Overview displays.

3. Click **PTP** for viewing the port status, corrections, and clock status for the telemetry policy pushed to the switch. For more information, see the " PTP monitoring" section in Working with Inventory in Your Nexus Dashboard LAN or IPFM Fabrics.

Edit a PTP telemetry policy configuration

1. Navigate to **Manage > Fabrics** and click on the IPFM fabric for which you want to edit your PTP configuration.

   The **Fabric Overview** page displays.

2. Click **Configuration Polices**.
3. Choose the PTP telemetry policy you want to edit and click **Edit policy** from the **Actions** drop-down list.

   The **Edit policy** page appears.

4. Edit the necessary fields.

5. Click **Save** to save your edits.
6. Click **Recalculate and deploy**.

View the PTP telemetry policy configuration on Topology

1. Navigate to **Manage > Fabrics** and click on the IPFM fabric for which you want to view your PTP configuration.

   The **Fabric Overview** page displays.

2. Click **View in topology** to view a visual representation of the Cisco Catalyst 9000 switch or switches you added for PTP monitoring.

Creating an IPFM fabric group

A Society of Motion Picture and Television Engineers (SMPTE 2022-7)-enabled transmitter duplicates an input stream and sends the input stream using two different paths to a destination receiver, which is also SMPTE 2022-7 enabled. The receiver combines the streams from both paths and reconstructs the original stream. If a packet is lost on path 1, the packet is taken from path 2. This involves two active IPFM fabrics named as red and blue fabrics. You can choose to name the IPFM fabrics other than red and blue fabrics.

You can group 2022-7 redundant fabrics into a fabric group. This feature allows you to associate endpoints and multicast groups from both fabrics for a side-by-side topology view for individual flows.



There is no change to the topology view compared to prior releases if there is no associated redundant flow or the IPFM fabrics are not grouped.

Benefits of creating an IPFM fabric group

- Provides high availability with two switches in an IPFM fabric group
- Provides a single entity for managing IPFM fabrics
- Supports a side-by-side view of the red and blue fabrics for managing and monitoring both fabrics
- Supports the SMPTE 2022-7 standard for sending digital video over an IP network
- Provides endpoint group and multicast group associations

Guidelines and limitations for creating an IPFM fabric group

- You cannot have more than two IPFM fabrics in a single fabric group. If you try to add a third IPFM fabric to a fabric group, you receive an error message.

Create an IPFM fabric group

An IPFM fabric group can contain individual IPFM, IPFM Classic, or Classic LAN fabrics. An IPFM fabric group allows for shared host and flow definitions.

For information on how to create an IPFM fabric group, see the section "Create fabric groups" in

Creating Fabrics and Fabric Groups.

Add a child IPFM fabric to an IPFM fabric group

For information on how to add a child IPFM fabric to an IPFM fabric group, see the section "Add child fabrics to the fabric group" in Creating Fabrics and Fabric Groups.

Associate hosts from two fabrics in a host group

By adding two hosts to the host group, the hosts are associated together and are linked, so you can view the hosts in a side-by-side visual representation.

To associate hosts to a host group, perform the following steps:

1. Click **Manage > Fabrics > Fabric Groups**.
2. Choose a fabric group.

   The **Overview** page of the fabric group displays.
3. Click **Connectivity > Host Groups**.
4. Click **Actions > Add Host Group**.

   The **Add Host Group** page displays.

   To link hosts from two IPFM fabrics, you need to specify the VRF associated with the fabric where the host resides, as well as enter the IP address of the host for each fabric. Optionally, you can add an alias to each host for better recognition.

Field	Description
VRF	Specify the VRF associated with the fabric for where each host resides.
IP Address	Enter the host IP address of the red fabric.
Host Alias	(Optional) Enter the host alias for the red fabric.
IP Address	Enter the host IP address of the blue fabric.
Host Alias	(Optional) Enter the host alias for the ble fabric.

5. Click **Save**.

   Nexus Dashboard adds the hosts to the host group view where you can view the hosts in a side-by-side visual representation.

Associate flows to a host group

To associate flows to a host group, perform the following steps:

1. Click **Manage > Fabrics > Fabric Groups**.
2. Choose a fabric group.

   The **Overview** page of the fabric group displays.

3. Click **Connectivity > Flow Groups**.
4. On the **Flow Groups** page, click **Actions > Add Flow Group**.

   To link flows from two IPFM fabrics in a flow group, you need to specify the VRF associated with the fabric where the flow resides, as well as enter the multicast destination IP address of the flows in each fabric. Optionally, you can add a flow alias and a description for better recognition. Nexus Dashboard adds the flows to the host group view in a side-by-side representation.

Field	Description
VRF	Specify the VRF associated with the fabric for where the flow resides.
IP Address	Enter the multicast IP address for the red fabric.
Flow Alias	(Optional) Enter the flow alias for the red fabric.
Description	(Optional) Enter the description for the red fabric.
IP Address	Enter the multicast IP address for the blue fabric.
Flow Alias	(Optional) Enter the flow alias for the ble fabric.
Description	(Optional) Enter the description for the blue fabric.

5. Click **Save** and close the **Fabric Overview** page.

   Nexus Dashboard adds the flows to the flow group view where you can view a side-by-side representation of both flows.

View side-by-side associations of IPFM member fabrics

You can view side-by-side associations of IPFM member fabrics on the **Flows > Flow Status** page.

1. Navigate to the **Manage > Fabrics** page, and click on a child member of an IPFM fabric group.

   The **Fabric Overview** page displays.

2. Click on **Connectivity > Flows**.
3. Click on **Flow Status** and under the **Flow Link State** column, click on the **active** link.

   Nexus Dashboard displays a side-by-side representation of the two fabrics and the grouped flows.

4. To access the same page from the topology view, click **View in topology**.
5. Right-click on the fabric group and click **Detailed View**.

   The **Fabric Overview** page displays.

6. Right-click on a member of the fabric group.

   The **Fabric Overview** page displays.

Working with policies when configuring an IPFM fabric

Fabric settings apply a uniform configuration across all leaf and spine switches in a fabric. When you

need to configure a feature on specific switches, or configure settings that differ between switches, you can use policy templates.

Nexus Dashboard provides several policy templates for IPFM fabrics. The following are the available templates.

Policy template	Purpose
ipfm_tcam_nat_9300	Configures NAT TCAM on Cisco Catalyst 9300 switches.
ipfm_telemetry	Configures telemetry for IPFM fabrics.
ipfm_vrf	Configures VRF settings, including routing, PIM, and ASM.
ipfm_pfm_sd	Configures PFM-SD for a non-default VRF on a specific switch.
ipfm_pfm_sd_multisite	Configures MSDP peering between border switches in neighbor fabrics for inter-fabric multicast source sharing.

Add a policy for an IPFM fabric

Follow these steps to add a policy to one or more switches in an IPFM fabric.

1. Navigate to the **Fabrics** page.


   Go to **Manage > Fabrics**.

2. From the **Fabrics** table, click an IPFM fabric.

   The **Fabric Overview** page displays.

3. Click the **Configuration policies** tab.
4. From the **Actions** drop-down list, choose **Add policy**.

   The **Add Policy** page displays.



5. Choose one or more switches and click **Next**.

6. Under **Configure policy**, click **Select Policy Template**.

   The **Select Policy Template** page appears.

7. Choose the required template, for example, **ipfm_tcam_nat_9300**.
8. Click **Select**.
9. Enter a priority for the template. The valid value ranges are from 1 to 1000.
10. Enter the values in the template-specific fields, then click Save.



The fields that appear depend on the template you chose. For example, the ipfm_tcam_nat_9300 template requires you to enter the TCAM size in increments of 256.

11. Navigate to **Manage > Fabrics > Configuration Policies > Policies**.
12. From the toolbar, choose **Actions > Recalculate and deploy** to push the configuration to the switch or switches.
13. Review the pending configuration and then click **Deploy all**.
14. After deployment, verify that all switches show an **In sync** status.

Edit a policy for an IPFM fabric

Follow these steps to edit an existing policy on a switch in an IPFM fabric.

1. Navigate to the **Fabrics** page.

   Go to **Manage > Fabrics**.

2. From the **Fabrics** table, click an IPFM fabric.

   The **Fabric Overview** page displays.

3. Click the **Configuration policies** tab.
4. From the policies table choose the policy you want to edit.
5. From the **Actions** drop-down list, choose **Edit policy**.

   The **Edit policy** page appears.

6. Make the required changes and click **Save & view summary**.
7. From the toolbar, choose **Actions > Recalculate and deploy** to push the updated configuration to the switches.
8. Review the pending configuration and then click **Deploy all**.
9. After deployment, verify that all switches show an **In sync** status.


PFM-SD policies for non-default VRFs and multi-site deployments

Nexus Dashboard provides the following two additional policy templates to support PFM-SD in non-default VRFs and across multi-site deployments.

Template	Purpose
ipfm_pfm_sd	Configures PFM-SD for a non-default VRF on a specific switch.
ipfm_pfm_sd_multisite	Configures MSDP peering between border switches in neighbor fabrics for inter-fabric multicast source sharing.

The ipfm_pfm_sd_multisite policy depends on the ipfm_pfm_sd policy. Before you create an ipfm_pfm_sd_multisite policy, an ipfm_pfm_sd policy must already exist for the same VRF on the same switch. You also cannot delete an ipfm_pfm_sd policy while an ipfm_pfm_sd_multisite policy exists for the same VRF. You must first delete the ipfm_pfm_sd_multisite policy.

The following diagram illustrates the configuration workflow for PFM-SD on a non-default VRF.



Prerequisites for configuring PFM-SD on a non-default VRF

Before you can add an ipfm_pfm_sd policy for a non-default VRF, you must complete the following prerequisite tasks in order.

1. Create the non-default VRF on the fabric.
2. Create a loopback interface and assign it to the non-default VRF.

These prerequisites are required because the ipfm_pfm_sd policy uses the loopback interface in the non-default VRF as the source IP for PFM-SD announcements. If either is missing, the policy deployment fails with a validation error.

These prerequisites apply only to non-default VRF configurations. For the default VRF, PFM-SD is configured directly through fabric settings and does not require these steps.

Create a non-default VRF

Follow these steps to create a non-default VRF on an IPFM fabric.

1. Navigate to the **Fabrics** page.

   Go to **Manage > Fabrics**.

2. From the Fabrics table, click an IPFM fabric.

   The **Fabric Overview** page displays.

3. Click the **Configuration policies** tab.
4. From the **Actions** drop-down list, choose **Add policy**.

   The **Add Policy** page displays.

5. Under **Select switches**, choose the switches for which you want to create non-default VRF and click **Next**.
6. Under **Configure policy**, provide the following information.

Field	Description
Switch list	Displays the switches you chose.
Priority	Provide a priority value for this policy. Valid values range from 1 to 1000. The default value is 500.
Description	Provide a description for the VRF.
Policy template	1. Click **Select policy template**. 2. In the **Filter by attributes** field, choose **Name**, **contains**, and enter ipfm_vrf. 3. From the policies table choose ipfm_vrf and click **Select**.
Group	Click the toggle button to create a single policy instance shared across all chosen switches, instead of creating individual policy instances per switch. You can use this option when you want to apply the same VRF configuration uniformly to multiple switches.

7. In the **VRF name** field, provide a unique name for the non-default VRF (for example, red).
8. Click **Save** to save the configuration.

   The new configuration appears under the **Policy configuration summary**.

9. Click **Done**.
10. Navigate to the **Fabric Overview** page, from the **Actions** drop-down list, choose **Recalculate and deploy** to push the VRF configuration to the switches.
11. Review the pending configuration, then click **Deploy all**.
12. After deployment completes, verify that all switches show an **In sync** status.

Create a loopback interface for the non-default VRF

After the non-default VRF is created and deployed, create a loopback interface and assign it to that VRF. This loopback serves as the source interface for PFM-SD announcements.

Follow these steps to create a loopback interface for the non-default VRF.

1. Navigate to the **Fabrics** page.

   Go to **Manage > Fabrics**.

2. From the Fabrics table, click an IPFM fabric.

   The **Fabric Overview** page displays.

3. Click the **Inventory** tab.
4. From the **Switches** table, click the switch on which you want to create the loopback interface.

   The **Switch Overview** page displays.

5. In the **Switch Overview** page, click the **Connectivity** tab.
6. In the **Interfaces** table, click **Actions > Create interface**.

   The **Create interface** page displays.

7. From the **Type** drop-down list, choose **Loopback**.
8. From the **Select a device** drop-down list, choose the switch on which you want to create the loopback interface.
9. In the **Loopback ID** field, provide a unique loopback ID.
10. In the **Policy options** area, provide the following information.

Field	Description
Interface VRF	Provide the name of the non-default VRF you created earlier (for example, red). For more information, see Create a non-default VRF.
Loopback IP	Provide an IPv4 address for the loopback interface. You must assign this IP address manually.
Secondary loopback ips	(Optional)
Routing tag	(Optional) Provide the routing tag associated with the interface IP.
Advertise loopback	(Optional)Check this option to advertise loopback by configuring OSPF/IS-IS on the interface.
Is service-reflect interface	(Optional)Check this option if this loopback used as service reflect source. Change of this parameter requires recalculate config from the fabric.
Interface description	(Optional) Provide a description for the interface. The maximum size limit is 254 characters.
Freeform Config	(Optional) Provide additional CLI commands for the loopback interface if required.
Enable Interface	Check this check box to enable the interface.

OSPF and PIM parameters are automatically added by the template. You only need to manually assign the loopback IP address and the VRF.

11. Click **Save**.
12. Navigate to the **Fabrics** page (go to **Manage > Fabrics**).
13. From the **Actions** drop-down list, choose **Recalculate and deploy** to push the loopback configuration to the switch.
14. Review the pending configuration, then click **Deploy all**

After you create a non-default VRF and a loopback interface you can enable PFM-SD for the switch. For more information. see Enable PFM-SD.

Add an ipfm_pfm_sd policy (non-default VRF)

You can use the ipfm_pfm_sd policy to configure PFM-SD for a non-default VRF on a specific switch. The default VRF is configured at the fabric level through fabric settings and does not require this policy.

Follow these steps to add an ipfm_pfm_sd policy.

1. Navigate to the **Fabrics** page.

   Go to **Manage > Fabrics**.

2. From the Fabrics table, click an IPFM fabric.


   The **Fabric Overview** page displays.

3. Click the **Inventory** tab.
4. From the **Switches** table, click the switch.

   The **Switch Overview** page displays.

5. In the **Switch Overview** page, click the **Configuration policies** tab.
6. From the **Actions** drop-down list, choose **Add policy**.

   The **Add Policy** page displays.



7. Under **Configure policy**, provide description of the PFM-SD policy.
8. Click **Select Policy Template**.

   The **Select Policy Template** page appears.

9. In the **Select Policy Template** page, in the **Filter by attributes** field, choose **Name**, **contains**, and enter pfm_sd.
10. From the policies table choose ipfm_pfm_sd and click **Select**.

    The following fields display under **Configure policy**.

Field	Description
VRF Name	Provide the non-default VRF name.
Originator Loopback	Provide the loopback interface ID used as the PFM-SD source. The loopback must exist in the specified VRF. Valid values range from 0 to 1023.
PFM-SD Announcement Gap	Provide the gap in milliseconds between announcements. Valid values range from 100 to 65535. The default value is 1000.
PFM-SD Announcement Rate	Provide the rate of announcements per interval. Valid values range from 1 to 60. The default value is 10.

11. In the **PFM-SD Groups** table, add one or more multicast group ranges eligible for PFM-SD source discovery.

    Follow these steps to add multicast group.

    a. From the **Actions** drop-down list, choose **Add**.

       The **Add Item** dialog box appears.



b. Provide the following values.

- **Group Subnet**—provide the IPv4 multicast group subnet address.
- **Prefix**—provide the subnet mask length for the multicast group subnet. Valid values range from 4 to 32.

c. Click **Save** to add the group range to the table.

12. Click **Save**.

    You can view the summary of policy changes under **Policy configuration summary**.

13. Navigate to **Manage > Fabrics**.
14. From the **Actions** drop-down list, choose **Recalculate and deploy** to push the configuration to the switch.
15. Review the pending configuration, then click **Deploy all**.

Add an ipfm_pfm_sd_multisite policy

You can use the ipfm_pfm_sd_multisite policy to configure MSDP peering on a border switch for inter-fabric multicast source sharing.

Before you begin

Ensure that an ipfm_pfm_sd policy already exists for the target VRF on this switch. For the default VRF, ensure that PFM-SD is enabled in fabric settings. The switch must be running Cisco NX-OS Release 10.6(3) or later.

Follow these steps to add an ipfm_pfm_sd_multisite policy.

1. Navigate to the **Fabrics** page.

   Go to **Manage > Fabrics**.

2. From the **Fabrics** table, click an IPFM fabric.


   The **Fabric Overview** page displays.

3. Click the **Inventory** tab.
4. From the **Switches** table, click the switch.

   The **Switch Overview** page displays.

5. In the **Switch Overview** page, click the **Configuration policies** tab.
6. From the **Actions** drop-down list, choose **Add policy**.

   The **Add Policy** page displays.



7. Under **Select switches**, choose the switch on which you want to configure the PFM-SD policy and click **Next**.
8. Under **Configure policy**, provide description of the PFM-SD policy.
9. Click **Select Policy Template**.

   The **Select Policy Template** page appears.

10. In the **Select Policy Template** page, in the **Filter by attributes** field, choose **Name**, **contains**, and enter pfm_sd.
11. From the policies table choose ipfm_pfm_sd_multisite and click **Select**.

    The following fields display under **Configure policy**.

Field	Description
VRF Name	Provide the VRF name. The VRF name must match the VRF used in ipfm_pfm_sd policy (or use default for fabric-level PFM-SD).

Field	Description
MSDP Peer IPs	Specifies the list of MSDP peer IP addresses from the neighbor fabrics. Use the **Actions** drop-down list to add, edit, or delete peer IPs. At least one peer IP is required. You must create ipfm_pfm_sd policy for the same VRF on this switch before adding MSDP peer IPs.
Use Custom Multisite Route-Map	Check this check box to define a custom route-map for multi-site SA (Source Active) message filtering that is separate from the local PFM-SD route-map. Checking this check box enables the **Multisite PFM-SD Groups** table. You must configure at least one multi-site group range.

12. In the **Multisite PFM-SD Groups** table, add one or more multicast group ranges eligible for PFM-SD source discovery.

    Follow these steps to add multicast group.

    a. From the **Actions** drop-down list, choose **Add**.

    The **Add Item** dialog box appears.



    b. Provide the following values.

    - **Group Subnet**—provide the IPv4 multicast group subnet address.
    - **Prefix**—provide the subnet mask length for the multicast group subnet. Valid values range from 4 to 32.

c. Click **Save** to add the group range to the table.

13. Click **Save**.

    You can view the summary of policy changes under **Policy configuration summary**.

14. Navigate to **Manage > Fabrics**.
15. From the **Actions** drop-down list, choose **Recalculate and deploy** to push the configuration to the switch.
16. Review the pending configuration, then click **Deploy all**.

Disable PFM-SD

Disabling PFM-SD removes the PFM-SD configuration from all switches in the fabric. To disable PFM-SD on a fabric without encountering validation errors, you must delete its dependent policies in the correct reverse order of creation.

- Deleting a policy removes the entire policy from the switch, not just individual peer addresses or group ranges.
- Non-default VRF PFM-SD configurations do not appear in the default fabric settings. They must be deleted as separate per-switch policies before the fabric-level PFM-SD can be disabled.
- If you attempt to disable PFM-SD while child policies still exist, Nexus Dashboard displays a validation error preventing the save operation.

Follow these steps to disable PFM-SD on an IPFM fabric.

1. Delete all ipfm_pfm_sd_multisite policies. Navigate to **Configuration policies** and choose each multi-site policy. Click **Actions > Delete policy**. Then choose **Actions > Recalculate and deploy** to remove the MSDP configuration from the switches.
2. Delete all ipfm_pfm_sd policies for non-default VRFs. Navigate to **Configuration policies** and choose each ipfm_pfm_sd policy. Click **Actions > Delete policy**. Then choose **Actions > Recalculate and deploy** to remove the non-default VRF PFM-SD configuration.
3. Disable PFM-SD in fabric settings. From the **Fabric Overview** page, choose **Actions > Edit fabric settings**. Click the **Fabric management** tab, then click the **Multicast** tab. Uncheck the **Enable PFM-SD** check box and click **Save**.
4. In the **Fabric Overview** page, choose **Actions > Recalculate and deploy** to remove the default VRF configuration.
5. Review the pending configuration, then click **Deploy all**.
6. After deployment completes, verify that all switches show an **In sync** status.

Copyright

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

The documentation set for this product strives to use bias-free language. For the purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

© 2017-2026 Cisco Systems, Inc. All rights reserved.

Americas Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706

USA
https://www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883