

Configuring Active Buffer Monitoring

This chapter contains the following sections:

- Information About Active Buffer Monitoring, on page 1
- Configuring Active Buffer Monitoring, on page 2
- Displaying Buffer Histogram Data, on page 3

Information About Active Buffer Monitoring

Active Buffer Monitoring Overview

The Active Buffer Monitoring feature provides detailed buffer occupancy data to help you detect network congestion, review past events to understand when and how network congestion is affecting network operations, understand historical trending, and identify patterns of application traffic flow.

A hardware component, called the Algorithm Boost Engine (Algo Boost Engine) supports buffer histogram counters for unicast buffer usage per individual port, total buffer usage per buffer block, and multicast buffer usage per buffer block. Each histogram counter has 18 buckets that span across the memory block. The Algo Boost Engine polls buffer usage data every hardware sampling interval (the default is every 4 milliseconds, but you can configure it to be as low as 10 nanoseconds). Based on the buffer utilization, the corresponding histogram counter is incremented. For example, if Ethernet port 1/4 is consuming 500 KB of the buffer, the bucket 2 counter (which represents 384 KB to 768 KB) for Ethernet 1/4 is incremented.

To avoid a counter overflow, the Cisco NX-OS software collects the histogram data every polling interval and maintains it in the system memory. The software maintains the histogram data in the system memory for the last 60 minutes with 1-second granularity. Every hour, the software copies the buffer histogram data from the system memory to the bootflash as a backup.

The Active Buffer Monitoring feature has two modes of operation:

- Unicast mode—The Algo Boost Engine monitors and maintains a buffer histogram for total buffer utilization per buffer block and unicast buffer utilization for all 48 ports.
- Multicast mode—The Algo Boost Engine monitors and maintains buffer histogram data for total buffer utilization per buffer block and multicast buffer utilization per buffer block.

Buffer Histogram Data Access and Collection

After active buffer monitoring is enabled, the device maintains 70 minutes of data—the first 60 minutes (0 to 60 minutes) in the log and another 60 minutes (10 to 70 minutes) in memory.

You can access buffer histogram data using several methods:

- You can access it from the system memory using **show** commands.
- You can integrate the Active Buffer Monitoring feature with Cisco NX-OS Python scripting to collect historical data by copying the data to a server regularly.
- You can access the buffer histogram data using an XML interface.
- You can configure Cisco NX-OS to log a message in the syslog whenever the buffer occupancy exceeds the configured threshold.

Configuring Active Buffer Monitoring

Note If you use NX-API over the front panel port, you must increase the CoPP policy (for HTTP) to allow 3000 PPS traffic. Doing so prevents packet drops, and the CLIs, creating larger outputs, return within the expected time.

Note Active Buffer Monitoring (ABM) is enabled on all front ports, but only default class traffic can be monitored.

SUMMARY STEPS

1. switch# **configure terminal**
2. switch(config)# **hardware profile buffer monitor** {**unicast** | **multicast**}
3. switch(config)# **hardware profile buffer monitor** {**unicast** | **multicast**} **threshold** *threshold-value*
4. switch(config)# **hardware profile buffer monitor** {**unicast** | **multicast**} **sampling** *sampling-value*
5. (Optional) switch(config)# **copy running-config startup-config**

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	switch# **configure terminal**	Enters global configuration mode.
Step 2	switch(config)# **hardware profile buffer monitor** {**unicast** | **multicast**}	Enables the hardware profile buffer for either unicast or multicast traffic.

	Command or Action	Purpose
Step 3	switch(config)# **hardware profile buffer monitor** {**unicast** | **multicast**} **threshold** *threshold-value*	Generates a syslog entry when the specified maximum buffer size is exceeded. The range is 384–6144 kilobytes with 384-kilobyte increments. The default is 90 percent of the total available shared buffer.
Step 4	switch(config)# **hardware profile buffer monitor** {**unicast** | **multicast**} **sampling** *sampling-value*	Specifies to sample data at the specified interval. Range is 10–20,000,000 nanoseconds. The default sampling value is 4 milliseconds.
Step 5	(Optional) switch(config)# **copy running-config startup-config**	Saves the change persistently through reboots and restarts by copying the running configuration to the startup configuration.

Example

This example shows how to configure Active Buffer Monitoring for unicast traffic. A threshold value of 384 kilobytes and a sampling value of 5000 nanoseconds is used:

```
switch# configure terminal
switch(config)# hardware profile buffer monitor unicast
switch(config)# hardware profile buffer monitor unicast threshold 384
switch(config)# hardware profile buffer monitor unicast sampling 5000
switch(config)# copy running-config startup-config
```

The following example shows how to configure Active Buffer Monitoring for multicast traffic. A threshold value of 384 kilobytes and a sampling value of 5000 nanoseconds is used.

```
switch# configure terminal
switch(config)# hardware profile buffer monitor multicast
switch(config)# hardware profile buffer monitor multicast threshold 384
switch(config)# hardware profile buffer monitor multicast sampling 5000
switch(config)# copy running-config startup-config
```

Displaying Buffer Histogram Data

SUMMARY STEPS

1. switch# **show hardware profile buffer monitor** [**interface ethernet** *slot/port*] {**brief** | **buffer-block** | **detail** | **multicast** | **summary**}
2. (Optional) switch# **clear hardware profile buffer monitor**

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	switch# **show hardware profile buffer monitor** [**interface ethernet** *slot/port*] {**brief** | **buffer-block** | **detail** | **multicast** | **summary**}	Displays data collected about the buffer. The keywords are defined as follows: • **brief**—Specifies to show limited information about each interface. • **buffer-block**—Specifies to display information about a specific buffer block. • **detail**—Specifies to display all information gathered for each interface. • **interface**—(Optional) Specifies to display information about a specific port. • **multicast**—Specifies to show buffer data for multicast traffic only. • **summary**—Specifies to display summary information about each buffer block. **Note** The show command option **interface** is only multicast mode.
Step 2	(Optional) switch# **clear hardware profile buffer monitor**	Clears the collected buffer data.

Example

This example shows how to display summary information for each buffer block and for all of the buffers combined:

```
switch# show hardware profile buffer monitor summary
Summary CLI issued at: 09/18/2012 07:38:39

                    Maximum buffer utilization detected
                  1sec     5sec    60sec     5min      1hr
                 ------   ------   ------   ------   ------
Buffer Block 1       0KB      0KB      0KB      0KB      N/A

Total Shared Buffer Available = 5049 Kbytes
Class Threshold Limit = 4845 Kbytes
============================================================
Buffer Block 2       0KB      0KB      0KB      0KB      N/A

Total Shared Buffer Available = 5799 Kbytes
Class Threshold Limit = 5598 Kbytes
```

```
============================================================
Buffer Block 3       0KB      0KB   5376KB   5376KB      N/A

Total Shared Buffer Available = 5799 Kbytes
Class Threshold Limit = 5598 Kbytes
```

This example shows how to display the maximum buffer utilization of each buffer block and each interface for unicast mode:

```
switch# show hardware profile buffer monitor brief
Brief CLI issued at: 09/18/2012 07:38:29

                  Maximum buffer utilization detected
                 1sec     5sec    60sec     5min      1hr
                ------   ------   ------   ------   ------
Buffer Block 1       0KB      0KB      0KB      0KB      N/A

Total Shared Buffer Avaliable = 5049 Kbytes
Class Threshold Limit = 4845 Kbytes
------------------------------------------------------------
Ethernet1/45         0KB      0KB      0KB      0KB      N/A
Ethernet1/46         0KB      0KB      0KB      0KB      N/A
Ethernet1/47         0KB      0KB      0KB      0KB      N/A
Ethernet1/48         0KB      0KB      0KB      0KB      N/A
Ethernet1/21         0KB      0KB      0KB      0KB      N/A
Ethernet1/22         0KB      0KB      0KB      0KB      N/A
Ethernet1/23         0KB      0KB      0KB      0KB      N/A
Ethernet1/24         0KB      0KB      0KB      0KB      N/A
Ethernet1/9          0KB      0KB      0KB      0KB      N/A
Ethernet1/10         0KB      0KB      0KB      0KB      N/A
Ethernet1/11         0KB      0KB      0KB      0KB      N/A
Ethernet1/12         0KB      0KB      0KB      0KB      N/A
Ethernet1/33         0KB      0KB      0KB      0KB      N/A
Ethernet1/34         0KB      0KB      0KB      0KB      N/A
Ethernet1/35         0KB      0KB      0KB      0KB      N/A
Ethernet1/36         0KB      0KB      0KB      0KB      N/A
============================================================
Buffer Block 2       0KB      0KB      0KB      0KB      N/A

Total Shared Buffer Avaliable = 5799 Kbytes
Class Threshold Limit = 5598 Kbytes
------------------------------------------------------------
Ethernet1/17         0KB      0KB      0KB      0KB      N/A
Ethernet1/18         0KB      0KB      0KB      0KB      N/A
Ethernet1/19         0KB      0KB      0KB      0KB      N/A
Ethernet1/20         0KB      0KB      0KB      0KB      N/A
Ethernet1/5          0KB      0KB      0KB      0KB      N/A
Ethernet1/6          0KB      0KB      0KB      0KB      N/A
Ethernet1/7          0KB      0KB      0KB      0KB      N/A
Ethernet1/8          0KB      0KB      0KB      0KB      N/A
Ethernet1/41         0KB      0KB      0KB      0KB      N/A
Ethernet1/42         0KB      0KB      0KB      0KB      N/A
Ethernet1/43         0KB      0KB      0KB      0KB      N/A
Ethernet1/44         0KB      0KB      0KB      0KB      N/A
Ethernet1/29         0KB      0KB      0KB      0KB      N/A
Ethernet1/30         0KB      0KB      0KB      0KB      N/A
Ethernet1/31         0KB      0KB      0KB      0KB      N/A
Ethernet1/32         0KB      0KB      0KB      0KB      N/A
============================================================
Buffer Block 3       0KB      0KB   5376KB   5376KB      N/A

Total Shared Buffer Avaliable = 5799 Kbytes
```

```
Class Threshold Limit = 5598 Kbytes
-----------------------------------------------------------
Ethernet1/13          0KB       0KB       0KB       0KB       N/A
Ethernet1/14          0KB       0KB       0KB       0KB       N/A
Ethernet1/15          0KB       0KB       0KB       0KB       N/A
Ethernet1/16          0KB       0KB       0KB       0KB       N/A
Ethernet1/37          0KB       0KB       0KB       0KB       N/A
Ethernet1/38          0KB       0KB       0KB       0KB       N/A
Ethernet1/39          0KB       0KB       0KB       0KB       N/A
Ethernet1/40          0KB       0KB       0KB       0KB       N/A
Ethernet1/25          0KB       0KB       0KB       0KB       N/A
Ethernet1/26          0KB       0KB       0KB       0KB       N/A
Ethernet1/27          0KB       0KB       0KB       0KB       N/A
Ethernet1/28          0KB       0KB       0KB       0KB       N/A
Ethernet1/1           0KB       0KB       0KB       0KB       N/A
Ethernet1/2           0KB       0KB       0KB       0KB       N/A
Ethernet1/3           0KB       0KB       0KB       0KB       N/A
Ethernet1/4           0KB       0KB    5376KB    5376KB       N/A
```

This example shows how to display the maximum buffer utilization information of each buffer block for multicast mode:

```
switch# show hardware profile buffer monitor brief
Brief CLI issued at: 09/18/2012 08:30:08

                    Maximum buffer utilization detected
                  1sec      5sec     60sec      5min       1hr
                 ------    ------    ------    ------    ------
Buffer Block 1       0KB       0KB       0KB       0KB       0KB

Total Shared Buffer Avaliable = 5049 Kbytes
Class Threshold Limit = 4845 Kbytes
Mcast Usage 1        0KB       0KB       0KB       0KB       0KB
============================================================
Buffer Block 2       0KB       0KB       0KB       0KB       0KB

Total Shared Buffer Avaliable = 5799 Kbytes
Class Threshold Limit = 5598 Kbytes
Mcast Usage 2        0KB       0KB       0KB       0KB       0KB
============================================================
Buffer Block 3       0KB       0KB       0KB       0KB       0KB

Total Shared Buffer Avaliable = 5799 Kbytes
Class Threshold Limit = 5598 Kbytes
Mcast Usage 3        0KB       0KB       0KB       0KB       0KB
```

The following example shows how to display detailed buffer utilization information of buffer block 3 for multicast mode:

```
switch# show hardware profile buffer monitor multicast 3 detail
Detail CLI issued at: 09/18/2012 08:30:12

Legend -
384KB  - between   1 and 384KB of shared buffer consumed by port
768KB  - between 385 and 768KB of shared buffer consumed by port
307us  - estimated max time to drain the buffer at 10Gbps

Active Buffer Monitoring for Mcast Usage 3 is: Active
KBytes                384  768 1152 1536 1920 2304 2688 3072 3456 3840 4224 4608 4992 5376
 5760 6144
us @ 10Gbps           307  614  921 1228 1535 1842 2149 2456 2763 3070 3377 3684 3991 4298
```

```
 4605 4912
                      ---- ---- ---- ---- ---- ---- ---- ---- ---- ---- ---- ---- ---- ----
 ---- ----
09/18/2012 08:30:12      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 08:30:11      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 08:30:10      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 08:30:09      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 08:30:08      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 08:30:07      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 08:30:06      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 08:30:05      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 08:30:04      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 08:30:03      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
```

The following example shows how to display detailed buffer data about Ethernet interface 1/4:

```
switch# show hardware profile buffer monitor interface ethernet 1/4 detail
Detail CLI issued at: 09/18/2012 07:38:43

Legend -
384KB  - between   1 and 384KB of shared buffer consumed by port
768KB  - between 385 and 768KB of shared buffer consumed by port
307us  - estimated max time to drain the buffer at 10Gbps

Active Buffer Monitoring for port Ethernet1/4 is: Active
KBytes                384  768 1152 1536 1920 2304 2688 3072 3456 3840 4224 4608 4992 5376
 5760 6144
us @ 10Gbps           307  614  921 1228 1535 1842 2149 2456 2763 3070 3377 3684 3991 4298
 4605 4912
                      ---- ---- ---- ---- ---- ---- ---- ---- ---- ---- ---- ---- ---- ----
 ---- ----
09/18/2012 07:38:42      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:41      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:40      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:39      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:38      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:37      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:36      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:35      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:34      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:33      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:32      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:31      0    0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
```

```
09/18/2012 07:38:30      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:29      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:28      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:27      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:26      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:25      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:24      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:23      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:22      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:21      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:20    177   36    0    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:19      0  143  107    0    0    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:18      0    0   72  178    3    0    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:17      0    0    0    0  176   74    0    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:16      0    0    0    0    0  105  145    0    0    0    0    0    0
0    0    0
09/18/2012 07:38:15      0    0    0    0    0    0   33  179   38    0    0    0    0
0    0    0
09/18/2012 07:38:14      0    0    0    0    0    0    0    0  140  113    0    0    0
0    0    0
09/18/2012 07:38:13      0    0    0    0    0    0    0    0    0   66  178    6    0
0    0    0
09/18/2012 07:38:12      0    0    0    0    0    0    0    0    0    0    0  173   77
0    0    0
09/18/2012 07:38:11      1    0    0    1    0    0    1    0    0    1    0    0  102
42    0    0
09/18/2012 07:38:10      0    0    0    0    0    0    0    0    0    0    0    0    0
0    0    0
```