

Flexible Netflow—Egress VRF Support

The Flexible Netflow—Egress VRF Support feature enables collecting the virtual routing and forwarding (VRF) ID from outgoing packets on a router by applying an output flow monitor having a flow record that collects the VRF ID as a key or a nonkey field.

- Information About Flexible Netflow Egress VRF Support , on page 1
- How to Configure Flexible Netflow Egress VRF Support , on page 1
- Configuration Examples for Flexible Netflow Egress VRF Support , on page 8
- Additional References, on page 8
- Feature Information for Flexible NetFlow—Egress VRF Support, on page 9

Information About Flexible Netflow Egress VRF Support

Flexible Netflow—Egress VRF Support Overview

The Flexible Netflow—Egress VRF Support feature enables collecting the virtual routing and forwarding (VRF) ID from outgoing packets on a router by applying an output flow monitor having a flow record that collects the VRF ID as a key or a nonkey field.

How to Configure Flexible Netflow Egress VRF Support

Creating a Flow Record

Perform this task to configure a customized flow record.

Customized flow records are used to analyze traffic data for a specific purpose. A customized flow record must have at least one **match** criterion for use as the key field and typically has at least one **collect** criterion for use as a nonkey field.

There are hundreds of possible permutations of customized flow records. This task shows the steps that are used to create one of the possible permutations. Modify the steps in this task as appropriate to create a customized flow record for your requirements.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **flow record** *record-name*
4. **description** *description*
5. **match** {**ip** | **ipv6**} {**destination** | **source**} **address**
6. Repeat Step 5 as required to configure additional key fields for the record.
7. **match flow cts** {**source** | **destination**} **group-tag**
8.
9. Repeat the above step as required to configure additional nonkey fields for the record.
10. **end**
11. **show flow record** *record-name*
12. **show running-config flow record** *record-name*

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	**enable** **Example:** `Device> enable`	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	**configure terminal** **Example:** `Device# configure terminal`	Enters global configuration mode.
Step 3	**flow record** *record-name* **Example:** `Device(config)# flow record FLOW-RECORD-1`	Creates a flow record and enters Flexible NetFlow flow record configuration mode. • This command also allows you to modify an existing flow record.
Step 4	**description** *description* **Example:** `Device(config-flow-record)# description Used for basic traffic analysis`	(Optional) Creates a description for the flow record.
Step 5	**match** {**ip**	**ipv6**} {**destination**	**source**} **address** **Example:** `Device(config-flow-record)# match ipv4 destination address`	**Note** This example configures the IPv4 destination address as a key field for the record. For information about the other key fields available for the **match ipv4** command, and the other **match** commands that are available to configure key fields.

	Command or Action	Purpose
Step 6	Repeat Step 5 as required to configure additional key fields for the record.	—

Step 7	**match flow cts** {**source** | **destination**} **group-tag**
	Example:
	`Device(config-flow-record)# match flow cts source group-tag`
	`Device(config-flow-record)# match flow cts destination group-tag`
		Note This example configures the CTS source group tag and destination group tag as a key field for the record. For information about the other key fields available for the **match ipv4**/**ipv6** command, and the other **match** commands that are available to configure key fields.
		Note
		• Ingress:
		• In an incoming packet, if a header is present, SGT will reflect the same value as the header. If no value is present, it will show zero.
		• The DGT value will not depend on the ingress port SGACL configuration.
		• Egress:
		• If either propagate SGT or CTS is disabled on the egress interface, then SGT will be zero.
		• In an outgoing packet, if SGACL configuration that corresponds to the (SGT, DGT) exists, DGT will be non-zero.
		• If SGACL is disabled on the egress port/VLAN or if global SGACL enforcement is disabled, then DGT will be zero

Step 8	**Example:**	Configures the input interface as a nonkey field for the record. **Note** This example configures the input interface as a nonkey field for the record.
Step 9	Repeat the above step as required to configure additional nonkey fields for the record.	—
Step 10	**end** **Example:** `Device(config-flow-record)# end`	Exits Flexible NetFlow flow record configuration mode and returns to privileged EXEC mode.
Step 11	**show flow record** *record-name* **Example:**	(Optional) Displays the current status of the specified flow record.

	Command or Action	Purpose
	`Device# show flow record FLOW_RECORD-1`	
Step 12	**show running-config flow record** *record-name* **Example:** `Device# show running-config flow record FLOW_RECORD-1`	(Optional) Displays the configuration of the specified flow record.

Creating a Customized Flow Monitor

Perform this required task to create a customized flow monitor.

Each flow monitor has a separate cache assigned to it. Each flow monitor requires a record to define the contents and layout of its cache entries.

Before you begin

If you want to use a customized record instead of using one of the Flexible NetFlow predefined records, you must create the customized record before you can perform this task.

If you want to add a flow exporter to the flow monitor for data export, you must create the exporter before you can complete this task.

Note You must use the **no ip flow monitor** command to remove a flow monitor from all of the interfaces to which you have applied it before you can modify the parameters for the **record** command on the flow monitor. For information about the **ip flow monitor** command, refer to the *Cisco IOS Flexible NetFlow Command Reference*.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **flow monitor** *monitor-name*
4. **description** *description*
5. **record** {*record-name* | **netflow-original** | **netflow** {**ipv4** | **ipv6**} *record* [**peer**]}
6. **cache** {**entries** *number* | **timeout** {**active** | **inactive** | **update**} *seconds* | **type** {**immediate** | **normal** | **permanent**}}
7. Repeat Step 6 as required to finish modifying the cache parameters for this flow monitor.
8. **statistics packet protocol**
9. **statistics packet size**
10. **exporter** *exporter-name*
11. **end**
12. **show flow monitor** [[**name**] *monitor-name* [**cache** [**format** {**csv** | **record** | **table**}]] [**statistics**]]
13. **show running-config flow monitor** *monitor-name*

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	**enable** **Example:** `Device> enable`	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	**configure terminal** **Example:** `Device# configure terminal`	Enters global configuration mode.
Step 3	**flow monitor** *monitor-name* **Example:** `Device(config)# flow monitor FLOW-MONITOR-1`	Creates a flow monitor and enters Flexible NetFlow flow monitor configuration mode. • This command also allows you to modify an existing flow monitor.
Step 4	**description** *description* **Example:** `Device(config-flow-monitor)# description Used for basic ipv4 traffic analysis`	(Optional) Creates a description for the flow monitor.
Step 5	**record** {*record-name* | **netflow-original** | **netflow** {**ipv4** | **ipv6**} *record* [**peer**]} **Example:** `Device(config-flow-monitor)# record FLOW-RECORD-1`	Specifies the record for the flow monitor.
Step 6	**cache** {**entries** *number* | **timeout** {**active** | **inactive** | **update**} *seconds* | **type** {**immediate** | **normal** | **permanent**}} **Example:** `Device(config-flow-monitor)# cache type normal`	(Optional) Modifies the flow monitor cache parameters such as timeout values, number of cache entries, and the cache type. • The values for the keywords associated with the **timeout** keyword have no effect when the cache type is set to **immediate**.
Step 7	Repeat Step 6 as required to finish modifying the cache parameters for this flow monitor.	—
Step 8	**statistics packet protocol** **Example:** `Device(config-flow-monitor)# statistics packet protocol`	(Optional) Enables the collection of protocol distribution statistics for Flexible NetFlow monitors.

	Command or Action	Purpose
Step 9	**statistics packet size** **Example:** `Device(config-flow-monitor)# statistics packet size`	(Optional) Enables the collection of size distribution statistics for Flexible NetFlow monitors.
Step 10	**exporter** *exporter-name* **Example:** `Device(config-flow-monitor)# exporter EXPORTER-1`	(Optional) Specifies the name of an exporter that was created previously.
Step 11	**end** **Example:** `Device(config-flow-monitor)# end`	Exits Flexible NetFlow flow monitor configuration mode and returns to privileged EXEC mode.
Step 12	**show flow monitor** [[**name**] *monitor-name* [**cache** [**format** {**csv** | **record** | **table**}]] [**statistics**]] **Example:** `Device# show flow monitor FLOW-MONITOR-2 cache`	(Optional) Displays the status and statistics for a Flexible NetFlow flow monitor.
Step 13	**show running-config flow monitor** *monitor-name* **Example:** `Device# show running-config flow monitor FLOW_MONITOR-1`	(Optional) Displays the configuration of the specified flow monitor.

Applying a Flow Monitor to an Interface

Before it can be activated, a flow monitor must be applied to at least one interface. Perform this required task to activate a flow monitor.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **interface** *type number*
4. {**ip** | **ipv6**} **flow monitor** *monitor-name* {**input** | **output**}
5. Repeat Steps 3 and 4 to activate a flow monitor on any other interfaces in the device over which you want to monitor traffic.
6. **end**
7. **show flow interface** *type number*
8. **show flow monitor name** *monitor-name* **cache format record**

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	**enable** **Example:** `Device> enable`	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	**configure terminal** **Example:** `Device# configure terminal`	Enters global configuration mode.
Step 3	**interface** *type number* **Example:** `Device(config)# interface GigabitEthernet 0/0/0`	Specifies an interface and enters interface configuration mode.
Step 4	{**ip** | **ipv6**} **flow monitor** *monitor-name* {**input** | **output**} **Example:** `Device(config-if)# ip flow monitor FLOW-MONITOR-1 input`	Activates a flow monitor that was created previously by assigning it to the interface to analyze traffic.
Step 5	Repeat Steps 3 and 4 to activate a flow monitor on any other interfaces in the device over which you want to monitor traffic.	—
Step 6	**end** **Example:** `Device(config-if)# end`	Exits interface configuration mode and returns to privileged EXEC mode.
Step 7	**show flow interface** *type number* **Example:** `Device# show flow interface GigabitEthernet 0/0/0`	Displays the status of Flexible NetFlow (enabled or disabled) on the specified interface.
Step 8	**show flow monitor name** *monitor-name* **cache format record** **Example:** `Device# show flow monitor name FLOW_MONITOR-1 cache format record`	Displays the status, statistics, and flow data in the cache for the specified flow monitor.

Configuration Examples for Flexible Netflow Egress VRF Support

Example Configuring Flexible NetFlow for Egress VRF Support

The following example configures the collection of the virtual routing and forwarding (VRF) ID from outgoing packets on a router by applying an output flow monitor having a flow record that collects the VRF ID as a key field.

This example starts in global configuration mode.

```
!
flow record rm_1
match routing vrf output
match ipv4 source address
match ipv4 destination address
collect interface input
collect interface output
collect counter packets
!
flow monitor mm_1
record rm_1
!
interface GigabitEthernet 0/0/0
ip vrf forwarding green
ip address 172.16.2.2 255.255.255.252
ip flow monitor mm_1 output
!
end
```

Additional References

Related Documents

Related Topic	Document Title
Cisco IOS commands	Cisco IOS Master Command List, All Releases
Flexible NetFlow conceptual information and configuration tasks	*Flexible NetFlow Configuration Guide*
Flexible NetFlow commands	*Cisco IOS Flexible NetFlow Command Reference*

Standards/RFCs

Standard	Title
No new or modified standards/RFCs are supported by this feature.	—

MIBs

MIB	MIBs Link
None	To locate and download MIBs for selected platforms, Cisco software releases, and feature sets, use Cisco MIB Locator found at the following URL: http://www.cisco.com/go/mibs

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Feature Information for Flexible NetFlow—Egress VRF Support

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for Flexible NetFlow—Egress VRF Support

Feature Name	Releases	Feature Information
Flexible NetFlow—Egress VRF Support	Cisco IOS XE Release 3.8S	Enables collecting the virtual routing and forwarding (VRF) ID from outgoing packets on a router by applying an output flow monitor having a flow record that collects the VRF ID as a key or a nonkey field. The following commands were introduced or modified: **collect routing**, **match routing**, **option (Flexible NetFlow**, **show flow monitor**.