

IPv6 IPsec Quality of Service

The IPv6 IPsec QoS feature allows the quality of service (QoS) policies to be applied to IPv6 IPsec.

- Information About IPv6 IPsec QoS, on page 1
- How to Configure IPv6 IPsec QoS, on page 1
- Configuration Examples for QoS, on page 6
- Additional References for IPv6 IPsec QoS, on page 8
- Feature Information for IPv6 IPsec QoS, on page 9

Information About IPv6 IPsec QoS

IPv6 IPsec QoS Overview

The IPv6 IPsec QoS feature applies the quality of service (QoS) policies to IPV6 IPsec. This feature supports the following functionalities:

- Crypto LLQ QoS—Traffic that is classified by QoS and marked as priority level 1 or 2 by traditional Cisco Modular QoS CLI (MQC) QoS configuration, for example PAK priority, is enqueued to the priority queue before the crypto processor. The low latency queuing (LLQ) for IPsec encryption engines helps reduce packet latency for priority traffic.
- IPsec QoS Pre-Classify—QoS pre-classify is configured under a crypto map to enable IPsec to save the original Layer 3 and Layer 4 header before the encryption so that QoS can do the classification using the saved header.
- QoS group-based LLQ—The QoS group-based LLQ feature allows IPsec to check the LLQ QoS group setting to determine whether a packet is a high priority packet before it is enqueued to low latency queuing (LLQ).

How to Configure IPv6 IPsec QoS

Configuring Crypto LLQ QoS

When IPsec and QoS are configured on a physical interface and if the QoS policy has priority class, IPSec will classify the packet based on the policy attached to the interface. It will enqueue the packet matching

priority class into Low Latency Queue. The high-priority packet will be enqueued to low latency queueing (LLQ).

Perform this task to attach a service policy to the output interface and enable LLQ for IPsec encryption engines.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **interface** *physical-interface-name*
4. **ipv6 address** *{ipv6-address /prefix-length | prefix-name sub-bits/prefix-length}*
5. **service-policy output** *policy-map*
6. **ipv6 crypto map** *map-name*
7. **end**

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	**enable** **Example:** `Device> enable`	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	**configure terminal** **Example:** `Device# configure terminal`	Enters global configuration mode.
Step 3	**interface** *physical-interface-name* **Example:** `Device(config)# interface GigabitEthernet0/0/1`	Specifies the interface using the LLQ for IPsec encryption engines.
Step 4	**ipv6 address** *{ipv6-address /prefix-length | prefix-name sub-bits/prefix-length}* **Example:** `Device(config-if)# ipv6 address 2001:DB8:FFFF::2/64`	Configures an IPv6 address on an interface.
Step 5	**service-policy output** *policy-map* **Example:** `Device(config-if)# service-policy output p1`	Attaches the specified service policy map to the output interface and enables LLQ for IPsec encryption engines.
Step 6	**ipv6 crypto map** *map-name* **Example:**	Enables an IPv6 crypto map on an interface.

	Command or Action	Purpose
	`Device(config-if)# ipv6 crypto map CMAP_1`	
Step 7	**end** **Example:** `Device(config-if)# end`	Exits interface configuration mode and returns to privileged EXEC mode.

Configuring QoS Pre-classify

Configuring Pre-classify on the Crypto Map

The **qos pre-classify** command is applied on the crypto map, allowing configuration on a per-tunnel basis. QoS policy is applied to Packets based on the L3 and L4 Header before encryption.

Perform this task to apply the QoS pre-classify on the crypto map.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ipv6 crypto map** *map-name*
4. **qos pre-classify**
5. **end**

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	**enable** **Example:** `Device> enable`	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	**configure terminal** **Example:** `Device# configure terminal`	Enters global configuration mode.
Step 3	**ipv6 crypto map** *map-name* **Example:** `Device(config-if)# ipv6 crypto map CM_V6`	Enters crypto map configuration mode and specifies the crypto map to be configured.

	Command or Action	Purpose
Step 4	**qos pre-classify** **Example:** `Device(config-if)# qos pre-classify`	Enables QoS pre-classify on the crypto map.
Step 5	**end** **Example:** `Device(config-if)# end`	Exits interface configuration mode and returns to privileged EXEC mode.

Configuring Pre-classify on the Tunnel Interface

The **qos pre-classify** command is applied on the IPv6 IPsec tunnel interface, making QoS a configuration option on a per-tunnel basis.

Perform this task to apply the QOS pre-classify on the tunnel interface.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **interface** *tunnel-interface-name*
4. **ipv6 address** *{ipv6-address /prefix-length | prefix-name sub-bits/prefix-length}*
5. **qos pre-classify**
6. **end**

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	**enable** **Example:** `Device> enable`	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	**configure terminal** **Example:** `Device# configure terminal`	Enters global configuration mode.
Step 3	**interface** *tunnel-interface-name* **Example:** `Device(config)# interface Tunnel1`	Enters interface configuration mode and specifies the tunnel or virtual interface to configure.

	Command or Action	Purpose
Step 4	**ipv6 address** *{ipv6-address /prefix-length | prefix-name sub-bits/prefix-length}* **Example:** `Device(config-if)# ipv6 address 2001:DB8:FFFF::2/64`	Configures an IPv6 address on an interface.
Step 5	**qos pre-classify** **Example:** `Device(config-if)# qos pre-classify`	Enables QoS pre-classify on the tunnel interface.
Step 6	**end** **Example:** `Device(config-if)# end`	Exits interface configuration mode and returns to privileged EXEC mode.

Configuring LLQ QoS Group

The **platform ipsec llq qos-group** command enables low latency queuing for traffic that matches the QoS groups configured with this command.

Perform this task to enable LLQ for QoS groups.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **platform ipsec llq qos-group** *group-number*
4. **end**

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	**enable** **Example:** `Device> enable`	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	**configure terminal** **Example:** `Device# configure terminal`	Enters global configuration mode.

	Command or Action	Purpose
Step 3	**platform ipsec llq qos-group** *group-number* **Example:** `Device(config)# platform ipsec llq qos-group 1`	Specifies the QoS group to enable LLQ. Valid values are from 1 to 99.
Step 4	**end** **Example:** `Device(config-if)# end`	Exits interface configuration mode and returns to privileged EXEC mode.

Configuration Examples for QoS

Example: Configuring Crypto LLQ QoS

The following example shows how to specify the service policy map to the output interface and enable an IPv6 crypto map on an interface.

```
!
class-map match-all c2
  match precedence 5  6  7
class-map match-all c1
  match precedence 0  1  2  3

policy-map p1
  class c1
    priority percent 10
  class c2
    bandwidth remaining percent 3

crypto map ipv6 CMAP_1 1 ipsec-isakmp
  set peer address 2001:DB8:FFFF::1
  set transform-set ESP-3DES-SHA
  match address 102

interface GigabitEthernet0/0/1
  ipv6 address 2001:DB8:FFFF::2/64
  ipv6 crypto map CMAP_1
  service-policy output p1
```

Example: Configuring Pre-classify on the Crypto Map

The following example shows how to enable QoS pre-classification using the **qos pre-classify** command on the crypto map CM_V6.

```
!
crypto map ipv6 CM_V6 10 ipsec-isakmp
  match address ACL_IPV6_1
  set transform-set set1
```

```
  set peer 2001:DB8:FFFF::1
  qos pre-classify
!
interface GigabitEthernet0/0/1
  ipv6 address 2001:DB8:FFFF::2/64
  service-policy output policy1
  ipv6 crypto map CM_V6
```

Example: Configuring Pre-classify on the Tunnel Interface

The following example shows how to enable QoS pre-classification using the **qos pre-classify** command on the tunnel interface tunnel1.

```
interface GigabitEthernet1/1/2
  ipv6 address 2001:DB8:1::F/64
  service-policy output policy1
!
interface Tunnel1
  ipv6 address 2001:DB8:2::F/64
  qos pre-classify
  ipv6 mtu 1400
  tunnel protection ipsec profile greprof
```

Example: Configuring LLQ QoS Group

The following example shows how to configure low latency queuing on a QoS group.

```
!
platform ipsec llq qos-group 1
platform ipsec llq qos-group 49
!
!
crypto map ipv6 cmap 1 ipsec-isakmp
  set peer 2001:DB8:FFFF:1::E/64
  set security-association lifetime seconds 600
  set transform-set aes-192
  match address 102
!
!
class-map match-all c1
  match precedence 5
class-map match-all c2
  match precedence 2
class-map match-all c3
  match precedence 4
class-map match-all c4
  match precedence 3
!
policy-map p1
  class c3
    set qos-group 20
  class c1
    set qos-group 49
  class c4
    set qos-group 77
!
```

```
policy-map p2
  class class-default
    set qos-group 1
!
interface GigabitEthernet0/2/0
  ipv6 address
  negotiation auto
  cdp enable
  ipv6 crypto map cmap
  service-policy input p2
!
!
interface GigabitEthernet0/2/7
  ipv6 address 2001:DB8:FFFF:1::F/64
  negotiation auto
  cdp enable
  service-policy input p1
!
```

Additional References for IPv6 IPsec QoS

Related Documents

Related Topic	Document Title
Security commands	• *Cisco IOS Security Command Reference Commands A to C* • *Cisco IOS Security Command Reference Commands D to L* • *Cisco IOS Security Command Reference Commands M to R* • *Cisco IOS Security Command Reference Commands S to Z*
IPv6 Commands	*IPv6 Command Reference*
QoS Commands	*Cisco IOS Quality of Service Solutions Command Reference*
IPv6 Addressing and Connectivity	*IPv6 Configuration Guide*

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Feature Information for IPv6 IPsec QoS

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for IPv6 IPsec QoS

Feature Name	Releases	Feature Information
IPv6 IPsec QoS	15.4(1)S	The IPv6 IPsec QoS feature allows the QoS policies to be applied to IPv6 IPsec. This feature supports the following functionalities: • Crypto LLQ QoS • IPsec QoS Pre-Classify • QoS group-based LLQ The following command was modified: **ipv6 crypto map**