

Cellular Interfaces

- Feature history for cellular interfaces, on page 1
- Cellular interfaces, on page 2
- Supported devices, on page 3
- Guidelines, on page 4
- Configure cellular interface, on page 4
- Reset the profile configuration of a cellular modem, on page 23
- Troubleshoot LTE modem crash, on page 24

Feature history for cellular interfaces

Table 1: Feature History

Feature Name	Release Information	Description
Configure Cellular Interfaces	Cisco Catalyst SD-WAN Manager Release 18.1.1	You can configure cellular interfaces on devies with cellular modules to enable LTE connectivity.
Ability to Configure APNs under Running Configurations for Single and Dual SIMs	Cisco IOS XE Catalyst SD-WAN Release 17.8.1a Cisco vManage Release 20.8.1	This feature allows you to create a data profile for a cellular device.
Cellular Module Support for Cisco Catalyst Rugged Series Routers	Cisco IOS XE Catalyst SD-WAN Release 17.15.4 Cisco Catalyst SD-WAN Manager 20.15.4	Support for cellular modules on Cisco Cisco Catalyst IR1101, IR1800 and IR18340 Rugged Series Routers.

Feature Name	Release Information	Description
Reset the Profile Configuration of Cellular Modem	Cisco IOS XE Catalyst SD-WAN Release 17.18.1a Cisco Catalyst SD-WAN Manager Release 20.18.1	This sub-feature of the Cellular Controller feature enables you to reset the configuration of a cellular modem operating on a device using CLI.
Band Select Support in Controller Mode	Cisco Catalyst SD-WAN Manager Release 20.18.1	This sub-feature of the Cellular Controller feature introduces the Cellular Band Select feature-parcel, enabling you to specify which cellular bands to use.

Cellular interfaces

A cellular interface is a network interface that enables wireless communication over a cellular network.

- Provides wireless connectivity when all wired WAN tunnel interfaces on the device are unavailable.
- Functions as the primary WAN link for a branch office, depending on usage patterns and supported data rates.

Cellular module and data profile components

The following components are essential for cellular interface operation:

- Cellular module: Installed in a router to enable LTE connectivity, provides wireless connectivity over a service provider's cellular network, and supports network access for use cases such as branch office connectivity.
- Data profile: Defines parameters for how the device connects to a cellular network and uses the parameters for communication with the service provider.

Supported devices

Table 2: Supported Platforms and Modules

Platform	Minimum Supported Release	Supported Modules
IR1101 Rugged Series Router	Cisco IOS XE Catalyst SD-WAN Release 17.15.1a Cisco Catalyst SD-WAN Manager Release 20.15.1	P-LTE-MNA, P-LTE-VZ, P-LTE-US, P-LTE-GB, P-LTE-IN, P-LTE-JN, P-LTEA-EA, P-LTEA-LA, P-LTEAP18-GL, P-5GS6-GL
	Cisco IOS XE Catalyst SD-WAN Release 17.15.4 Cisco Catalyst SD-WAN Manager 20.15.4	P-LTEA7-JP, P-LTEA7-NA, P-LTEA7-EAL, P-5GS6-R16SA-GL
	Cisco IOS XE Catalyst SD-WAN Release 17.18.1a Cisco Catalyst SD-WAN Manager Release 20.18.x	P-LTE-450
IR8100 Rugged Series Router	Cisco IOS XE Catalyst SD-WAN Release 17.15.1a Cisco Catalyst SD-WAN Manager Release 20.15.1	IRMH-LTE-MNA, IRMH-LTEA-EA, IRMH-LTEA-LA, IRMH-LTEAP18-GL, IRMH-5GS6-GL
	Cisco IOS XE Catalyst SD-WAN Release 17.16.1a Cisco Catalyst SD-WAN Manager Release 20.16.1	IRMH-LTE7-NA-900, IRMH-5GR16SA, IRMH-LTE7-EAL
IR1800 Rugged Series Router	Cisco IOS XE Catalyst SD-WAN Release 17.15.1a Cisco Catalyst SD-WAN Manager Release 20.15.1	P-LTE-MNA, P-LTE-VZ, P-LTE-US, P-LTE-GB, P-LTE-IN, P-LTE-JN, P-LTEA-EA, P-LTEA-LA, P-LTEAP18-GL, P-5GS6-GL
	Cisco IOS XE Catalyst SD-WAN Release 17.15.4 Cisco Catalyst SD-WAN Manager 20.15.4	P-LTEA7-NA, P-LTEA7-JP, P-LTEA7-EAL, P-5GS6-R16SA-GL
	Cisco IOS XE Catalyst SD-WAN Release 17.18.1a Cisco Catalyst SD-WAN Manager Release 20.18.x	P-LTE-450
IR8340 Rugged Series Router	Cisco IOS XE Catalyst SD-WAN Release 17.15.1a Cisco Catalyst SD-WAN Manager Release 20.15.1	P-LTE-MNA, P-LTEA-EA, P-LTEA-LA, P-LTEAP18-GL P-5GS6-GL
	Cisco IOS XE Catalyst SD-WAN Release 17.15.4 Cisco Catalyst SD-WAN Manager 20.15.4	P-LTEA7-NA, P-LTEA7-JP, P-LTEA7-EAL, P-5GS6-R16SA-GL
Cisco ESR 6300 Series	Cisco IOS XE Catalyst SD-WAN Release 17.15.1a Cisco Catalyst SD-WAN Manager Release 20.15.1	P-LTE-MNA, P-LTEA-EA, P-LTEA-LA, P-LTEAP18-GL

Guidelines

Circuit of last resort

Configure an interface as a circuit of last resort to ensure it remains dormant and is skipped during control connection calculations while primary interfaces are active. Use the **last-resort-circuit** command to enable this functionality on cellular or GigabitEthernet interfaces.

- Ensure that when primary interfaces establish BFD connections, the circuit of last resort shuts down to prevent unnecessary traffic.
- Recognize that the circuit of last resort activates only when all primary interfaces lose their connections, which triggers BFD TLOC Down and Control TLOC Down alarms.

Active circuit

Optimize bandwidth usage when using a cellular interface as an active circuit by adjusting control packet timers and prioritizing non-cellular interfaces for control traffic.

- Increase control packet timers using **omp timers advertisement-interval** and **bfd color hello-interval** to reduce the frequency of OMP update packets and BFD hello packets.
- Configure the **vmanage-connection-preference** command on tunnel interfaces to prioritize non-cellular paths for Cisco SD-WAN Manager control traffic, ensuring at least one interface maintains a non-zero preference value.

Configure cellular interface

A cellular interface is a network interface that enables wireless communication over a cellular network.

Use one of the methods to configure cellular interface.

- Configure cellular interfaces using a configuration group
- Configure cellular interfaces using the CLI
- Configure cellular interfaces using feature templates

Configure cellular interfaces using a configuration group

Minimum supported releases: Cisco IOS XE Catalyst SD-WAN Release 17.16.1a, Cisco Catalyst SD-WAN Manager Release 20.16.1

Before you begin

On the **Configuration** > **Configuration Groups** page, choose **SD-WAN** as the solution type.

Procedure

Step 1 From the Cisco SD-WAN Manager menu, choose **Configuration** > **Configuration Groups** .

Step 2 Create and configure a Transport VPN feature in a Transport & Management profile.

a. Configure the basic configuration parameters, such as the VPN.

Table 3: Basic Configuration

Field	Description
VPN	Enter the numeric identifier of the VPN.
Enhance ECMP Keying	Enable the use in the ECMP hash key of Layer 4 source and destination ports, in addition to the combination of the source IP address, destination IP address, protocol, and DSCP field, as the ECMP hash key. Default: Disabled

b. Configure DNS.

Table 4: DNS

Field	Description
Add DNS	
Primary DNS Address (IPv4)	Enter the IP address of the primary IPv4 DNS server in this VPN.
Secondary DNS Address (IPv4)	Enter the IP address of a secondary IPv4 DNS server in this VPN.
Add DNS IPv6	
Primary DNS Address (IPv6)	Enter the IP address of the primary IPv6 DNS server in this VPN.
Secondary DNS Address (IPv6)	Enter the IP address of a secondary IPv6 DNS server in this VPN.

c. Configure host mapping.

Table 5: Host Mapping

Field	Description
Add New Host Mapping	
Hostname*	Enter the hostname of the DNS server. The name can be up to 128 characters.
List of IP*	Enter up to 14 IP addresses to associate with the hostname. Separate the entries with commas.

d. Configure routes.

Table 6: Route

Field	Description
Add IPv4 Static Route	
Network address*	Enter the IPv4 address or prefix, in decimal four-point-dotted notation, and the prefix length of the IPv4 static route to configure in the VPN.
Subnet Mask*	Enter the subnet mask.
Gateway*	Choose one of the following options to configure the next hop to reach the static route: • **nextHop**: When you choose this option and click **Add Next Hop**, the following fields appear: • **Address***: Enter the next-hop IPv4 address. • **Administrative distance***: Enter the administrative distance for the route. • **dhcp** • **null0**: When you choose this option, the following field appears: • **Administrative distance**: Enter the administrative distance for the route.
Add IPv6 Static Route	
Prefix*	Enter the IPv6 address or prefix, in decimal four-point-dotted notation, and the prefix length of the IPv6 static route to configure in the VPN.
Next Hop/Null 0/NAT	Choose one of the following options to configure the next hop to reach the static route: • **Next Hop**: When you choose this option and click **Add Next Hop**, the following fields appear: • **Address***: Enter the next-hop IPv6 address. **Administrative distance***: Enter the administrative distance for the route. • **Null 0**: When you choose this option, the following field appears: • **IPv6 Route Null 0***: Enable this option to set the next hop to be the null interface. All packets sent to this interface are dropped without sending any ICMP messages. • **NAT**: When you choose this option, the following field appears: • **IPv6 NAT***: Choose NAT64 or NAT66.
Add BGP Routing	Choose a BGP route.

e. Configure services.

Table 7: Service

Field	Description
Add Service	
Service Type	Choose the service available in the VPN. Value: **TE**

Step 3 Configure a Cellular Interface feature to associate with the Transport VPN.

a. Adjacent to the Transport VPN feature, click + and add a Cellular Interface feature as a subfeature.

b. Configure the basic parameters.

Field	Description
Shutdown*	Enable or disable the interface.
Interface Name*	Enter the name of the interface.
Description*	Enter a description of the cellular interface.
DHCP Helper	Enter up to four IP addresses for DHCP servers in the network, separated by commas, to have the interface be a DHCP helper. A DHCP helper interface forwards BOOTP (Broadcast) DHCP requests that it receives from the specified DHCP servers.

c. Configure the tunnel parameters.

Field	Description
Tunnel Interface	Enable this option to create a tunnel interface.
Carrier	Choose the carrier name or private network identifier to associate with the tunnel. Values: carrier1, carrier2, carrier3, carrier4, carrier5, carrier6, carrier7, carrier8, default Default: default
Color	Choose a color for the TLOC.
Color Description	Minimum supported release: Cisco Catalyst SD-WAN Manager Release 20.18.1 Enter a description associated to the TLOC color.
Hello Interval	Enter the interval between Hello packets sent on a DTLS or TLS WAN transport connection. Range: 100 through 600000 milliseconds Default: 1000 milliseconds (1 second)

Field	Description
Hello Tolerance	Enter the time to wait for a Hello packet on a DTLS or TLS WAN transport connection before declaring that transport tunnel to be down. Range: 12 through 6000 seconds Default: 12 seconds
Last-Resort Circuit	Enable this option to use the tunnel interface as the circuit of last resort.
Restrict	Enable this option to limit the remote TLOCs that the local TLOC can establish BFD sessions with. When a TLOC is marked as restricted, a TLOC on the local router establishes tunnel connections with a remote TLOC only if the remote TLOC has the same color.
Group	Enter a group number. Range: 1 through 4294967295
Border	Enable this option to set the TLOC as a border TLOC.
Maximum Control Connections	Specify the maximum number of Cisco SD-WAN Controllers that the WAN tunnel interface can connect to. To have the tunnel establish no control connections, set the number to 0. Range: 0 through 100 Default: 2
NAT Refresh Interval	Enter the interval between NAT refresh packets sent on a DTLS or TLS WAN transport connection. Range: 1 through 60 seconds Default: 5 seconds
Validator As Stun Server	Enable Session Traversal Utilities for NAT (STUN) to allow the tunnel interface to discover its public IP address and port number when the Cisco IOS XE Catalyst SD-WAN device is located behind a NAT.
Exclude Controller Group List	Set the identifiers of one or more Cisco SD-WAN Controller groups that this tunnel is not allowed to connect to. Range: 1 through 100
Manager Connection Preference	Set the preference for using a tunnel interface to exchange control traffic with Cisco SD-WAN Manager. Range: 0 through 8 Default: 5

Field	Description
Full Port Hop	Minimum release: Cisco IOS XE Catalyst SD-WAN Release 17.18.1a Enable full port hopping at the TLOC level to allow devices to establish connections with controllers by switching to the next port if the current port is blocked or non-functional. Default: Disabled
Port Hop	Enable port hopping. When a router is behind a NAT, port hopping rotates through a pool of preselected OMP port numbers (called base ports) to establish DTLS connections with other routers when a connection attempt is unsuccessful. The default base ports are 12346, 12366, 12386, 12406, and 12426. To modify the base ports, set a port offset value. Default: Enabled Starting from Cisco IOS XE Catalyst SD-WAN Release 17.18.1a, this field is deprecated. Instead use the **Full Port Hop** option. See the **Full Port Hop** field.
Low-Bandwidth Link	Enable the low-bandwidth feature.
Tunnel TCP MSS	Specify the maximum segment size (MSS) of TPC SYN packets passing through the router. By default, the MSS is dynamically adjusted based on the interface or tunnel MTU such that TCP SYN packets are never fragmented. Range: 500 to 1460 bytes Default: None
Clear-Dont-Fragment	Enable this option to clear the Don't Fragment (DF) bit in the IPv4 packet header for packets being transmitted out the interface. When the DF bit is cleared, packets larger than the MTU of the interface are fragmented before being sent.
Network Broadcast	Enable this option to accept and respond to network-prefix-directed broadcasts.

Field	Description
Allow Service	Allow or disallow the following services on the interface: • **All** • **BGP** • **DHCP** • **NTP** • **SSH** • **DNS** • **ICMP** • **HTTPS** • **OSPF** • **STUN** • **SNMP** • **NETCONF** • **BFD**
Encapsulation	
GRE	Use GRE encapsulation on the tunnel interface. By default, GRE is disabled. If you select both IPsec and GRE encapsulations, two TLOCs are created for the tunnel interface that have the same IP addresses and colors, but that differ by their encapsulation.
GRE Preference	Specify a preference value for directing traffic to the tunnel. A higher value is preferred over a lower value. Range: 0 through 4294967295 Default: 0
GRE Weight	Enter a weight to use to balance traffic across multiple TLOCs. A higher value sends more traffic to the tunnel. Range: 1 through 255 Default: 1
IPsec	Use IPsec encapsulation on the tunnel interface. By default, IPsec is enabled. If you select both IPsec and GRE encapsulations, two TLOCs are created for the tunnel interface that have the same IP addresses and colors, but that differ by their encapsulation.

Field	Description
IPsec Preference	Specify a preference value for directing traffic to the tunnel. A higher value is preferred over a lower value. Range: 0 through 4294967295 Default: 0
IPsec Weight	Enter a weight to use to balance traffic across multiple TLOCs. A higher value sends more traffic to the tunnel. Range: 1 through 255 Default: 1

d. Configure NAT.

Field	Description
NAT	Enable this option to have the interface act as a NAT device.
UDP Timeout*	Specify when NAT translations over UDP sessions time out. Range: 1 through 8947 minutes Default: 1 minutes
TCP Timeout*	Specify when NAT translations over TCP sessions time out. Range: 1 through 8947 minutes Default: 60 minutes (1 hour)

e. Configure ACL/QoS.

f. Configure the advanced parameters.

Field	Description
MAC Address	Specify a MAC address to associate with the interface, in colon-separated hexadecimal notation.
IP MTU	Specify the maximum MTU size of packets on the interface. Range: 576 through 9216 Default: 1500 bytes
Interface MTU	Enter the maximum transmission unit size for frames received and transmitted on the interface. Range: 1500 through 9216 Default: 1500 bytes

Field	Description
TCP MSS	Specify the maximum segment size (MSS) of TPC SYN packets passing through the router. By default, the MSS is dynamically adjusted based on the interface or tunnel MTU such that TCP SYN packets are never fragmented. Range: 500 to 1460 bytes Default: None
TLOC Extension	Enter the name of a physical interface on the same router that connects to the WAN transport. This configuration then binds this service-side interface to the WAN transport. A second router at the same site that itself has no direct connection to the WAN (generally because the site has only a single WAN connection) and that connects to this service-side interface is then provided with a connection to the WAN. **Note** TLOC extension over L3 is supported only for Cisco IOS XE Catalyst SD-WAN devices. If configuring TLOC extension over L3 for a Cisco IOS XE Catalyst SD-WAN device, enter the IP address of the L3 interface.
Tracker	Tracking the interface status is useful when you enable NAT on a transport interface in VPN 0 to allow data traffic from the router to exit directly to the internet rather than having to first go to a router in a data center. In this situation, enabling NAT on the transport interface splits the TLOC between the local router and the data center into two, with one going to the remote router and the other going to the internet. When you enable transport tunnel tracking, Cisco Catalyst SD-WAN periodically probes the path to the internet to determine whether it is up. If Cisco Catalyst SD-WAN detects that this path is down, it withdraws the route to the internet destination, and traffic destined to the internet is then routed through the data center router. When Cisco Catalyst SD-WAN detects that the path to the internet is again functioning, the route to the internet is reinstalled. Enter the name of a tracker to track the status of transport interfaces that connect to the internet.
IP Directed-Broadcast	An IP directed broadcast is an IP packet whose destination address is a valid broadcast address for some IP subnet but which originates from a node that is not itself part of that destination subnet. A device that is not directly connected to its destination subnet forwards an IP directed broadcast in the same way it would forward unicast IP packets destined to a host on that subnet. When a directed broadcast packet reaches a device that is directly connected to its destination subnet, that packet is broadcast on the destination subnet. The destination address in the IP header of the packet is rewritten to the configured IP broadcast address for the subnet, and the packet is sent as a link-layer broadcast. If directed broadcast is enabled for an interface, incoming IP packets whose addresses identify them as directed broadcasts intended for the subnet to which that interface is attached are broadcast on that subnet.

Step 4 Click **Add New Feature** to create and configure a Cellular Controller feature.

Configure the basic parameters, mostly related to SIMs.

Table 8: Basic Settings

Field	Description
Type	Choose a feature from the drop-down list.
Feature Name	Enter a name for the feature. The name can be up to 128 characters and can contain only alphanumeric characters.
Description	Enter a description of the feature. The description can be up to 2048 characters and can contain only alphanumeric characters.
Cellular ID	Enter the interface slot and port number in which the cellular NIM card is installed. Currently, it can be 0/1/0 or 0/2/0.
Primary SIM slot	Enter the number of the primary SIM slot. It can be 0 or 1. The other slot is automatically set to be the secondary. If there is a single SIM slot, this parameter is not applicable.
SIM Failover Retries	Specify the maximum number of times to retry connecting to the secondary SIM when service on the primary SIM becomes unavailable. If there is a single SIM slot, this parameter is not applicable. Range: 0 through 65535 Default: 10
SIM Failover Timeout	Specify how long to wait before switching from the primary SIM to the secondary SIM if service on the primary SIM becomes unavailable. If there is a single SIM slot, this parameter is not applicable. Range: 3 to 7 minutes Default: 3 minutes
Firmware Auto Sim	By default, this option is enabled. AutoSIM analyzes any active SIM card and determines which service provider network is associated with that SIM. Based on that analysis, AutoSIM automatically loads the appropriate firmware.

Step 5 Configure a Cellular Profile feature to associate with the Cellular Controller.

a. Adjacent to the Cellular Controller feature, click **+** and add a Cellular Profile feature as a subfeature.

b. Configure the basic parameters.

Table 9: Basic Settings

Field	Description
Type	Choose a feature from the drop-down list.
Feature Name	Enter a name for the feature. The name can be up to 128 characters and can contain only alphanumeric characters.

Field	Description
Description	Enter a description of the feature. The description can be up to 2048 characters and can contain only alphanumeric characters.
Profile ID	Enter the identification number of the profile to use on the router. Range: 1 through 15
Access Point Name	Enter the name of the gateway between the service provider network and the public internet. It can be up to 32 characters long.
Authentication	Choose the authentication method used for the connection to the cellular network. It can be **none**, **pap**, **chap**, or **pap_chap**.
Profile Username	Enter the username to use when making cellular connections for web services. It can be 1 to 32 characters. It can contain any alphanumeric characters, including spaces.
Profile Password	Enter the user password to use when making cellular connections for web services. The password is case-sensitive and can be clear text, or an AES-encrypted key. From Cisco Catalyst SD-WAN Manager Release 20.15.1, when you enter the password as clear text, Cisco SD-WAN Manager encrypts the password. When you view the configuration preview, the password appears in its encrypted form.
Packet Data Network Type	Choose the packet data network (PDN) type of the cellular network. It can be IPv4, IPv6, or IPv4v6.
No Overwrite	Enable this option to overwrite the profile on the cellular modem. By default, this option is disabled.
Slot	Enter the associated SIM slot for the profile.

Step 6 If you need to configure specific cellular bands, do this:

a) In the **Cellular Controller** area, click + and choose **Cellular Band Select**.
b) Enable **Cellular Band Select**.
c) Configure the basic parameters.

Table 10: Cellular Band Select

Field	Description
Name	Specify the name of cellular band select.
Description (Optional)	Provide a description for the cellular band select.
Enable Cellular Band Select (Optional)	Enable/Disable cellular band.
All UMTS 3G only	Enable all UMTS3g bands in the cellular modem.
All LTE only	Enable all LTE bands in the cellular modem.

Field	Description
LTE 4G	Specify the LTE indices.
Indices	Enable/Disable cellular band indices.
UMTS 3G	Specify the 3G indices.
NR 5G	Specify the 5G SA indices.
NR 5G NSA	Specify the 5G NSA indices

Note
This sub-feature is applicable to both SD-Routing and SD-WAN modes.

What to do next

Also see Deploy a configuration group.

Configure cellular interfaces using CLI

The following example enables a cellular interface:

Procedure

Use the `interface Cellular` command to enable a cellular interface.

Example:

```
interface Cellular0/2/0
   description Cellular interface
   no shutdown
   ip address negotiated
   ip mtu 1428
   mtu 1500
  exit

  controller Cellular 0/2/0
   lte sim max-retry 1
   lte failovertimer 7
   profile id 1 apn Broadband authentication none pdn-type ipv4
```

Configure cellular interfaces using templates

To configure cellular interfaces using Cisco SD-WAN Manager templates:

1. Create a VPN Interface Cellular feature template to configure cellular module parameters
2. Create a Cellular Profile template to configure the profiles used by the cellular modem.

3. Create a VPN feature template to configure VPN parameters.

If your deployment includes devices with cellular interface, you must include cellular controller templates in Cisco SD-WAN Manager, even if these templates are not used.

If the device has the LTE or cellular controller module configured and the cellular controller feature template does not exist, then the device tries to remove the cellular controller template. For releases earlier than Cisco IOS XE Release 17.4.2, the following error message is displayed.

```
bad-cli - No controller Cellular 0/2/0, parser-context - No controller Cellular 0/2/0,
parser-response % Cannot remove controllers this way
```

For devices running on Cisco IOS XE Release 17.4.2 and later, the device will return an access-denied error message.

Procedure

Step 1 From the Cisco SD-WAN Manager menu, choose **Configuration** > **Templates**.

Step 2 Click **Feature Templates**.

In Cisco vManage Release 20.7.x and earlier releases, **Feature Templates** is titled **Feature**.

Step 3 Click **Add Template**.

Step 4 Select the type of device for which you are creating the template.

Step 5 Click **VPN Interface Cellular**.

Step 6 In **Template Name**, enter a name for the template. The name can be up to 128 characters and can contain only alphanumeric characters.

Step 7 In **Template Description**, enter a description of the template. The description can be up to 2048 characters and can contain only alphanumeric characters.

When you first open a feature template, for each parameter that has a default value, the scope is set to Default (indicated by a check mark), and the default setting or value is shown. To change the default or to enter a value, click the scope drop-down list.

Step 8 Configure cellular interface.

a) Configure basic cellular interface functionality.

Table 11:

Parameter Name	Description
Shutdown*	Click **No** to enable the interface.
Interface Name*	Enter the name of the interface. It must be **cellular0**.
Description	Enter a description of the cellular interface.
DHCP Helper	Enter up to four IP addresses for DHCP servers in the network, separated by commas, to have the interface be a DHCP helper. A DHCP helper interface forwards BOOTP (Broadcast) DHCP requests that it receives from the specified DHCP servers.
Bandwidth Upstream	For transmitted traffic, set the bandwidth above which to generate notifications. Range: 1 through $(2^{32} / 2) – 1$ kbps

Parameter Name	Description
Bandwidth Downstream	For received traffic, set the bandwidth above which to generate notifications. Range: 1 through (2^{32} / 2) – 1 kbps
IP MTU*	Enter 1428 to set the MTU size, in bytes. This value must be 1428. You cannot use a different value.

b) Configure a tunnel interface on the cellular interface to configure an interface in VPN 0 to be a WAN transport connection. The tunnel, which provides security from attacks, is used to send the phone number. At a minimum, select **On** and select a color for the interface. You can generally accept the system defaults for the reminder of the tunnel interface settings.

Parameter Name	Description
Tunnel Interface*	From the drop-down, select **Global**. Click **On** to create a tunnel interface.
Per-tunnel QoS	From the drop-down, select **Global**. Click **On** to create per-tunnel QoS. You can apply a Quality of Service (QoS) policy on individual tunnels, and is only supported for hub-to-spoke network topologies.
Per-tunnel QoS Aggregrator	From the drop-down, select **Global**. Click **On** to create per-tunnel QoS. **Note** 'bandwidth downstream' is required for per-Tunnel QoS feature to take effect as spoke role.
Color*	From the drop-down, select **Global**. Select a color for the TLOC. The color typically used for cellular interface tunnels is **lte**.
Color Description	Minimum supported release: SD-WAN Manager 20.18.1 Enter a description associated to the TLOC color.
Groups	From the drop-down, select **Global**. Enter the list of groups in the field.
Border	From the drop-down, select **Global**. Click **On** to set TLOC as border TLOC.
Maximum Control Connections	Set the maximum number of Cisco SD-WAN Controller that the WAN tunnel interface can connect to. To have the tunnel establish no control connections, set the number to 0. Range: 0 through 8 Default: 2
vBond As STUN Server	Click **On** to enable Session Traversal Utilities for NAT (STUN) to allow the tunnel interface to discover its public IP address and port number when the router is located behind a NAT.
Exclude Control Group List	Set the identifiers of one or more Cisco SD-WAN Controller groups that this tunnel is not allows to establish control connections with. Range: 0 through 100

Parameter Name	Description
vManage Connection Preference	Set the preference for using the tunnel to exchange control traffic with the Cisco SD-WAN Manager. Range: 0 through 9 Default: 5 If the edge device has two or more cellular interfaces, you can minimize the amount of traffic between the Cisco SD-WAN Manager and the cellular interfaces by setting one of the interfaces to be the preferred one to use when sending updates to the Cisco SD-WAN Manager and receiving configurations from the Cisco SD-WAN Manager. To have a tunnel interface never connect to the Cisco SD-WAN Manager, set the number to 0. At least one tunnel interface on the edge device must have a nonzero Cisco SD-WAN Manager connection preference.
Full Port Hop	Minimum release: SD-WAN Manager 20.18.1 Enable full port hopping at the TLOC level to allow devices to establish connections with controllers by switching to the next port if the current port is blocked or non-functional. Default: Disabled
Port Hop	From the drop-down, select **Global**. Click **Off** to allow port hopping on tunnel interface. Default: **On**, which disallows port hopping on tunnel interface. Starting from SD-WAN Manager 20.18.1, this field is deprecated. Instead use the **Full Port Hop** option. See the **Full Port Hop** field.
Low-Bandwidth Link	Click **On** to set the tunnel interface as a low-bandwidth link. Default: **Off**
Tunnel TCP MSS	TCP MSS affects any packet that contains an initial TCP header that flows through the router. When configured, TCP MSS is examined against the MSS exchanged in the three-way handshake. The MSS in the header is lowered if the configured TCP MSS setting is lower than the MSS in the header. If the MSS header value is already lower than the TCP MSS, the packets flow through unmodified. The host at the end of the tunnel uses the lower setting of the two hosts. If the TCP MSS is to be configured, it should be set at 40 bytes lower than the minimum path MTU. Specify the MSS of TPC SYN packets passing through the Cisco IOS XE Catalyst SD-WAN device. By default, the MSS is dynamically adjusted based on the interface or tunnel MTU such that TCP SYN packets are never fragmented. Range: 552 to 1460 bytes. Default: None

Parameter Name	Description
Clear-Dont-Fragment	Configure **Clear-Dont-Fragment** for packets that arrive at an interface that has Don't Fragment configured. If these packets are larger than what MTU allows, they are dropped. If you clear the Don't Fragment bit, the packets are fragmented and sent. Click **On** to clear the Dont Fragment bit in the IPv4 packet header for packets being transmitted out of the interface. When the Dont Fragment bit is cleared, packets larger than the MTU of the interface are fragmented before being sent. **Note** **Clear-Dont-Fragment** clears the Dont Fragment bit and the Dont Fragment bit is set. For packets not requiring fragmentation, the Dont Fragment bit is not affected.
Network Broadcast	From the drop-down, select **Global**. Click **On** to accept and respond to network-prefix-directed broadcasts. Turn this **On** only if the **Directed Broadcast** is enabled on the LAN interface feature template. Default: **Off**
Allow Service	Click **On** or **Off** for each service to allow or disallow the service on the cellular interface.

To configure additional tunnel interface parameters, click **Advanced Options** and configure the following parameters:

Table 12:

Parameter Name	Description
GRE	From the drop-down, select **Global**. Click **On** to use GRE encapsulation on the tunnel interface. By default, GRE is disabled. If you select both IPsec and GRE encapsulations, two TLOCs are created for the tunnel interface that have the same IP addresses and colors, but that differ by their encapsulation.
GRE Preference	From the drop-down, select **Global**. Enter a value to set GRE preference for TLOC. Range: 0 to 4294967295
GRE Weight	From the drop-down, select **Global**. Enter a value to set GRE weight for TLOC. Default: 1
IPsec	From the drop-down, select **Global**. Click **On**to use IPsec encapsulation on the tunnel interface. By default, IPsec is enabled. If you select both IPsec and GRE encapsulations, two TLOCs are created for the tunnel interface that have the same IP addresses and colors, but that differ by their encapsulation.
IPsec Preference	From the drop-down, select **Global**. Enter a value to set the preference for directing traffic to the tunnel. A higher value is preferred over a lower value. Range: 0 through 4294967295. Default: 0

Parameter Name	Description
IPsec Weight	From the drop-down, select **Global**. Enter a value to set weight for balancing traffic across multiple TLOCs. A higher value sends more traffic to the tunnel. Range: 1 through 255. Default: 1
Carrier	From the drop-down, select **Global**. From the **Carrier** drop-down, select the carrier name or private network identifier to associate with the tunnel. Values: carrier1, carrier2, carrier3, carrier4, carrier5, carrier6, carrier7, carrier8, default. Default: default
Bind Loopback Tunnel	Enter the name of a physical interface to bind to a loopback interface. The interface name has the format **ge** *slot*/*port*.
Last-Resort Circuit	From the drop-down, select **Global**. Click **On** to use the tunnel interface as the circuit of last resort. By default, it is disabled. **Note** An interface configured as a circuit of last resort is expected to be down and is skipped while calculating the number of control connections, the cellular modem becomes dormant, and no traffic is sent over the circuit. When the configurations are activated on the edge device with cellular interfaces, then all the interfaces begin the process of establishing control and BFD connections. When one or more of the primary interfaces establishes a BFD connection, the circuit of last resort shuts itself down. Only when all the primary interfaces lose their connections to remote edges, then the circuit of last resort activates itself triggering a BFD TLOC Down alarm and a Control TLOC Down alarm on the edge device. The last resort interfaces are used as backup circuit on edge device and are activated when all other transport links BFD sessions fail. In this mode the radio interface is turned off, and no control or data connections exist over the cellular interface.
NAT Refresh Interval	Set the interval between NAT refresh packets sent on a DTLS or TLS WAN transport connection. Range: 1 through 60 seconds. Default: 5 seconds.
Hello Interval	Enter the interval between Hello packets sent on a DTLS or TLS WAN transport connection. Range: 100 through 10000 milliseconds. Default: 1000 milliseconds (1 second).

Parameter Name	Description
Hello Tolerance	Enter the time to wait for a Hello packet on a DTLS or TLS WAN transport connection before declaring that transport tunnel to be down. Range: 12 through 60 seconds. Default: 12 seconds. The default hello interval is 1000 milliseconds, and it can be a time in the range 100 through 600000 milliseconds (10 minutes). The default hello tolerance is 12 seconds, and it can be a time in the range 12 through 600 seconds (10 minutes). To reduce outgoing control packets on a TLOC, it is recommended that on the tunnel interface you set the hello interval to 60000 milliseconds (10 minutes) and the hello tolerance to 600 seconds (10 minutes) and include the **no track-transport disable** regular checking of the DTLS connection between the edge device and the controller. For a tunnel connection between a edge device and any controller device, the tunnel uses the hello interval and tolerance times configured on the edge device. This choice is made to minimize the traffic sent over the tunnel, to allow for situations where the cost of a link is a function of the amount of traffic traversing the link. The hello interval and tolerance times are chosen separately for each tunnel between a edge device and a controller device. Another step taken to minimize the amount of control plane traffic is to not send or receive OMP control traffic over a cellular interface when other interfaces are available. This behavior is inherent in the software and is not configurable.

c) Configure the cellular interface as a NAT device.

Table 13:

Parameter Name	Description
NAT	Click **On** to have the interface act as a NAT device.
Refresh Mode	Select how NAT mappings are refreshed, either outbound or bidirectional (outbound and inbound). Default: Outbound
UDP Timeout	Specify when NAT translations over UDP sessions time out. Range: 1 through 65536 minutes. Default: 1 minute
TCP Timeout	Specify when NAT translations over TCP sessions time out. Range: 1 through 65536 minutes. Default: 60 minutes (1 hour)
Block ICMP	Select **On** to block inbound ICMP error messages. By default, a router acting as a NAT device receives these error messages. Default: Off
Respond to Ping	Select **On** to have the router respond to ping requests to the NAT interface's IP address that are received from the public side of the connection.

To create a port forwarding rule, click **Add New Port Forwarding Rule** and configure the following parameters. You can define up to 128 port-forwarding rules to allow requests from an external network to reach devices on the internal network.

Table 14:

Parameter Name	Description
Port Start Range	Enter a port number to define the port or first port in the range of interest. Range: 0 through 65535
Port End Range	Enter the same port number to apply port forwarding to a single port, or enter a larger number to apply it to a range of ports. Range: 0 through 65535
Protocol	Select the protocol to which to apply the port-forwarding rule, either TCP or UDP. To match the same ports for both TCP and UDP traffic, configure two rules.
VPN	Specify the private VPN in which the internal server resides. This VPN is one of the VPN identifiers in the overlay network. Range: 0 through 65530
Private IP	Specify the IP address of the internal server to which to direct traffic that matches the port-forwarding rule.

d) Configure a shaping rate to a cellular interface and apply a QoS map, a rewrite rule, access lists, and policers to a router interface.

Table 15: Access Lists Parameters

Parameter Name	Description
Shaping rate	Configure the aggreate traffic transmission rate on the interface to be less than line rate, in kilobits per second (kbps).
QoS map	Specify the name of the QoS map to apply to packets being transmitted out the interface.
Rewrite rule	Click **On**, and specify the name of the rewrite rule to apply on the interface.
Ingress ACL – IPv4	Click **On**, and specify the name of an IPv4 access list to packets being received on the interface.
Egress ACL– IPv4	Click **On**, and specify the name of an IPv4 access list to packets being transmitted on the interface.
Ingress ACL – IPv6	Click **On**, and specify the name of an IPv6 access list to packets being received on the interface.
Egress ACL– IPv6	Click **On**, and specify the name of an IPv6 access list to packets being transmitted on the interface.
Ingress policer	Click **On**, and specify the name of the policer to apply to packets being received on the interface.
Egress policer	Click **On**, and specify the name of the policer to apply to packets being transmitted on the interface.

e) Add ARP table entries.

Table 16:

Parameter Name	Description
IP Address	Enter the IP address for the ARP entry in dotted decimal notation or as a fully qualified host name.
MAC Address	Enter the MAC address in colon-separated hexadecimal notation.

f) Configure other interface properties.

Table 17: Cellular Interfaces Advanced Parameters

Parameter Name	Description
PMTU Discovery	Click **On** to enable path MTU discovery on the interface, to allow the router to determine the largest MTU size supported without requiring packet fragmentation.
TCP MSS	Specify the maximum segment size (MSS) of TPC SYN packets passing through the router. By default, the MSS is dynamically adjusted based on the interface or tunnel MTU such that TCP SYN packets are never fragmented. Range: 552 to 1460 bytes. Default: None.
Clear-Dont-Fragment	Click **On** to clear the Don't Fragment (DF) bit in the IPv4 packet header for packets being transmitted out the interface. When the DF bit is cleared, packets larger than that interface's MTU are fragmented before being sent.
Static Ingress QoS	Select a queue number to use for incoming traffic. Range: 0 through 7
Autonegotiate	Click **Off** to turn off autonegotiation. By default, an interface runs in autonegotiation mode.
TLOC Extension	Enter the name of a physical interface on the same router that connects to the WAN transport. This configuration then binds this service-side interface to the WAN transport. A second router at the same site that itself has no direct connection to the WAN (generally because the site has only a single WAN connection) and that connects to this service-side interface is then provided with a connection to the WAN.
Tracker	Enter the name of a tracker to track the status of transport interfaces that connect to the internet.
IP Directed-Broadcast	From the drop-down, select **Global**. Click **On** for IP directed-broadcast. Default: **Off**

Step 9 Click **Save**.

Reset the profile configuration of a cellular modem

From Cisco IOS XE Catalyst SD-WAN Release 17.18.1a, when you need to switch from one cellular provider to another, you can reset the cellular modem to clear existing profile configurations and apply new settings using the **cellular** slot **lte profile reset** command.

Resetting the profile configuration of a modem prevents remnants of previous carrier settings (such as Access Point Name (APN) or authentication details) from interfering with new configurations, which is vital for successful network attachment and operation.

Procedure

For routers, use the command with a 3-tuple slot identifier. For cellular gateways, the `slot` variable is 1.

Example:

Routers:

```
CellularGateway# cellular 0/2/0 profile-reset
```

Cellular gateways:

```
CellularGateway# cellular 1 profile-reset
```

Troubleshoot LTE modem crash

In the event that an LTE modem crashes, `crash dump` is the information stored in the device bootflash that:

- makes troubleshooting easier by appearing in the admin-tech file
- helps diagnose the cause of the crash

When enabled, this command instructs the device to automatically collect a crash dump from the LTE modem upon a crash event. This dump contains various diagnostic logs and memory states that are essential for analyzing why the modem crashed.

Before you begin

Ensure that the device has sufficient bootflash storage available to accommodate the large amount of data collected.

Procedure

Use the **lte modem crash-action auto-collect** command to automatically gather and store detailed operational data in the event of an LTE modem crash.

What to do next

Use the following command to verify the crash-dump progress.

```
Device#show cellular 0/2/0 logs modem-crashdump
Modem crashdump logging = off
Device#
```

When a crash-dump is in progress, it is displayed as follows:

```
Router#show cellular 0/3/0 logs modem-crashdump
Modem crashdump logging = on
Progress = 44%
Router#
Router#show cellular 0/3/0 logs modem-crashdump
Modem crashdump logging = on
Progress = 98%
Router#show cellular 0/3/0 logs modem-crashdump
Modem crashdump logging = off
```

Once the collection is complete, the status will return to off.