

Introduction to the Secure Firewall ASA

The Secure Firewall ASA provides advanced stateful firewall and VPN concentrator functionality in one device. The ASA includes many advanced features, such as multiple security contexts (similar to virtualized firewalls), clustering (combining multiple firewalls into a single firewall), transparent (Layer 2) firewall or routed (Layer 3) firewall operation, advanced inspection engines, IPsec VPN, SSL VPN, and clientless SSL VPN support, and many more features.

- Hardware and Software Compatibility, on page 1
- VPN Compatibility, on page 1
- New Features, on page 1
- Firewall Functional Overview, on page 8
- VPN Functional Overview, on page 11
- Security Context Overview, on page 12
- ASA Clustering Overview, on page 12
- Special and Legacy Services, on page 12

Hardware and Software Compatibility

For a complete list of supported hardware and software, see Cisco ASA Compatibility.

VPN Compatibility

See Supported VPN Platforms, Cisco ASA Series.

New Features

This section lists new features for each release.

Note New, changed, and deprecated syslog messages are listed in the syslog message guide.

New Features in ASA 9.24(10)

Released: September 21, 2026

Feature	Description
Firewall Features	
Removed support for HTTP cut through proxy. HTTPS cut through proxy remains available.	You can no longer configure cut-through proxy using the HTTP protocol. You must use the secure HTTPS protocol if you use this feature. Cut-through proxy will always use TLS authentication. The following commands have been removed: **aaa authentication listener http** (note that the **https** version remains available), **aaa authentication secure-http-client**.
Simplify Carrier-Grade NAT tracing with predictable port blocks	Introduced deterministic Carrier-Grade NAT (CGNAT), which maps each subscriber to a predefined public IPv4 address and port block instead of assigning ports dynamically for each connection. This helps you reduce NAT logging overhead while making subscriber traceability and troubleshooting easier in large-scale deployments. You configure the feature through the CLI by defining the port block size and assignment algorithm for the NAT policy. New/modified commands: • **nat** (*inside*, *outside*) **source dynamic** *subscriber_object* **pat-pool** *public_pool* **block-allocation deterministic** *block_size* *sequential* | *inverse* | *block-to-net* • **show xlate type deterministic**
High Availability and Scalability Features	
Cluster redirect: flow offload support for the Secure Firewall 6100 asymmetric cluster traffic	For asymmetric flows, cluster redirect lets the forwarding node offload flows to hardware. This feature is enabled by default. When traffic for an existing flow is sent to a different node, then that traffic is redirected to the owner node over the cluster control link. Because asymmetric flows can create a lot of traffic on the cluster control link, letting the forwarder offload these flows can improve performance. New/modified commands • **flow-offload cluster-redirect** • **show conn** • **show flow-offload**
Interface Features	

Feature	Description
Support for configuring multiple DHCPv6 relay link-addresses per interface	ASA DHCPv6 relay agent can now use multiple configured IPv6 interface addresses as relay link-address values in DHCPv6 RELAY-FORWARD messages. This support provides the flexibility for the DHCPv6 server to choose the appropriate address pool by matching the client's prefix. New/modified commands: • **ipv6 dhcp relay link-address** *ipv6_address* • **show ipv6 dhcprelay interface**
License Features	
Unlimited performance tier (ASAvU) for AWS	ASA Virtual for AWS now supports an unlimited performance tier (ASAvU). Supported vCPU and memory configuration: • 32 vCPU and 64 GB RAM • 64 vCPU and 128 GB RAM
VPN Features	
Distributed site-to-site VPN with inter-site clustering	Distributed VPN support for inter-site clustering enables seamless site-to-site VPN session continuity across geographically dispersed sites. This feature enhances high availability by maintaining both local and remote backups for IKEv2/IPsec traffic during member or site failures. New/modified commands: • **cluster redistribute vpn-sessiondb** • **show cluster vpn-sessiondb** • **vpn-mode** • **show cluster resource usage** • **show vpn-sessiondb** • **show conn detail** • **show crypto ikev2 stats**
IPsec flow offload for traffic on the cluster control link on the Secure Firewall 6100 in distributed site-to-site VPN mode	For asymmetric flows in distributed site-to-site VPN mode, IPsec flow offload now lets the flow owner decrypt IPsec traffic in hardware that was forwarded over the cluster control link. This feature is not configurable and is always available when you enable IPsec flow offload. New/modified commands: **show crypto ipsec sa detail**

New Features in ASA 9.24(1)

Released: December 3, 2025

Feature	Description
Platform Features	
Secure Firewall 220	The Secure Firewall 220 is an affordable security appliance for branch offices and remote locations, balancing cost and features.
Secure Firewall 6160, 6170	The Secure Firewall 6160 and 6170 are ultra-high-end firewalls for demanding data center and telecom networks. It has exceptional price-to-performance, modular capability, and high throughput.
ASA VirtualGrub bootloader upgraded with UEFI firmware and secure boot.	With the Grub bootloader upgrade from Grub 0.94 to Grub 2.12, we now support UEFI firmware with or without secure boot functionality, along with legacy BIOS mode. Secure boot functionality gives boot-level malware protection. New deployments also use GPT-partitioned images instead of MS-DOS-partitioned disks. If you upgrade, you cannot change to UEFI and secure boot; only new deployments can use the new options. **Note** After upgrading to 9.24, you cannot downgrade to an earlier version. To upgrade to later versions, you must first upgrade to 9.24.
ASA Virtual AWS dual-arm clustering	In dual-arm mode, after inspection, the ASA Virtual will NAT and forward outbound traffic from its outside interface directly to the internet via the Internet Gateway. Since outbound traffic is directly forwarded to the internet after inspection without making a round trip through the GWLB and the GWLB endpoint, the number of traffic hops is reduced by 2. This reduction is especially useful in providing a common egress path for a multi-VPC deployment.For dual-arm deployments, only egress traffic is supported.
ASA Virtual GCP clustering with autoscale	GCP clustering with autoscale is now supported for ASAv30, ASAv50, and ASAv100.
ASA VirtualOCI Ampere A1 ARM compute shape support	New shapes for OCI. **Note** For ASA Virtual on OCI, Arm instances may experience reduced throughput on legacy hypervisors (especially with SR-IOV enabled)—See https://docs.oracle.com/en-us/iaas/Content/Compute/known-issues.htm for more information. Contact OCI for support.
ASA VirtualKVM flow offload	Flow offload is now supported on the DPU for KVM.
ASA Virtual Nutanix support for AOS 6.8	Nutanix AOS 6.8 supports VPCs, similar toVPCs in public clouds.
ASA Virtual OpenStack support for Caracal	ASA Virtual deployment is supported on the Caracal release of OpenStack.

Feature	Description
ASA Virtual MANA NIC Support	ASA Virtual supports MANA NIC hardware on Microsoft Azure for the following instances: • Standard_D8s_v5 • Standard_D16s_v5
ASA Virtual on VMware ESXi support	ESXi versions 8.0, 9.0, and 9.1 are supported on ASA Virtual 9.24(1) and later versions.
Firewall Features	
Application Visibility and Control for the Secure Firewall 6100	Application Visibility and Control (AVC) makes it possible for you to write access control rules based on applications rather than just IP addresses and ports. AVC downloads the Vulnerability Database (VDB), which creates network-service objects and groups that you can use in access control rules. The objects define various applications, and the groups define application categories, so you can easily block applications or entire classes of connections without specifying IP address and port. We introduced or modified the following commands: **avc**, **avc download vdb**, **clear avc**, **clear object-group**, **network-service reload**, **show avc**, **show service-policy**. In addition, you can no longer enter the **app-id** command as part of a network-service object definition. Supported platforms: Secure Firewall 6100
High Availability and Scalability Features	
No reboot required for changing the VPN mode	When changing the VPN mode between distributed and centralized, a reboot is no longer required. However, you now need to disable clustering on all nodes before changing the mode.
Data nodes can join the cluster concurrently	Formerly, the control node only allowed one data node to join the cluster at a time. If the configuration sync takes a long time, data nodes can take a long time to join. Concurrent join is enabled by default. If you have NAT and VPN distributed mode enabled, you cannot use concurrent join. Added/modified commands: **concurrent-join**, **show cluster info concurrent-join incompatible-config**
MTU ping test on cluster node join provides more information by trying smaller MTUs	When a node joins the cluster, it checks MTU compatibility by sending a ping to the control node with a packet size matching the cluster control link MTU. If the ping fails, it tries the MTU divided by 2 and keeps dividing by 2 until an MTU ping is successful. The successful ping value is shown in **show cluster info trace** so you can fix the MTU to a working value and try again. Even if the ping fails, the node is allowed to join the cluster. In this case, you need to resolve the MTU mismatch as soon as possible. We recommend increasing the switch MTU size to the recommended value, but if you can't change the switch configuration, a working value for the cluster control link will let you form the cluster. Added/modified commands: **show cluster info trace**, **show cluster history**.

Feature	Description
Improved cluster control link health check with high CPU	When a cluster node CPU usage is high, the health check will be suspended, and the node will not be marked as unhealthy. You can configure at what CPU use threshold to suspend the health check. Added/modified commands: **cpu-healthcheck-threshold**.
Clustering on the Secure Firewall 6100	You can cluster up to 4 Secure Firewall 6100 nodes in Spanned EtherChannel or Individual interface mode.
Block depletion monitoring in clustering	When block depletion occurs, the ASA collects troubleshooting logs and sends out a syslog. For clustering, the node will leave the cluster so that the other nodes can handle the traffic. The ASA can also force a crash and reload to recover from depletion. Added/modified commands: **fault-monitor**, **block-depletion**, **block-depletion recovery-action**, **block-depletion monitor-interval**.
Dynamic PAT support for distributed site-to-site VPN mode	Distributed mode now supports dynamic PAT. However, interface PAT is still not supported.
SNMP enhancements	This release includes SNMP enhancements to improve the polling experience for ENTITY-MIB and IF-MIB. These improvements are specific to the Secure Firewall 4200 and Secure Firewall 6100 series platforms.
Interface Features	
Recursive DNS Server (RDNSS) and DNS Search List (DNSSL) options to advertise a list of DNS servers and domains to IPv6 clients	You can now configure Recursive DNS Server (RDNSS) and DNS Search List (DNSSL) options to provide DNS servers and domains to SLAAC clients using router advertisements. New/modified commands: **ipv6 nd ra dns-search-list domain**, **ipv6 nd ra dns server**, **show ipv6 nd detail**, **show ipv6 nd ra dns-search-list**, **show ipv6 nd ra dns server**, **show ipv6 nd summary**
Administrative, Monitoring, and Troubleshooting Features	
SSH X.509 certificate authentication	You can now use an X.509v3 certificate to authenticate a user for SSH (RFC 6187). New/Modified commands: **aaa authorization exec ssh-x509**, **ssh authentication method**, **ssh trustpoint sign**, **ssh username-from-certificate**, **validation-usage ssh-client** *Also in 9.20(4), 9.22(3).*
AES-256-GCM SSH cipher	The ASA supports the AES-256-GCM cipher for SSH. It is enabled by default for **all** and **high** encryption levels. New/Modified commands: **ssh cipher encryption** *Also in 9.20(4), 9.22(3).*
Message-of-the-day (motd) banner shows the failover state and the last failover time	When using failover, if you configure the **banner motd** command, then the banner shows information about the failover state and the last failover time of the unit you are logging into. This information is useful if you are performing actions at the CLI, such as troubleshooting, and a failover occurs between sessions. New or modified commands: **banner motd** *Also in 9.22(3).*

Feature	Description
Display of UDP's initiator and responder values in connection status output	For UDP traffic flows, the ASA displays the initiator and responder field values in the connection detail status. These field values indicate the direction of communication, which helps in troubleshooting network connectivity issues. New/Modified commands: **show conn detail** *Also in 9.20(1).*
Linux kernel crash dump	The Linux kernel crash dump feature lets you debug kernel crash events and find the root cause. This feature is enabled by default. New/Modified commands: **show kernel crash-dump**, **kernel crash-dump**, **crashinfoforce kernel-dump**
Root Shell Access Support Using Consent Token on ASA Virtual	ASA Virtual supports a new Consent Token mechanism that allows authorized users to obtain one-time access to the Linux root shell for troubleshooting or diagnostic purposes — without requiring the administrator password. New/Modified commands: **consent-token generate-challenge shell-access**, **consent-token accept-response shell-access**
ASDM Features	
ASDM certificate authentication	ASDM Launcher 1.9(10), which comes with ASDM 7.24, now supports user certificate authentication. Previously, this feature was only supported with Java Web Start (discontinued in 7.18). Because the ASA commands were not deprecated in 9.18, you can configure earlier ASA versions to use certificate authentication when using any ASDM version with ASDM Launcher 1.9(10). New/Modified commands: **http authentication-certificate**, **http username-from-certificate** New/Modified screens: • ASDM Launcher login window.
VPN Features	
SGT over VTI	VTI tunnels now support Cisco TrustSec SGT tags. New/Modified commands: **cts manual**, **propagate sgt**, **policy static sgt**
ECMP and BFD fault detection support for VTIs	One or more dynamic VTI interfaces can be part of an Equal-Cost Multi-Path (ECMP) zone. Using zones, traffic towards the spoke can be load-balanced. Bidirectional Forwarding Detection (BFD) link detection is faster, detecting faulty VTI links in few milliseconds or microseconds. New/Modified commands: **bfd template**, **vtemplate-bfd**, **vtemplate-zone-member**, **show zone**, **show conn all**, **show route**
Loopback interface support for distributed site-to-site VPN	You can now create site-to-site VPN tunnels using loopback interfaces in distributed site-to-site mode. Unlike outside addresses that are tied to a location network, the loopback interfaces are not. This independence means you can move the address to another cluster and use routing protocols to propagate the new location to the upstream routers. The peer's traffic would then be sent to the new location.

Feature	Description
IPsec flow offload and DTLS crypto accelerator for the Secure Firewall 6100	Secure Firewall 6100 supports AES-GCM-128 and AES-GCM-256 ciphers only.
IPsec flow offload for the ASA Virtual on KVM	IPsec flow offload is now supported on the DPU for KVM.

Firewall Functional Overview

Firewalls protect inside networks from unauthorized access by users on an outside network. A firewall can also protect inside networks from each other, for example, by keeping a human resources network separate from a user network. If you have network resources that need to be available to an outside user, such as a web or FTP server, you can place these resources on a separate network behind the firewall, called a *demilitarized zone* (DMZ). The firewall allows limited access to the DMZ, but because the DMZ only includes the public servers, an attack there only affects the servers and does not affect the other inside networks. You can also control when inside users access outside networks (for example, access to the Internet), by allowing only certain addresses out, by requiring authentication or authorization, or by coordinating with an external URL filtering server.

When discussing networks connected to a firewall, the *outside* network is in front of the firewall, the *inside* network is protected and behind the firewall, and a *DMZ*, while behind the firewall, allows limited access to outside users. Because the ASA lets you configure many interfaces with varied security policies, including many inside interfaces, many DMZs, and even many outside interfaces if desired, these terms are used in a general sense only.

Security Policy Overview

A security policy determines which traffic is allowed to pass through the firewall to access another network. By default, the ASA allows traffic to flow freely from an inside network (higher security level) to an outside network (lower security level). You can apply actions to traffic to customize the security policy.

Permitting or Denying Traffic with Access Rules

You can apply access rules to limit traffic from inside to outside, or allow traffic from outside to inside. For bridge group interfaces, you can also apply an EtherType access rule to allow non-IP traffic.

Applying NAT

Some of the benefits of NAT include the following:

- You can use private addresses on your inside networks. Private addresses are not routable on the Internet.
- NAT hides the local addresses from other networks, so attackers cannot learn the real address of a host.
- NAT can resolve IP routing problems by supporting overlapping IP addresses.

Protecting from IP Fragments

The ASA provides IP fragment protection. This feature performs full reassembly of all ICMP error messages and virtual reassembly of the remaining IP fragments that are routed through the ASA. Fragments that fail the security check are dropped and logged. Virtual reassembly cannot be disabled.

Applying HTTP, HTTPS, or FTP Filtering

Although you can use access lists to prevent outbound access to specific websites or FTP servers, configuring and managing web usage this way is not practical because of the size and dynamic nature of the Internet.

You can configure Cloud Web Security on the ASA. You can also use the ASA in conjunction with an external product such as the Cisco Web Security Appliance (WSA).

Applying Application Inspection

Inspection engines are required for services that embed IP addressing information in the user data packet or that open secondary channels on dynamically assigned ports. These protocols require the ASA to do a deep packet inspection.

Applying QoS Policies

Some network traffic, such as voice and streaming video, cannot tolerate long latency times. QoS is a network feature that lets you give priority to these types of traffic. QoS refers to the capability of a network to provide better service to selected network traffic.

Applying Connection Limits and TCP Normalization

You can limit TCP and UDP connections and embryonic connections. Limiting the number of connections and embryonic connections protects you from a DoS attack. The ASA uses the embryonic limit to trigger TCP Intercept, which protects inside systems from a DoS attack perpetrated by flooding an interface with TCP SYN packets. An embryonic connection is a connection request that has not finished the necessary handshake between source and destination.

TCP normalization is a feature consisting of advanced TCP connection settings designed to drop packets that do not appear normal.

Enabling Threat Detection

You can configure scanning threat detection and basic threat detection, and also how to use statistics to analyze threats.

Basic threat detection detects activity that might be related to an attack, such as a DoS attack, and automatically sends a system log message.

A typical scanning attack consists of a host that tests the accessibility of every IP address in a subnet (by scanning through many hosts in the subnet or sweeping through many ports in a host or subnet). The scanning threat detection feature determines when a host is performing a scan. Unlike IPS scan detection that is based on traffic signatures, the ASA scanning threat detection feature maintains an extensive database that contains host statistics that can be analyzed for scanning activity.

The host database tracks suspicious activity such as connections with no return activity, access of closed service ports, vulnerable TCP behaviors such as non-random IPID, and many more behaviors.

You can configure the ASA to send system log messages about an attacker or you can automatically shun the host.

Firewall Mode Overview

The ASA runs in two different firewall modes:

- Routed
- Transparent

In routed mode, the ASA is considered to be a router hop in the network.

In transparent mode, the ASA acts like a “bump in the wire,” or a “stealth firewall,” and is not considered a router hop. The ASA connects to the same network on its inside and outside interfaces in a "bridge group".

You might use a transparent firewall to simplify your network configuration. Transparent mode is also useful if you want the firewall to be invisible to attackers. You can also use a transparent firewall for traffic that would otherwise be blocked in routed mode. For example, a transparent firewall can allow multicast streams using an EtherType access list.

Routed mode supports Integrated Routing and Bridging, so you can also configure bridge groups in routed mode, and route between bridge groups and regular interfaces. In routed mode, you can replicate transparent mode functionality; if you do not need multiple context mode or clustering, you might consider using routed mode instead.

Stateful Inspection Overview

All traffic that goes through the ASA is inspected using the Adaptive Security Algorithm and either allowed through or dropped. A simple packet filter can check for the correct source address, destination address, and ports, but it does not check that the packet sequence or flags are correct. A filter also checks *every* packet against the filter, which can be a slow process.



Note The TCP state bypass feature allows you to customize the packet flow.

A stateful firewall like the ASA, however, takes into consideration the state of a packet:

- Is this a new connection?

  If it is a new connection, the ASA has to check the packet against access lists and perform other tasks to determine if the packet is allowed or denied. To perform this check, the first packet of the session goes through the “session management path,” and depending on the type of traffic, it might also pass through the “control plane path.”

  The session management path is responsible for the following tasks:

  - Performing the access list checks
  - Performing route lookups
  - Allocating NAT translations (xlates)
  - Establishing sessions in the “fast path”

The ASA creates forward and reverse flows in the fast path for TCP traffic; the ASA also creates connection state information for connectionless protocols like UDP, ICMP (when you enable ICMP inspection), so that they can also use the fast path.



Note For other IP protocols, like SCTP, the ASA does not create reverse path flows. As a result, ICMP error packets that refer to these connections are dropped.

Some packets that require Layer 7 inspection (the packet payload must be inspected or altered) are passed on to the control plane path. Layer 7 inspection engines are required for protocols that have two or more channels: a data channel, which uses well-known port numbers, and a control channel, which uses different port numbers for each session. These protocols include FTP, H.323, and SNMP.

- Is this an established connection?

  If the connection is already established, the ASA does not need to re-check packets; most matching packets can go through the "fast" path in both directions. The fast path is responsible for the following tasks:

  - IP checksum verification
  - Session lookup
  - TCP sequence number check
  - NAT translations based on existing sessions
  - Layer 3 and Layer 4 header adjustments

  Data packets for protocols that require Layer 7 inspection can also go through the fast path.

  Some established session packets must continue to go through the session management path or the control plane path. Packets that go through the session management path include HTTP packets that require inspection or content filtering. Packets that go through the control plane path include the control packets for protocols that require Layer 7 inspection.

VPN Functional Overview

A VPN is a secure connection across a TCP/IP network (such as the Internet) that appears as a private connection. This secure connection is called a tunnel. The ASA uses tunneling protocols to negotiate security parameters, create and manage tunnels, encapsulate packets, transmit or receive them through the tunnel, and unencapsulate them. The ASA functions as a bidirectional tunnel endpoint: it can receive plain packets, encapsulate them, and send them to the other end of the tunnel where they are unencapsulated and sent to their final destination. It can also receive encapsulated packets, unencapsulate them, and send them to their final destination. The ASA invokes various standard protocols to accomplish these functions.

The ASA performs the following functions:

- Establishes tunnels
- Negotiates tunnel parameters
- Authenticates users

- Assigns user addresses
- Encrypts and decrypts data
- Manages security keys
- Manages data transfer across the tunnel
- Manages data transfer inbound and outbound as a tunnel endpoint or router

The ASA invokes various standard protocols to accomplish these functions.

Security Context Overview

You can partition a single ASA into multiple virtual devices, known as security contexts. Each context is an independent device, with its own security policy, interfaces, and administrators. Multiple contexts are similar to having multiple standalone devices. Many features are supported in multiple context mode, including routing tables, firewall features, IPS, and management; however, some features are not supported. See the feature chapters for more information.

In multiple context mode, the ASA includes a configuration for each context that identifies the security policy, interfaces, and almost all the options you can configure on a standalone device. The system administrator adds and manages contexts by configuring them in the system configuration, which, like a single mode configuration, is the startup configuration. The system configuration identifies basic settings for the ASA. The system configuration does not include any network interfaces or network settings for itself; rather, when the system needs to access network resources (such as downloading the contexts from the server), it uses one of the contexts that is designated as the admin context.

The admin context is just like any other context, except that when a user logs into the admin context, then that user has system administrator rights and can access the system and all other contexts.

ASA Clustering Overview

ASA Clustering lets you group multiple ASAs together as a single logical device. A cluster provides all the convenience of a single device (management, integration into a network) while achieving the increased throughput and redundancy of multiple devices.

You perform all configuration (aside from the bootstrap configuration) on the control unit only; the configuration is then replicated to the member units.

Special and Legacy Services

For some services, documentation is located outside of the main configuration guides and online help.

Special Services Guides

Special services allow the ASA to interoperate with other Cisco products; for example, by providing a security proxy for phone services (Unified Communications), or by providing Botnet traffic filtering in conjunction with the dynamic database from the Cisco update server, or by providing WCCP services for the Cisco Web Security Appliance. Some of these special services are covered in separate guides:

- Cisco ASA Botnet Traffic Filter Guide
- Cisco ASA NetFlow Implementation Guide
- Cisco ASA Unified Communications Guide
- Cisco ASA WCCP Traffic Redirection Guide
- SNMP Version 3 Tools Implementation Guide

Legacy Services Guide

Legacy services are still supported on the ASA, however there may be better alternative services that you can use instead. Legacy services are covered in a separate guide:

Cisco ASA Legacy Feature Guide

This guide includes the following chapters:

- Configuring RIP
- AAA Rules for Network Access
- Using Protection Tools, which includes Preventing IP Spoofing (**ip verify reverse-path**), Configuring the Fragment Size (**fragment**), Blocking Unwanted Connections (**shun**), Configuring TCP Options (for ASDM), and Configuring IP Audit for Basic IPS Support (**ip audit**).
- Configuring Filtering Services