Cisco IP Phone 7800 Release Notes for Firmware Release 14.3(1)SR3

First Published: 2025-05-22

Cisco IP Phone 7800 Release Notes for Firmware Release 14.3(1)SR3

These release notes support the Cisco IP Phones 7811, 7821, 7841, and 7861 running SIP Firmware Release 14.3(1)SR3.

The following table lists the support compatibility for the Cisco IP Phones.

Table 1: Cisco IP Phones, Cisco Unified Communications Manager, and Firmware Release Compatibility

Cisco IP Phone	Cisco Unified Communications Manager
Cisco IP Phones 7811, 7821, 7841, and 7861	Cisco Unified Communications Manager version 8.5(1) and later Cisco Unified Communications Manager DST Olsen version D or later SRST 8.0 (IOS load 15.1(1)T) and above
Cisco IP Phones 7811, 7821, 7841, and 7861	CME 10.0 (IOS load 15.3(3)M)
Cisco IP Phones 7811, 7821, 7841, and 7861	Cisco Expressway X8.7 or Cisco TelePresence Video Communication Server X8.7 (for Mobile and Remote Access)

Related Documentation

Use the following sections to obtain related information.

Cisco IP Phone 7800 Series Documentation

Find documentation specific to your language, phone model, and call control system on the product support page for the Cisco IP Phone 7800 Series.

Cisco Unified Communications Manager Documentation

See the *Cisco Unified Communications Manager Documentation Guide* and other publications that are specific to your Cisco Unified Communications Manager release on the product support page.

New and Changed Features

This release contains the following features for EU RED DA (Radio Equipment Directive Delegated Act) compliance:

- Min TLS version (default is 1.2) for server and client on phone
- Transition of PRT log uploads over HTTPS for CUCM
- Special user events logging for privacy assets, including the following:

SSH	Successful login/logout Rejected login attempt Service on/off
Web	Service on /off
Personal directory	Create/Update/Delete on phone UI or web
Call history	Delete on phone UI or web
PIN on phone UI	Successful unlock Rejected unlock attempt

TLS Client Min Version

Now the phone that acts as a TLS client can require the minimum TLS version to establish a TLS connection. By default, the TLS min version for the phone is TLS 1.2.

To use this feature, configure the field **TLS Client Min Version** under the section **Product Specific Configuration Layout** on Unified CM.

In addition, the default value of **Disable TLS 1.0 and TLS 1.1 for Web Access** is changed from **Disabled** to **Enabled**.

Where to Find More Information

- *Cisco IP Phone 7800 Series Administration Guide for Cisco Unified Communications Manager*

Installation

Installation Requirements

Before you install the firmware release, you must ensure that your Cisco Unified Communications Manager is running the latest device package. For more information about how to install a Unified CM device package, see Cisco Unified Communications Manager Device Package Installation Guide.

Note If your Cisco Unified Communications Manager doesn't have the required device package to support this firmware release, the firmware may not work correctly.

For information on the device packages, see the Cisco Unified Communications Manager Device Package Compatibility Matrix.

Install the Firmware Release on Cisco Unified Communications Manager

You must install the latest Cisco Unified Communications Manager firmware on all Cisco Unified Communications Manager servers in the cluster.

Procedure

Step 1 Go to the Software Download page for the IP Phone 7800 Series.

Step 2 Choose your phone model.

Step 3 Choose **Session Initiation Protocol (SIP) Software**.

Step 4 In the Latest Release folder, choose **14.3(1)SR3**.

Step 5 Select the firmware file, click the **Download** or **Add to Cart** button, and follow the prompts.

The firmware filename is cmterm-78xx.14-3-1-0301-349.k4.cop.sha512.

Note
If you added firmware to the cart, when you are ready to download the files, click the Cart and then click **Download All**.

Step 6 Click the + next to the firmware file name in the File Information section to access more information about this file.

Step 7 Click the Readme link to open the installation instructions for the firmware.

Step 8 Follow the instructions in the Readme file to install the firmware.

Install the Firmware Zip Files

If a Cisco Unified Communications Manager is not available to load the installer program, the following zip file is available to load the firmware cmterm-78xx.14-3-1-0301-349.zip.

Procedure

Step 1 Go to the Software Download page for the IP Phone 7800 Series.

Step 2 Choose your phone model.

Step 3 Choose **Session Initiation Protocol (SIP) Software**.

Step 4 In the Latest Release folder, choose **14.3(1)SR3**.

Step 5 Select the firmware file, click the **Download** or **Add to Cart** button, and follow the prompts.

The firmware filename is cmterm-78xx.14-3-1-0301-349.zip.

Note
If you added firmware to the cart, when you are ready to download the files, click the Cart and then click **Download All**.

Step 6 Unzip the files.

Step 7 Manually copy the unzipped files to the directory on the TFTP server. For more information about how to manually copy the firmware files to the server, see the *Cisco Unified Communications Operating System Administration Guide*.

Limitations and Restrictions

Phone Behavior During Times of Network Congestion

Anything that degrades network performance can affect phone audio and, in some cases, can cause a call to drop. Sources of network degradation can include, but are not limited to, the following activities:

- Administrative tasks, such as an internal port scan or security scan.
- Attacks that occur on your network, such as a Denial of Service attack.

Health-Care Environment Use

This product is not a medical device and uses an unlicensed frequency band that is susceptible to interference from other devices or equipment.

On-Hook Transfer Limitation in SIP Phones

When the Cisco Unified Communications Manager **Transfer On-Hook Enabled** field is enabled, users might report a problem with direct call transfer in SIP phones. If the user transfers the call and immediately goes on hook before they hear the ring signal, the call may drop instead of being transferred.

The user needs to hear the ring signal so that they can be sure that the call is being routed.

Language Limitation

There is no localized Keyboard Alphanumeric Text Entry (KATE) support for the following Asian locales:

- Chinese (China)
- Chinese (Hong Kong)
- Chinese (Taiwan)
- Japanese (Japan)
- Korean (Korea Republic)

The default English (United States) KATE is presented to the user instead.

For example, the phone screen will show text in Korean, but the **2** key on the keypad will display **a b c 2 A B C**.

Softkey Templates and Video Mode

You can't configure softkey templates for Video mode on the Cisco IP Phone 7800 Series phones. If a softkey appears on the phone, then it will not function correctly.

Downgrade limitation for phones with multiple lines

If the phone firmware is downgraded from the version 14.3(1) or higher to a version below 14.3(1), the loss of ringtone association might occur. Typically, this issue occurs on the phone with multiple lines configured.

To resolve the issue when it occurs, perform a factory reset on the phone.

Customized Ringtone Settings

After you upgrade the firmware to one of the following releases, the previously customized ringtone settings will be lost:

- 14.3(1)
- 14.3(1)SR1
- 14.3(1)SR2
- 14.3(1)SR3

Caveats

View Caveats

You can search for caveats using the Cisco Bug Search Tool.

Known caveats (bugs) are graded according to severity level, and can be either open or resolved.

Before you begin

To view caveats, you need the following items:

- Internet connection
- Web browser
- Cisco.com user ID and password

Procedure

Step 1 Perform one of the following actions:

- Use this URL for all caveats: https://bst.cloudapps.cisco.com/bugsearch/search?kw=&pf=prdNm&pfVal=284883944&rls=14.3(1)SR2&sb=anfr&svr=3nH&bt=custV
- Use this URL for all open caveats: https://bst.cloudapps.cisco.com/bugsearch/search?kw=&pf=prdNm&pfVal=284883944&rls=14.3(1)SR2&sb=afr&sts=open&svr=3nH&bt=custV
- Use this URL for all resolved caveats: https://bst.cloudapps.cisco.com/bugsearch/search?kw=*&pf=prdNm&pfVal=284883944&rls=14.3(1)SR2&sb=fr&svr=3nH&bt=custV

Step 2 When prompted, log in with your Cisco.com user ID and password.

Step 3 (Optional) Enter the bug ID number in the Search For field, then press **Enter**.

Open Caveats

The following list contains a snapshot of the severity 1, 2, and 3 caveats that are open for the Cisco IP Phone 7800 Series for Firmware Release 14.3(1)SR3.

For more information about an individual caveat, access the Bug Search Tool and search for the caveat using the bug ID number. You must be a registered Cisco.com user to access this online information.

Because bug status continually changes, the list reflects a snapshot of the bugs that were open at the time this report was compiled. For an updated view of open caveats, access the Bug Search Tool as described in View Caveats, on page 5.

- CSCvi99439: CME service URL throws XML error in 78xx
- CSCvs26183: 78xx phone aux port upgrade 56x without headset need 22mins
- CSCwa12226: Sometimes the DN will remain or disappear after login/logout the EMCC service

Resolved Caveats

This release doesn't resolve any issues.

Application Programming Interface

Cisco supports phone API utilization by 3rd party applications that have been tested and certified through Cisco by the 3rd party application developer. Any phone issues related to uncertified application interaction must be addressed by the 3rd party and will not be addressed by Cisco.

For support model of Cisco certified 3rd party applications/solutions, please refer to Cisco Solution Partner Program website for details.

Cisco Unified Communication Manager Public Keys

To improve software integrity protection, public keys are used to sign cop files for Cisco Unified Communications Manager Release 10.0.1 and later. These cop files have “k3 or k4” in their name. To install a k3 or k4 cop file on a pre-10.0.1 Cisco Unified Communications Manager, consult the Readme for the ciscocm.version3-keys.cop.sgn to determine if you must install this additional cop file on your specific Cisco Unified Communications Manager version. If these keys are not present and are required, you will see the error “The selected file is not valid” when you try to install the software package.

Unified Communications Manager Endpoints Locale Installer

By default, Cisco IP Phones are set up for the English (United States) locale. To use the Cisco IP Phones in other locales, you must install the locale-specific version of the Unified Communications Manager Endpoints Locale Installer on every Cisco Unified Communications Manager server in the cluster. The Locale Installer installs the latest translated text for the phone user interface and country-specific phone tones on your system so that they are available for the Cisco IP Phones.

To access the Locale Installer required for a release, access the Software Download page, navigate to your phone model, and select the Unified Communications Manager Endpoints Locale Installer link.

For more information, see the documentation for your particular Cisco Unified Communications Manager release.

Note The latest Locale Installer may not be immediately available; continue to check the website for updates.

Cisco IP Phone Documentation Updates on Cisco Unified Communications Manager

The Cisco Unified Communications Manager Self Care Portal (Release 10.0 and later) and User Options web pages (Release 9.1 and earlier) provide links to the IP Phone user guides in PDF format. These user guides are stored on the Cisco Unified Communications Manager and are up to date when the Cisco Unified Communications Manager release is first made available to customers.

After a Cisco Unified Communications Manager release, subsequent updates to the user guides appear only on the Cisco website. The phone firmware release notes contain the applicable documentation URLs. In the web pages, updated documents display “Updated” beside the document link.

Note The Cisco Unified Communications Manager Device Packages and the Unified Communications Manager Endpoints Locale Installer do not update the English user guides on the Cisco Unified Communications Manager.

You and your users should check the Cisco website for updated user guides and download the PDF files. You can also make the files available to your users on your company website.

Tip You may want to bookmark the web pages for the phone models that are deployed in your company and send these URLs to your users.

Cisco IP Phone Firmware Support Policy

For information on the support policy for phones, see the Cisco IP Phone Firmware Support Policy.

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED “AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses and phone numbers are listed on the Cisco website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/c/en/us/about/legal/trademarks.html. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2025 Cisco Systems, Inc. All rights reserved.